INCH-POUND

A-A-55230
23 September 1993

COMMERCIAL ITEM DESCRIPTION

SLACKS, WOMEN'S HOSPITAL DUTY UNIFORM (HDU)

The General Services Administration has authorized the use of this commercial item description in preference to MIL-S-44292.

Abstract. This commercial item description covers women's slacks made of twill weave, polyester/cotton cloth. They are intended to be worn as a hospital duty or food handler uniform by female personnel of the Department of Defense.

Salient characteristics. The straight leg hemmed slacks shall have a slide fastener fly front with a snap fastener, elasticized waist and 2 back darts facing towards the seat seam. The legs shall be pressed and creased in the center with the seams matching at bottom and in the crotch. All seams shall be overedged.

Material. The basic material shall be a 2/1 left-hand twill cloth that is a blend of 65 ± 5 percent polyester. The remaining percentage shall be combed and carded cotton, spun into singles yarn. The cloth shall be desized, scoured, mercerized, bleached, heat-set, and treated with a durable press finish. The material shall conform to the requirements specified in Table I.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FSSC, 2800 South 20th Street, Philadelphia, PA 19101-8419, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 8410

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

TABLE I. - Physical requirements

Characteristic	Requirement (Minimum)	Test Method
Weight (min.)	6.8 oz./sq. yd.	ASTM-D 3776 Option C
Yarns per inch (min.)		
Warp	116	ASTM-D 3775
Filling	47	ASTM-D 3775
Colorfastness to:		
Laundering (after 3 cycles)	Class 4 1/ 4/ 5/	AATCC 61 Test 3A
Perspiration	Class 4	AATCC 15
Light	"Good" 2/ 4/ 5/	AATCC 16A
Breaking strength (lbs. min.)		
Warp	170 lbs. (min.)	ASTM-D 5034
Filling	120 lbs. (min.)	"
Tearing strength (min.)		
Warp	5.0	ASTM-D 1424
Filling	4.5	"
Dimensional stability	±2% in either direction 6/	AATCC 135
Seam efficiency	80% (min.) 3/	FED-STD-191 TM-5110
Appearance Rating	DP 3.0 rating 6/ 7/	AATCC 124 Washing method IV Drying method A
pH	5.0 - 8.5	ASTM-D 2165-90

1/ The specimen shall be dried after each of the laundering cycles. Ten steel balls and multifiber test fabric shall be used.
2/ Exposure time shall be 40 hours.
3/ The needle shall measure 0.36 ± 0.001 inch across the blade of the eye. The thread used for this test shall conform to A-A-50199, ticket numbers 50, 2 ply for the top (needle) thread and ticket number 70, 2 ply for bottom (looper) thread.
4/ Evaluate color change of the test specimens using AATCC grey scale for color change.
5/ Or shall show colorfastness equal to the standard sample.
6/ Machine cycle 3, wash temp 3, dry-Aiii, and procedure-p.H 6/1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

7/ The minimum appearance rating after five launderings.

Color. The cloth shall be bleached optical white with a resulting peak emission in the blue violet region. The use of dyes and compounds containing elementary sulfur capable of oxidation to sulfuric acid is prohibited. A certificate of compliance shall be submitted and shall be acceptable for this requirement.

Thread. The sewing thread shall be white, cotton-covered, or polyester-covered polyester, ticket numbers 70 and 50, conforming to A-A-50199.

Slide fasteners. The slide fastener shall be polyester, continuous monofilament, (spiral or serpentine), nonseparating, nonreversible, and medium size with an automatic lock, open top stop, and closed bottom stop. The length shall be 5-1/2 inches for all sizes. The color of the tape shall be white with matching chain, slider, pull and stops.

Snap fasteners. The snap fastener shall be a small wire spring clamp type. The female components shall consist of a button, size 1 or 2, and a socket. The male component shall consist of a stud, and an eyelet, size 1, 2, 3, or 4, or a stud-eyelet combination, size 1, 2, or 3. The cap surface shall be coated with white enamel. The components will be firmly engaged when snapped on the appropriate studs and still permit disengagement or snapping off with a reasonable, properly applied force. The complete fastener shall be of one manufacturer's construction only.

Elastic webbing. The natural color elastic shall be 1-1/2 inches wide with a weight of 1.50 oz. per linear yard, when tested in accordance with ASTM D-3776. The webbing shall have suitable elongation for the intended purpose. Shuttleless-loom elastic webbing is permitted, style G1853 (Elastic Corporation of America), and style K103 (Uniweb, Inc.) may be used.

Sizes and lengths. The slacks shall be provided in the following sizes and lengths:

X-short	6	8	10	12	14	16	18	20		
Short	6	8	10	12	14	16	18	20	22	
Regular	6	8	10	12	14	16	18	20	22	24
Long		8	10	12	14	16	18	20	22	
X-long			10	12	14	16	18	20		

NOTE: The lengths of the slacks may be abbreviated as XS, S, R, L, or XL for X-short, short, regular, long, and X-Long.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

Label/marking. Each pair of slacks shall have a non-woven, commercial-type label containing the contractor's name, contract number, size and National Stock Number (NSN). The inscription shall show colorfastness to laundering and shall include fiber content and the following care instructions:

Machine Wash - Permanent Press Cycle - Warm Water
Tumble Dry - Medium Heat
or
Hang to Dry
Touch Up With Warm Iron

Label/tag. Each item shall be individually bar-coded with the type VIII, class 17 label/tag of DDD-L-20. This label/tag shall be located so that it is completely visible on the item when it is folded and/or packaged as specified and causes no damage to the item.

Patterns. The Government shall furnish a single size pattern. The contractor is responsible for grading patterns for additional sizes. The pattern generally provides for a seam allowance of 1/2 inch for joining seams. Commercial patterns may be used in lieu of the Government-furnished pattern provided they conform to the cited design and finished measurements.

Sizes and measurements. The finished slacks shall conform to the measurements below.

Table II. - Finished measurements

Sizes	6	8	10	12	14	16	18	20	22	24	Tolerance
1/2 Waist (Relaxed) 1/											
	8-1/2	9	9-1/2	10	10-3/4	11-1/2	12-1/4	13-1/4	14-1/4	15-1/4	± 1/2
1/2 Waist (Expanded) 2/											
	14-1/2	15-3/4	15-1/2	16	16-3/4	17-1/2	18-1/4	19-1/4	20-1/4	21-1/4	± 1/2
1/2 hip 3/											
	19-1/2	20	20-1/2	20-1/4	21-1/4	22	23-3/4	24-3/4	25-3/4	26-3/4	± 1/2

Inseam 4/					
X-short	Short	Regular	Long	X-long	tolerance
23	25-1/2	28-1/2	31	33-1/2	± 1/4

1/ With slide fastener closed and waistband in relaxed position, measure from folded edge to folded edge at center of waistband.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

2/ With slide fastener closed and waistband in stretched position, measure from folded edge to folded edge at center of waistband.
3/ At a point, 8 inches from top of waistband in stretched position, measure from folded edge.

4/ Measure from crotch seam along inseam to bottom of slacks.

Workmanship. The finished slacks shall conform to the quality of product established by this document. The occurrence of defects shall not exceed the contractor's own quality assurance standards and the quality assurance standards defined by the technical data in the bid package.

Product demonstration model. When required, offerers shall submit samples of their intended production. The product demonstration model will consist of units independently developed. Product demonstration models will be analyzed and evaluated by the Government. Evaluation criteria and basis for award are contained in the solicitation. Product demonstration models will be retained by the Government. One (1) product demonstration model approved by DPSC under the resultant contract will serve as a manufacturing standard for the corresponding production items delivered under this contract. Offerers are advised that the product demonstration model does not relieve the successful offerer of his responsibility to perform in accordance with the commercial item description specified above.

Regulatory requirements. The offeror/contractor is encouraged to use recovered materials in accordance with Public Law 94-580 to the maximum extent practicable.

Quality assurance

Certification. The contractor shall certify that the product offered meets the salient characteristics of this description and that the product conforms to the producer's own drawings, specifications, standards and quality assurance practices. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract. Reliance on contractor quality assurance systems shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract.

Examination

Visual examination. The slacks shall be examined for the defects listed below. The lot size shall be expressed in units of slacks. The sample unit is one pair of slacks.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

Defects. The slacks shall be examined for the following defects: any hole, cut, tear, or color not as specified or shaded parts when required to be cut from one piece of material; any spot or stain (outside); raw edges, open seams, thread ends not removed or loose tension resulting in loose seams; any material defects, distorted parts or poor workmanship; any component part omitted; label missing, incorrect, or illegible; measurement of item not as specified; bar code omitted or not readable by scanner; human-readable interpretation (HRI) omitted or illegible; not visible or folded, package item; causes damage to the item.

Dimensional examination. The finished slacks shall conform to the dimensions specified. Any dimension that is not within the established tolerance shall be classified as a defect. The sample unit shall be one pair of slacks.

Packaging examination. The fully packaged shipping containers shall be examined in accordance with defects listed below. The lot size shall be the number of shipping containers in the inspection lot.

EXAMINE	DEFECT
Marking (exterior and interior)	Omitted; incorrect; illegible; of improper size, location, or method of application
Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of container flaps, loose strapping, improper taping, or inadequate stapling
Content	Number of items in container is more or less than required
	NSN shown on one or more items is not as specified on shipping container
Palletization	Length, width, or height exceeds specified maximum requirements Pallet type not as specified Load not bonded as specified

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or order.

Source of Government documents. Copies of Military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

Sources of non-Government documents

ASTM-D 1424 - Standard Test Method for Tearing Strength
ASTM-D 2165 - Standard Test Method for pH
ASTM-D 3776 - Standard Test Method for Mass per Unit Area (Weight) of Woven Fabric
ASTM-D 3787 - Standard Test Method for Bursting Strength of Knitted Goods-Constant-Rate-of-Traverse (CRT) Ball Burst Test
ASTM-D 5034 - Standard Test Method for Breaking Strength

(Applications for copies should be addressed to American Society For Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

AATCC 15 - Colorfastness to Perspiration
AATCC 16 - Colorfastness to Light
AATCC 61 - Colorfastness to Laundering, Home, and Commercial: Accelerated
AATCC 124 - Appearance of Fabrics after Repeated Home Launderings
AATCC 135 - Dimensional Changes in Automatic Home Laundering of Woven and Knit Fabrics

(Applications for copies should be addressed to American Association of Textile Chemists and Colorists (AATCC), P.O. Box 12215, Triangle Park, NC 27709-2215.)

Custodian:
Army - GL
Air Force - 99

Review Activity:
Army - MD
Air Force - 82

Civil Agency Coordinating Activity:
GSA - FSS

Preparing Activity:
DLA - CT

Project No. 8410-0804

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER A-A-55230	2. DOCUMENT DATE (YYMMDD) 930923

3. DOCUMENT TITLE
SLACKS, WOMAN'S HOSPITAL DUTY UNIFORM (HDU)

4. NATURE OF CHANGE (*Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.*)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME Defense Personnel Support Center ATTN: DPSC-FSSD (12-3-D)	b. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON
c. ADDRESS (Include Zip Code) 2800 South 20th Street P. O. Box 8419 Philadelphia, Pennsylvania 19101-8419	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340

DD Form 1426, OCT 89

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T09:45Z
Check the source to verify that this is the current version before use.