INCH-POUND

MIL-B-81820F
SUPPLEMENT 1
21 February 1994

MILITARY SPECIFICATION

# BEARINGS PLAIN SELF-ALIGNING, SELF-LUBRICATING, LOW SPEED OSCILLATION, GENERAL SPECIFICATION FOR

This supplement form a part of MIL-B-81820F, dated 21 February 1994.

## SPECIFICATIONS SHEETS

MIL-B-81820/1 - Bearing, Plain, Self-Alligning, Self-Lubricating, Lined Bore, Low Speed, Narrow, Grooved Outer Ring, -65° tO 325°F

MIL-B-81820/2 - Bearing, Plain, Self-Aligning, Self-Lubricating, Lined Bore, Low Speed, Wide, Chamfered Outer Ri ng. -65° to 325°F

MIL-8-81820/3 - Bearing, Plain, Self-Aligning, Self-Lubricating, Lined Bore, Low Speed, Wide, Grooved Outer Ring, -65° to 325°F

MIL-B-81820/4 - Bearing, Plaln, Self-Aligning, Self-Lubricating, Low Speed, Narrow, Chamfered Outer Ring, -65° to 325°F

## MILITARY STANDARDS

MS14101 - Bearing. Plain. Self-Lubricating, Self-Aligning, Low Speed, Narrow, Grooved Outer Ring, -65° to 325°F

MS14102 - Bearing, Plain, Self-Lubricating, Self-Aligning, Low Speed, Wale, Chamfered Outer Ring, -65° to 325°F

MS14103 - Bearing, Plain, Self-Lubricating, Self-Aligning, Low Speed, Wide, Grooved Outer Ring, -65° to 325°F

MS14104 - Bearing, Plain, Self-Lubricating, Self-Aligning, Low Speed, Narrow, Chamfered Outer Ring, -65° to 325°F

Preparing Activity
Navy-AS



AMSC N/A FSC 3120

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:13Z
Check the source to verify that this is the current version before use.