INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

VISE, BENCH, CLAMP BASE; SHEET METAL WORKER'S; BENCH AND PIPE;

JEWELER'S; MACHINIST'S AND MULTIPOSITION

This interim amendment was developed by the Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification GGG-V-410a, dated May 26, 1966.

PAGE 2

Paragraph 3.3, first sentence: Delete "baked".

Paragraph 3.5.2.1, between the third and fourth sentences: Insert the following:

"The respective measurements shall be construed to mean a peripheral clearance of the sliding member and its counterpart with the clearance being measured circumferentially at four opposing points 90° to each other."

PAGE 3

Paragraph 3.5.4: Delete and substitute:

"3.5.4 Vise screw. The vise screw shall be of steel not less than 60,000 pounds per square inch (p.s.i.) yield and 80,000 p.s.i. tensile strength (see 4.5.3). It shall have American National, square, acme, modified acme, 7/16-14 UNC thread, or buttress threads. The screw threads, except the modified acme thread, or square thread shall be in accordance with NBS H28. One end of the screw shall have a steel or cast iron head of adequate size which shall be an integral part of the screw, welded to the screw, or otherwise securely attached in a permanent manner. The head shall be provided with a hole to receive the screw handle. The screw shall engage the full length of the threaded bearing of the body when the jaw is at the maximum opening indicated in the applicable table."

Paragraph 3.5.5, second sentence: Delete "Except for type I vises" and substitute "Except for types I and VII vises".

Paragraph 3.5.6: Delete last sentence and substitute:

"For types III, IV, V, and VI, the handle shall be of such diameter and length that it will not be deformed when tested as specified in 4.5.1."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.

PAGE 4

Paragraph 3.7: Delete sixth sentence.

TABLE I, column 3: Under "Throat depth (minimum)" for 1-1/2 inch jaw opening size, delete "1 inch" and substitute "7/8 inch".

TABLE I, column 4: Under "Weight (minimum)" for class 1, delete "2-1/4 pounds" and substitute "2 pounds".

PAGE 7

Paragraph 3.12.1: Add the following:

"(3) Jaw facings shall be of steel or nylon, and serrations are not required.

(4) Nut, when required by manufacturer's standard design, shall be of malleable iron, steel, brass, or bronze, and have a minimum length of 7/8 inch. A nut which is separate from the vise body shall not be required."

PAGE 9

Paragraph 4.5.1 and TABLE VIII: Delete and substitute:

"4.5.1 Loading test. Types III, IV, and VI vises shall be subjected to loading tests to determine conformance with the requirements to table VIII. Type V vises shall be subjected to a loading test of 100 inch-pounds. These tests shall consist of loading the handle as near the end as practicable while the jaws clamp a parallel block of such dimensions that the jaw opening is equal to the nominal width of the jaws specified in tables IV and VIII. The handle shall be considered as having taken a permanent set when the maximum deviation of the bent portion is 1/32 inch or more (measurement to be made before and after loading). After the loading test, the vise shall operate smoothly and the component parts shall show no visible distortion.

TABLE VIII. Loading test

Jaw width (nominal)	Test loads, types III and VI	Test loads, type IV
Inches	Inch-pounds	Inch-pounds
3	1,000	
3-1/2	1,200	1,100
4	1,600	
4-1/2	2,000	1,800
5	2,700	2,000
6	3,000	2,200
8	5,000	

"

PAGE 10

Paragraph 6.2, (d): Delete option "(d)".

GSA DC 73-8005

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.