INTERIM AMENDMENT

TO
FEDERAL SPECIFICATION

VISE: HAND; PIN; WIRE ROPE SPLICING; AND SQUARE END

This Interim Amendment was developed by Standardization Division, Federal Supply Service, General Services Administration, Washington, D. C. 20405, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this Interim Amendment as a valid exception to Federal Specification GGG-V-412a, dated June 29, 1966.

PAGE 2

Paragraph 3.5.1, second line: After "forged steel," add "hardenable malleable iron". In line five, after "surfaces", add, "with a steel pin no less than 1/8 inch in diameter,".

Paragraph 3.5.1.1: At end of sentence, after "serrated", add, "to a depth of 1/32 inch, minus 0.010 inch. A longitudinal and transverse vee notch 1/8 inch wide by 90° shall be located in the center of either jaw. There shall not be more than 3/64-inch sideways play in the jaws."

Paragraph 3.5.1.3: Delete and substitute:

3.5.1.3 Screw. The screw shall be provided with a washer and steel wing nut not less than 1-1/8 inches across the tip. The screw, washer and wing nut shall be nickel or cadmium plated.

Table I: Delete and substitute:

TABLE I. Type I, class 1, hand, hinged jaw

Jaw width ℄ 1/16	Jaw opening Min.	Throat depth ℄ 1/16	Overall length		Weight Max.
			Min.	Max.	
Inches	Inch	Inch	Inches	Inches	Ounces
1-1/2	1	1	4-1/2	5-1/2	15

PAGE 3

Paragraph 3.5.3.2, second line: Delete "forgings".

PSC 5120

GSA DC 68-16302

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:39Z
Check the source to verify that this is the current version before use.