MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, CLOSED CONSTRUCTION, EXPLOSION PROOF,
FLUX SEAL .500 INCH DIAMETER, .200 AMPERE, STYLE SR20

This amendment forms a part of MIL-S-3786/20H, dated 20 June 1995, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Title, delete and substitute:

"SWITCH, ROTARY, CLOSED CONSTRUCTION, EXPLOSION PROOF, NON FLUX SEAL & FLUX SEAL, .500 INCH DIAMETER, .200 AMPERE, STYLE SR20"

FIGURE 1, printed circuit configuration, dimension "A", delete and substitute:

"

DIM. "A"	
NON FLUX SEAL	.537 ±.020
FLUX SEAL	.542 ±.020
FLUX SEAL	.576 ±.015



"

PAGE 6

PIN, example B, delete and substitute:

"Example B: Flux sealed switches: M3786/20 - G E CL

	*	*	*
Switching characteristics, type of shaft and	*	*	*
length of housing (see table IV)_____	*	*	*
		*	*
Type construction, low level capability, shaft grounding,_____		*	*
and type of termination (see table V)			*
			*
Angle of throw, poles per deck, and number of _____			*
positions per pole (see table VI)			

NOTE: M3786/20-GECL identifies a flux-sealed rotary switch that is explosion proof, flux proof, closed construction, sealed shaft and panel seal, with a flatted shaft, .542 ±.020 inches (13.21±.51mm) length housing, nonshorting switching characteristics, a 45 degree angle of throw, 2 poles, 4 positions per pole, construction type K, a grounded shaft with low level capabilities and printed circuit termination."

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:37Z
Check the source to verify that this is the current version before use.

PAGE 9

TABLE IV, delete and substitute:

" TABLE IV. Switching characteristics and type of shaft

Code letter	Switching characteristics	Shaft type	Dimension "A" (figure 1)
A	Nonshorting	Flatted	.576 ±.015
B	Nonshorting	Slotted	.576 ±.015
C	Shorting	Flatted	.576 ±.015
D	Shorting	Slotted	.576 ±.015
E	Nonshorting	Flatted	.542 ±.020
F	Nonshorting	Slotted	.542 ±.020
G	Shorting	Flatted	.542 ±.020
H	Shorting	Slotted	.542 ±.020

"

PAGE 10

TABLE V, title, delete and substitute:

"TABLE VI. Code letter for combination of angle of throw, poles per deck, and number of positions per pole"

Custodians:
Army - CR
Navy - EC
Air Force - 85

Preparing activity:
DLA - CC

(Project 5930-1626)

Review activities:
Army - AR, AT, AV, ME, MI, SM
Navy - AS, CG, MC, OS
Air Force - 19, 99

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:37Z
Check the source to verify that this is the current version before use.