MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, CLOSED CONSTRUCTION, 1 AMPERE AND LOW LEVEL
STYLE SR28

This amendment forms a part of MIL-S-3786/28D, dated 21 December 1982, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 7

Bottom of page, add:

"Mounting hardware: Each switch shall be supplied with one each hexagon nut in accordance with MS25082-B20 or equivalent, and one internal-tooth lockwasher in accordance with MS35333-75 or equivalent."

PAGE 8

Table II, 2/, delete and substitute:

* "2/ Low level life is applicable. Low level shall be conducted as one of the electrical loads tested during life (rotational) testing. Contact resistance shall not exceed 7.5 milliohms. At the beginning of the test and every 5,000 cycles thereafter, the contact resistance shall be measured."

The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, MI
Navy - AS, OS
Air Force - 11, 17
DLA - ES

User activities:
Army - AT, ME, SM
Navy - CG, MC
Air Force - 19

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5930-1338-02)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:38Z
Check the source to verify that this is the current version before use.