INCH-POUND

MIL-S-3786/36
AMENDMENT 4
7 January 1994
SUPERSEDING
AMENDMENT 3
21 February 1990

MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, CLOSED CONSTRUCTION, 1/4 AMPERE, STYLE SR36

This amendment forms a part of MIL-S-3786/36, dated 4 August 1972, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Figure 1, shaft flat dimension, delete ".216" and substitute ".216 ±.005".

PAGE 6

Figure 2, 22°30' 4 pole/deck view, delete "C1" at end of bushing keyway centerline and add "C1" at end of line extending radially from terminal 1.

PAGE 8

Vibration grade, delete "Symbol 3 (10 to 2,000 Hz) and substitute "Symbol 2 (10 to 500 Hz)".

* Shock type, delete and substitute the following:

"Shock type: B (Medium and high impact, method I and method II)."

* Mounting hardware, delete and substitute the following:

"Mounting hardware: Switch shall be supplied with two mounting nuts in accordance with MS25082-C20, one lock washer in accordance with MS35333-76, and one non-turn washer in accordance with figure 3. Alternative base metals and protective finishes, as approved by the qualifying activity, may be utilized for mounting nut, lock washer, and non-turn washer material. Dimensions shall be in accordance with the referenced hardware specifications."

PAGE 9

Life (rotational), add the following:

"After life (rotational) test, the contact resistance shall not exceed 50 milliohms. Three additional sample units are required for qualification testing at the atmospheric pressure and room temperature condition specified in table IV; the switch to be tested shall be M3786/36-0230."

Table IV, delete and substitute the following:

Table IV. Circuit values for life (rotational) test.

*

Number of cycles and environmental condition	Inductive load (250 millihenries)		Resistive load	
	Milliamperes	Voltage	Milliamperes	Voltage
10,000 cycles at 70,000 feet altitude	10	28 V dc	50	28 V dc
			20	115 V ac, 60 Hz
10,000 cycles at atmospheric pressure and 125°C	25	28 V dc	75	28 V dc
			25	115 V ac, 60 Hz
10,000 cycles at atmospheric pressure and room temperature	75	28 V dc	250	28 V dc
			150	115 V ac, 60 Hz

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:40Z
Check the source to verify that this is the current version before use.

Part number, delete "M3786/##" and substitute "M3786/36".

NOTE: The margins of this amendment are marked with asterisks to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only, and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

CONCLUDING MATERIAL

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Army - AR, AT, AV, ME, MI
Navy - AS, CG, MC, OS
Air Force - 19, 99

Preparing activity:
Air Force - 85

Agent:
DLA - ES

(Project 5930-1579)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T21:40Z
Check the source to verify that this is the current version before use.