MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, CLOSED CONSTRUCTION,
0 5 AMPERE, STYLE SR41

This amendment forms a part of MIL-S-3786/41(USAF), dated 12 August 1976, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 6

Table III Delete and substitute

TABLE III Circuit values for life (rotational) test

Environmental condition	Inductive Load Per MIL-I-81023		Resistive Load	
	Milliamperes	Volts, dc	Amperes	Volts
At atmospheric pressure and elevated temperature (85°C or 125°C) (25,000 cycles	50	28	.125	28 dc
			075	115 V rms 60 Hz
At reduced barometric pressure (approx 25°C) (25,000 cycles)	10	28	.050	28 dc
			020	115 V rms 60 Hz
At atmospheric pressure and room temperature (approx 25°C) (10,000 cycles) 1/	250	28	.500	28 dc
			500	115 V rms 60 Hz

1/ The contact resistance (applicable to ac and dc), after life tests, shall not exceed 50 milliohms

CONCLUDING MATERIAL

Custodian
Air Force - 85

Preparing activity
Air Force - 85

Review activities
Air Force - 99
DLA - ES

(Project 5930-F675-02)

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

Source: https://assist.dla.mil - Downloaded: 2026-10-16T21:42Z
Check the source to verify that this is the current version before use.