MILITARY SPECIFICATION SHEET

SWITCH, ROTARY, OPEN CONSTRUCTION, .5 AMPERE,
LOW LEVEL, POSITIVE SHAFT GROUNDING,
EMI/RFI, STYLE SR15

This amendment forms a part of MIL-S-3786/15F, dated 31 March 1987, and is approved for use by all Departments and Agencies of the Department of Defense.

Page 4

Table III Delete and substitute

TABLE II. Electrical loads

Environmental condition	Inductive Load Per MIL-I-81023		Resistive Load	
	Milliamperes	Volts	Milliamperes	Volts
At atmospheric pressure and elevated temperature (125°C)	50	28 dc	500 125 50 10	28 dc 115 V rms 300 V rms 030 dc or peak AC maximum 1/

1/ Low level life is applicable Low level shall be conducted as one of the electrical loads tested during life (rotational) testing Contact resistance shall not exceed 7 5 milliohms At the beginning of the test and every 5,000 cycles thereafter, the contact resistance shall be measured

CONCLUDING MATERIAL

Custodians
Army - ER
Navy - EC
Air Force - 85

Preparing activity
Air Force - 85

(Project 5930-1430-05)

Review activities
Army - MI
Navy - AS, EC, OS
Air Force - 11, 99
DLA - ES

User activities
Army - AT, AV, ME, SM
Navy CG, MC
Air Force - 19

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited
Source: https://assist.dla.mil - Downloaded: 2025-07-20T13:37
Check the source to verify that this is the current version before use.