MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6352 1/

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Double Diode, Subminiature, Temperature Limited

Outline ---------- 3-2 (EIA)

Base ---------- E8-10

Envelope --------- T-3 (Note 1)

Cathode --------- Tungsten filament

Base Connections:

Pin No.	1	2	3	4	5	6	7	8
Element	f	ic	ic	fct	2a	f	1a	fct

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ib	Rl	Altitude
Unit:	Vac	Vdc	mAdc	Meg	Feet
Maximum:	4.0 Note 2	275	1.1 Note 3	---	80,000
TEST CONDITIONS:	(Adj for Ib = 50 µAdc; Note 2)			1.0	

GENERAL: Qualification - Not required

1/ See note 13

6352 1/

PSC 5960

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:02Z
Check the source to verify that this is the current version before use.

PAR. NO.	TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
						Min	Max	
	Quality conformance inspection, part 1							
1261	Electrode voltage (filament)	Ebb = 250 Vdc See note 3	0.65	II	Ef	2.6	3.4	Vac
----	Leakage	Ef = 0; Ebb = 250 Vdc See notes 3 and 6	0.65	II	LIb	---	5.0	µAdc
----	Stability	Ebb = 250 Vdc; See notes 3 and 7	0.65	II	Ib	40	60	µAdc
	Quality conformance inspection, part 2							
1301	Filament current	Ef = 3.0 Vac See note 2	4.0	S4	If	340	390	mAac
----	Vibrational stability	Ebb = 250 Vdc; F = 60 Hz; Acc = 22g See notes 3 and 8	6.5	S4	Ib	40	60	µAdc
----	Alignment	See note 12	6.5	S4	---	---	---	---
----	Resonance	See note 5	---	---	---	---	---	---
1041	Shock (1)	Ef = Ebb = 0 G = 450 See note 9	20	---	---	---	---	---
1041	Shock (2)	Ebb = 250 V G = 157.5 See notes 3 and 10	20	---	---	---	---	---
----	Vibration, lead, fatigue	Ebb = 250 Vdc; F = 60 Hz; Acc = 22g; See notes 3 and 11	6.5	S4	---	---	---	---
1202	Filament burnout	See note 3	6.5	S4	---	---	---	---
1116	Lead fatigue		4.0	S4	---	---	---	---
1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
1501	Intermittent-life	Ef = 1.5 Vdc; Ebb = 250 Vdc; Rl = 1.0 Meg; Group A See notes 3 and 4	---	---	t	500	---	hrs
	Intermittent-life end points	Filament voltage	---	---	Ef	---	3.8	Vac

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:02Z
Check the source to verify that this is the current version before use.

NOTES:

1. The tube is to be operated in a vertical position, base up or down.
2. Filament sections connected in series.
3. Plates connected together at the socket.
4. Heater sections connected in parallel.
5. The mount shall exhibit no pronounced mechanical resonance below 500 Hz when the tube is accelerated at 2g. Sample size for resonance test shall be code letter D with an AQL of 6.5% in accordance with MIL-STD-105.
6. Duration of this test shall be 2 seconds minimum. However tubes evidencing increased leakage up to 10 µAdc may be accepted providing that total variation in leakage current does not exceed 5 µAdc over a period of one minute.
7. Adjust filament voltage for Ib = 50 µAdc. Readjust, if necessary, in same manner at end of 3 seconds operation. The tube shall then operate for 5 seconds without further adjustment. At the end of this 5 second period, plate current shall be within the specified limits.
8. Adjust filament voltage for the specified plate current. The tube is then vibrated for 10 seconds in position X. During vibration, any plate current variation exceeding the specified limit within a 3 seconds period shall be acceptable. At the end of 10 seconds the tube must be within the specified limits.
9. Each tube shall be subjected to a total of four hammer blows. One hammer blow in each plane X, Y, and Z.
10. Each tube shall be subjected to one hammer blow in plane X only.
11. Vibrate the tube under test for 5 minutes in each of the three planes, X, Y, and Z in any sequence. Filament breakage shall be sole criterion of rejection for this test.
12. The plane of the filament shall be parallel to a plane passing through leads 1 and 6 within 22.5°.
13. This tube shall not be considered for use in new developments of Air Force airborne electronic systems, equipments, or item of equipment. This specification shall be used only to procure replacement tubes for existing Air Force airborne electronic applications.

Custodians:
Air Force - 80

Review activities:
Army - MI
Air Force - 11, 17

Preparing activity:
Air Force - 80

(Project 5960-P826-2)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:02Z
Check the source to verify that this is the current version before use.