INCH-POUND

MIL-PRF-1/1048D
w/AMENDMENT 1
12 February 2018
SUPERSEDING
MIL-PRF-1/1048D
3 February 2012

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, CATHODE RAY
TYPES 5AFP1 AND 5AFP7

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Dual beam, post-accelerator, flat face, electrostatic focus and deflection.

PIN CONNECTIONS AND DIMENSIONS: See figure 1.

ABSOLUTE RATINGS:

Parameter: Unit:	Ef V	Ec1 V dc	Eb1 V dc	Eb2 V dc	Eb3 V dc	ed v	Rg MegΩ	Zd MegΩ	Ehk V dc	Eb3/Eb2 Ratio	Alt ft
Maximum: Minimum:	6.9 5.7	0, -200 ---	1,750 ---	3,500 1,000 1/	10,500 1,000	750 ---	1.5 ---	1.0 --- 2/	±180 ---	3.0 --- 3/	5,000 ---
Test conditions: 4/	6.3	Adjust	Focus	2,000	4,000	---	---	1.0	---	2.0	---

See footnotes at end of table I.

GENERAL:

Qualification: Not Required.

This specification sheet uses accept on zero defect sampling in accordance with MIL-PRF-1, table III.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

Inspection	Method MIL-STD-1311	Conditions	Symbol	Limits		Unit
				Min	Max	
First article inspection						
Base material insulating quality	1216		---	---	---	---
Neck and bulb alignment (electrostatic types)	5101		Dia	---	3.31	inch
Face lift	5101		---	---	---	---
Cathode illumination	5216		---	---	---	---
Barometric pressure, reduced	1002	87 mmHg 6/	---	---	---	---
Pressure (implosion)	1141		---	---	---	---
Vibration	5111		Width	---	1	mm
Direct-interelectrode capacitance	1331	12/ k to all g1 to all D1 to D2 D3 to D4 D1 to all D2 to all D3 to all D4 to all	 Ck Cg1 C1D2 C3D4 CD1 CD2 CD3 CD4	 --- --- --- --- --- --- --- ---	 4.6 4.0 2.0 1.4 5.0 5.0 4.1 4.1	 pF pF pF pF pF pF pF pF
Deflection-factor uniformity	5248	1D2 3D4	--- ---	--- ---	2 3	% %
Interaction factor	5250		---	---	14×10^{-6}	inch/V dc
Magnetization	5256		---	---	---	---
Conformance inspection, part 1						
Voltage breakdown	5201		---	---	---	---
Voltage breakdown (electrostatic types)	5201		---	---	---	---
Gas "cross"	5206	Ib3 = 50 µA dc 5/	---	---	---	---
Modulation	5223	Ib3 = 25 µA dc	ΔEc1	---	35	V dc
Spot position (electrostatic deflection)	5231		---	---	15	mm
Spot displacement (leakage)	5231		Displ	---	10	mm
Grid cutoff voltage	5241		Eco	-45	-75	V dc
Tracking	---	9/	---	---	1.5	%
Useful scan	---	1D2 10/ 3D4 10/	--- ---	--- ---	4 4	inch inch

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

Inspection	Method MIL-STD-1311	Conditions	Symbol	Limits		Unit
				Min	Max	
Conformance inspectio part 1 - Continued						
Pattern distortion	5103	11/	---	---	2	%
Grid No. 1 leakage current	5251		---	---	---	---
Anode No. 1 leakage current	5251		Ib1	---	3	µA dc
Anode No. 2 leakage current	5251		---	---	---	---
Light output (P1)	5221	Ib3 = 25 µA dc 5/	Light	20	---	fL
Conformance inspection, part 2						
Heater current	1301		If	540	660	mA
Electrode currents (Anode No. 1)	5201		Ib1	-10	5	µA dc
Electrode current (cathode)	5201	Ib3 = 50 µA dc	Ik	---	600	µA dc
Base alignment (electrostatic types)	5101	+3D4, base key, collar index pin	---	---	---	---
Collar base alignment	---	+3D4, collar index pin	---	---	10	Degrees
Side terminal and base alignment	5101	Base key, collar index pin	---	---	---	---
Side terminal alignment (electrostatic types)	5101	+3D4	---	---	---	---
Neck and base alignment (electrostatic types)	5101		---	---	---	---
Screen (P7)	5221	5/	---	---	---	---
Line width B (electrostatic deflection)	5226	Ib3 = 25 µA dc	Width	---	0.69	mm
Focusing voltage at modulation condition	5246		Eb1	---	610	V dc
Angle between traces	5101		---	89	91	Degrees
Bulb, screen, and faceplate quality	5106		---	---	---	---
Trace alignment (gun to gun)	---	7/	---	---	---	---
Stray light emission (conventional types)	5216	Eb2 = 3,500 V dc; Eb3 = 10,500 V dc	---	---	---	---

See footnotes at end of table.

TABLE I. Testing and inspection - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.

Inspection	Method MIL-STD-1311	Conditions	Symbol	Limits		Unit
				Min	Max	
Conformance inspection, part 2 - Continued.						
Line width A (electrostatic deflection)	5226	Ib3 = 25 µA dc	Width	---	0.65	mm
Focusing voltage at cutoff	5246		Eb1	---	610	V dc
Deflection factor	5248	1D2 8/	DF	54	66	V dc/inch
Deflection factor	5248	3D4 8/	DF	43	53	V dc/inch
Deflection factor	5248	1D2; Eb3 = Eb2 = 2,000 V dc	DF	43	55	V dc/inch
Deflection factor	5248	3D4, Eb3 = Eb2 = 2,000 V dc	DF	36	44	V dc/inch
Heater-cathode leakage current	5251		Ihk	---	15	µA dc
Secureness of base, cap, or insert	1101		---	---	---	---
Base pin solder depth	1111		---	---	---	---
Permanence of marking	1105		---	---	---	---
Conformance inspection, part 3						
Life-test provisions	---	Group C; t = 500 hours (min); Ib3 = 25 µA dc; Eb2 = 3,500 V dc; Eb3 = 10,.500 V dc	---	---	---	---
Life-test end points	---	Ib3 - 18.75 µA dc				
		Modulation	ΔEc	---	35	V dc
		Line width A	Width	---	0.65	mm
		Line width B	Width	---	0.75	mm
		Grid No. 1 leakage	---	---	---	---
		Anode No. 2 leakage	---	---	---	---
		Heater-cathode leakage	---	---	---	---
		Anode No. 1 leakage	---	---	---	---
		Stray emission	---	---	---	---

See footnotes at top of next page.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

1/ Accelerator average power input shall be limited to 6 watts. Grid No. 4 and grid No. 2 are connected internally and referred to herein as accelerator. This shield and the accelerator electrodes should be connected together under normal operating and test conditions. However, the accelerator as well as the first ring of the post-deflection accelerating system may be operated at slightly different potentials for astigmatism control if desired and the shield potential should then be adjusted for optimum performance.

2/ Deflection electrode circuit resistances should be equal. Higher resistance values up to 5.0 MegΩ may be used for low-beam current operation.

3/ This tube is designed for optimum performance when operating at an Eb3/Eb2 ratio of 2.0. Operation at other ratios of Eb3/Eb2 may result in changes in deflection uniformity, pattern distortion, and tracking.

4/ All tests except capacitance, vibration, tracking, cathode illumination, stray emission, and interaction factor shall be made on each unit separately. Each deflection plate shall be connected to A2 through a resistance of 1 MegΩ.

5/ This test to be performed at the conclusion of the holding period.

6/ Maximum potentials applied to base, deflection plates, and A2 only.

7/ Corresponding traces of each unit shall be within 1° of each other.

8/ The ratio of the deflection factors of corresponding deflection electrodes shall not exceed 1.15.

9/ The focused spots of both guns shall be moved by means of a common dc voltage along the 1D2 axis until the spot of gun A is at ±1 inch from the geometrical center of the tracking area. Then by means of a small correction voltage, the spot of gun B shall be moved to the same distance. The spots then shall be moved by means of the common dc voltage in the opposite direction from the geometrical center until the spot of the less sensitive gun reaches -1 inch. The difference in deflection factor of the more sensitive gun is then compensated for by moving its spot back to -1 inch by means of a voltage divider. This entire procedure is to be duplicated along the 3D4 axis. Then by means of the two common dc voltages, the spots shall be tracked over the entire tracking area, a 4-inch diameter circle centered with respect to the tube face center, and the greatest distance between the spots shall not exceed the limit specified.

10/ Centered with respect to the tube face and with the tube shielded.

11/ With a raster pattern, adjusted so its widest points just touch the sides of a 3.060-inch square, will fall within the area bounded by the 3.060-inch square and an inscribed 2.940-inch square.

12/ All other electrodes contained within the envelope are to be tied together.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.




FIGURE 1. Outline drawing of electron tube types 5AFP1 and 5AFP7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.

Ltr	Dimensions			
	Inches		Millimeters	
	Min	Max	Min	Max
Conformance inspection, part 2				
A	5.16	5.37	130.97	135.73
B	4.50	---	114.30	---
C	2.94	3.06	74.61	77.79
D	18.00	18.50	457.20	469.90
E	12.00	12.50	304.80	317.50
F	7.75	8.25	196.85	209.55
G	3.44	3.94	87.31	100.01
H	4.25	4.375	107.95	111.13
J	---	.125	---	3.18
Conformance inspection, part 3 (periodic check)				
K	Envelope: J42R1, J42S1			
L	Contact: J1-22			
M	Collarbase: A12-94			
N	Base: B12-37			

NOTES:

1. Shield (collar pins 4 and 11) is common to both beams.
2. Minimum useful screen diameter.

FIGURE 1. Outline drawing of electron tube types 5AFP1 and 5AFP7 - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-1, this specification sheet references MIL-STD-1311.

The margins of this specification sheet are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Project (5960-2018-009)

Review activities:
Navy - AS, CG, MC, OS
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:03Z
Check the source to verify that this is the current version before use.