MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 5702WB

This amendment forms a part of Military Specification Sheet MIL-E-1/1069F, dated 19 February 1981, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Quality conformance inspection, part 3, Method 1501, Intermittent life, NOTES column: Delete "6" and substitute "6,8".

Quality conformance inspection, part 3, Method 1501, Intermittent life, Conditions column: Delete "TA = room" and "Group E".

PAGE 4

NOTES, add the following note:

"8. The life-test sample shall consist of 20 tubes per lot and not more than 1 tube failure shall be permitted. In the event of rejection of the first sample, due to failure of more than 1 tube, a second sample of 40 tubes shall be selected from the lot. Acceptance shall then be based on the combined first and second samples. The total tube failures from the combined first and second samples shall not exceed three."

Custodians:
Army - ER
Navy - EC
Air Force - 85

Review activities:
Air Force - 99
DLA - ES

User activities:
Army - AR
Navy - AS, OS, MC, CG
Air Force - 11

Agent:
DLA - ES

Preparing activity:
Navy - EC

(Project 5960-3269)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:06Z
Check the source to verify that this is the current version before use.