MILITARY SPECIFICATION

# COATING, REFLECTION REDUCING, FOR INSTRUMENT COVER GLASSES AND LIGHTING WEDGES

This amendment forms a part of Military Specification MIL-C-14806A, dated 12 June 1969 and is approved for use by all Departments and Agencies of the Department of Defense.

Paragraph 3.4: Delete and substitute:

"3.4 Specular reflectance.- When applied to substrate materials having indices of refraction within the range of 1.47-1.55 the specular reflectance from each coated surface shall not exceed the following limits for energy incident on the surface at an angle within the range 0-15 degrees inclusive and at an angle of 30 degrees:

| Wavelength Range (Nanometers) | Maximum Reflectance (%) (at any wavelength within specified spectral range) | |
|---|---|---|
| | 0° to 15° incl | 30° |
| 440-460 | 0.55 | -- |
| 460-660 | 0.45 | -- |
| 660-675 | 0.55 | -- |
| 425-460 | ---- | 1.0 |
| 460-620 | ---- | 0.7 |
| 620-665 | ---- | 1.0" |

Custodians:

Army - MU
Navy - AS
Air Force - 11

Preparing Activity:

Army - MU

Review Activities:

Army - MU, AV
Navy - AS, OS
Air Force - 11, 17, 71

User Activities:

Army - WC, MI
Navy - SH
Air Force - None
DSA-DM

Project No. 6650-0065

FSC 6650

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:48Z
Check the source to verify that this is the current version before use.