MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, M270

* This amendment forms a part of Military Specification MIL-C-14814B dated 10 January 1978, and is approved for use by all Departments and Agencies of the Department of Defense.

2.1: Under SPECIFICATIONS: Military, Add:

"MIL-C-48568 Catapult, Aircraft Ejection Seat: CKU-7/A Assembly"

Page 3

* TABLE I. Change value of Velocity at -65° to -70°F from "37.5" to "37.0"

Page 4

4.3.1: Delete in its entirety and substitute:

"4.3.1 Initial production sample. Unless otherwise specified in the contract (see 6.2), an initial production sample consisting of 76 assembled cartridges shall be divided up for testing as follows: 50 cartridges for the hardness test (see 4.7.1); 21 cartridges for the combined vibration and ballistic tests (see 4.7.3, 4.7.4 and TABLE VI); and 5 cartridges for sealant application tests (see 4.7.5). Ten sets of unassembled components scheduled for visual and dimensional examination and other tests specified herein shall be submitted to an activity designated by the procuring activity (see 6.2) for initial production examination and test.

TABLE VI. Initial production sample.

Conditioning	Vibrated	Not vibrated	Fired
-65°to -70°F	4	3	7
65°to 70°F	4	3	7
160°to 165°F	4	3	7

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 202610-18T04:49Z
Check the source to verify that this is the current version before use.

Page 10

4.6.4: Delete in its entirety and substitute:

"4.6.4 Ballistics. When a production lot of cartridges is to be supplied as an end item, the 21 assembled cartridges from each production lot shall be grouped and temperature conditioned in accordance with 4.7.4.1. Failure of any cartridge to comply with the requirements of 3.4 shall be cause for rejection of the lot. When cartridges are produced as a subassembly of MIL-C-48568 by the same producer, ballistic acceptance requirements of MIL-C-48568 shall apply."

Page 11

4.7.3: Delete in its entirety and substitute:

"4.7.3 Vibration. Initial production vibration test method and procedures shall be in accordance with the vibration test of MIL-C-83125."

The margins of this amendment are marked with an asterisk where changes (additions, modifications, corrections, deletions, etc.) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Navy - OS
Air Force - 99

Preparing Activity:
Navy - OS

Project No. 1377-0731

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:49Z
Check the source to verify that this is the current version before use.