MILITARY SPECIFICATION

FUZE, MT, M571 ASSEMBLY

This Amendment forms a part of Military Specification MIL-F-14805B (MU) dated 25 April 1977.

PAGE 1

Paragraph 2.1 under Specification add:

MIL-STD-1168 Ammunition Lot Numbering **

PAGE 4

Paragraph 4.1.2 add:

Lot numbering, as required, shall be in accordance with MIL-STD-1168. **

PAGE 6

Delete paragraph 4.2.6.1 and substitute the following:

4.2.6.1 Acceptance Criteria.-The acceptance criteria for the various test phases are defined in Table II. Rejection in any phase shall be cause for rejection of the initial production sample.

TABLE II

(See following page)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:47Z
Check the source to verify that this is the current version before use.

TABLE II

Phase/ Temperature Condition	Prior Function (See 6.2.1) Test/Acc/Rej Qty		Failure to Detonate within 50 feet of muzzle Test/Acc/Rej Qty	Failure to Detonate during flight (See 6.2.3) Test/Acc/Rej Qty	Failure to Detonate during flight or offtime (Any combination See 6.2.2 and 6.2.3) Test/Acc/Rej Qty		
MA/Ambient	-		20/1/2	-	-		
MA/-40°F to -45°F	-		5/1/2	-	-		
MA/+140°F to +145°F	-		5/1/2	-	-		
400M/Ambient	20	Combine Test Quantities 50/1/2	-	-	20	40/2/3	*
2000M/Ambient	20		-	-	20		*
2000M/-40°F to -45°F	5		-	5/1/2	-		
2000M/+140°F to +145°F	5		-	5/1/2	-		

Acc. - Accept
Rej. - Reject

Note: The ground impact results shall be reported for all rounds which did not detonate during flight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:47Z
Check the source to verify that this is the current version before use.

PAGE 24

Add to following paragraph:

4.3.2.38 Spring, Button Return, Drawing 9205166 covering a detail of drawing 10551670.

Critical - None defined.

Major - Inspection to be performed on 100% basis.

101.	Free length incorrect	Gage
102.	Solid height exceeds maximum	Gage
103.	Load at compressed length incorrect	Test

PAGE 29

Delete paragraph 4.3.3.17.1 and substitute the following:

4.3.3.17.1 The acceptance criteria for the various test phases are defined in Table III. Rejection of any test phase shall be cause for rejection of the lot that the ballistic sample represents.

TABLE III

Phase/ Temperature Condition	Prior Function (See 6.2.1) Test Qty/Acc/Rej		Failure to Detonate during Flight or Off-time (Any Combination, see 6.2.2 and 6.2.3) Test Qty/Acc/Rej		Failure to Detonate within 50 feet of muzzle Test Qty/Acc/Rej
MA/Ambient	-		-		20/1/2
400 M/Ambient	20	40/1/2	20	40/2/3	* -
2000M/Ambient	20		20		* -

*Or failure to meet the time limits in Table I by an estimated lot percent defective greater than the appropriate value given in Table IV (4.3.3.17.1) for each distance phase (see 4.4.17.2 and 6.2.4).

Acc. - Accept
Rej. - Reject

Note: The ground impact results shall be reported for all rounds which did not detonate during flight.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:47Z
Check the source to verify that this is the current version before use.

TABLE IV

SAMPLE SIZE	ACCEPTABLE % DEFECTIVE
20	4.09
19	4.10
18	4.12
17	4.16

PAGE 36

Delete paragraph 4.4.17.2.1 and substitute the following:

4.4.17.2.1 Lot Percent Defective.-Individual time values obtained by the chronograph systems shall be used to calculate the estimate of lot percent defective. When both chronograph systems provide a time value for an individual fuze, the average shall be taken as the individual fuze value. Individual fuze values shall be rounded off to the third decimal place using the method prescribed by the American Society for Testing Materials. The estimate of lot percent defective shall be calculated using the method prescribed in MIL-STD-414, Example B3. For sample sizes 17, 18 and 19 the estimated lot percent defective value shall be determined by interpolation between the values given in Table B5, MIL-STD-414 for sample sizes 15 and 20.

All appropriate time values obtained for each distance function phase shall be used in the calculation of sample average (x) and standard deviation(s). Any value which is an offtime shall be excluded. A minimum of 17 time values are required for each phase (see 6.2.4).

PAGE 38

Delete paragraph 6.2.2 and substitute the following:

6.2.2 Offtime.-An offtime (includes prior functions) is any time value outside of the applicable time limits of Table I. An offtime shall be determined from a time value obtained by the Chronograph systems, or by Hawk-Doppler velocimeter if no reading was obtained by the chronograph systems. In instances in which a round detonates in flight but its time value could not be determined from the chronograph systems and/or Hawk-Doppler velocimeter, the round shall be classified as an offtime if it can be definitely established from observation or use of a stopwatch that the functioning time of the round unmistakably exceeded the specification upper limit for time values; otherwise, the round shall be disregarded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:47Z
Check the source to verify that this is the current version before use.

Delete paragraph 6.2.3 and substitute the following:

6.2.3 Failure to Detonate in Flight.-Any round which fails to detonate in flight.

Delete paragraph 6.2.4 and substitute the following:

6.2.4 Where the number of time values obtained for either distance function phase is less than 17 and the lot is not rejected because of other reasons, the disposition of the lot shall be referred to the responsible procuring activity. The Government reserves the right to require the contractor to submit additional test samples. The number of additional test samples shall be sufficient to obtain a combined total of 20 values in order that the occurrence of offtimes will not reduce the number of normal values to less than minimum required. All normal values obtained in the combined tests shall be used to determine lot acceptance or rejection. Attribute characteristic failures, e.g. duds occurring in the additional samples shall not be used to reject the lot.

Delete the first sentence of paragraph 6.2.5.

**The margins of this Amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1390-A190

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:47Z
Check the source to verify that this is the current version before use.