MILITARY SPECIFICATION

INDICATOR, DIGITAL DISPLAY: 8215501

This amendment forms a part of Military Specification MIL-I-14811(MU), dated 21 October 1968.

Paragraph 3.5.1 Continuity: Delete "Drawing F10525617" and substitute "Drawing F10525671".

Paragraph 3.6.3.1 - Delete "172 ± 3" and substitute "172 ± 4".

Paragraph 3.6.3.2 - Delete "172 ± 4" and substitute "172 ± 5".

Paragraph 3.6.7 Test Points: Change requirements in the following test points:

b. J2, Line 3: Delete "86 ± 3" and substitute "86 ± 4 at 75°F ± 15°F and 86 ± 5 milliseconds over the range of -50°F ± 3°F to +140°F ± 3°F".

d. J4: Delete "0.12%" and substitute "0.012%".

e. J5: Line 4: Delete "125.8" and substitute "127.1".

f. J6: Delete "+11.5 ± 0.7" and substitute "+18.2 ± 1.9".

g. J7: Delete "95.64" and substitute "95.648".

h. J8: Line 4: Delete "85.64" and substitute "107.0".

i. J9: Line 2: Delete "sine wave swing" and substitute "clipped sine wave swinging".

m. J14: Delete "6.0 ± 0.8 volts" and substitute "+6.0 ± 0.8 volts in Delay 1 through 5 with CAL 2 depressed".

Paragraph 4.6.2.1.1 - Delete "172 ± 3" and substitute "172 ± 4".

Paragraph 4.6.2.1.2 - Line 1: Delete "At" and substitute "Over the range of".

Paragraph 4.6.2.1.2 - Line 2: Delete "172 ± 4" and substitute "172 ± 5".

Paragraph 4.6.2.2 Indicator Accuracy, Line 5: Delete "110 KHz" and substitute "110 KHz ± .001% KHz".

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:48Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.2.6 Test Points: Change test point subparagraphs as follows:

b. J2: Line 4: Delete "86 ± 3" and substitute "86 ± 4 milliseconds at 75°F ± 15°F and 86 ± 5 milliseconds, over the range of -50°F ± 3°F to + 140°F ± 3°F".

d. J4: Line 3: Delete "0.12%" and substitute "0.012%".

e. J5: Line 5: Delete "125.8" and substitute "127.1"; Line 7: Delete "82.98" and substitute "84.28".

f. J6: Line 3: Delete "11.5 ± 0.7" and substitute "+ 18.2 ± 1.9".

h. J8: Line 5: Delete "85.64" and substitute "107.0"; Line 7: Delete "42.82 + n 42.82 ± 0.1" and substitute "64.18 + n 42.82 ± 0.1".

i. J9: Line 3: Delete "sine wave" and substitute "clipped sine wave".

Paragraph 4.6.3.1: Change "3.4.1" to "3.5.1".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A265

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:48Z
Check the source to verify that this is the current version before use.