MIL-I-14811(MU)
AMENDMENT 2
27 October 1970
SUPERSEDING
AMENDMENT 1
11 May 1970

MILITARY SPECIFICATION

INDICATOR, DIGITAL DISPLAY: 8215501

This amendment forms a part of Military Specification MIL-I-14811(MU), dated 21 October 1968.

Paragraph 3.5.1 Continuity: Delete "Drawing F10525617" and substitute "Drawing F10525671".

Paragraph 3.6.3.1: Delete "172 ± 3" and substitute "172 ± 4".

Paragraph 3.6.3.2: Delete "172 ± 4" and substitute "172 ± 5".

Paragraph 3.6.7 Test Points: Change requirements in the following test points:

* a. J1: Delete "+2.3" and substitute "+6.0".

b. J2,Line 3: Delete "86 ± 3" and substitute "86 ± 4 at 75°F ± 15°F and 86 ± 5 milliseconds over the range of -50°F ± 3°F to +140°F ± 3°F".

d. J4: Delete "0.12%" and substitute "0.012%".

e. J5: Line 4: Delete "125.8" and substitute "127.1".

f. J6: Delete "+11.5 ± 0.7" and substitute "+18.2 ± 1.9".

g. J7: Delete "95.64" and substitute "95.648".

h. J8: Line 4: Delete "85.64" and substitute "107.0".

i. J9: Line 2: Delete "sine wave swing" and substitute "clipped sine wave swinging".

m. J14: Delete "6.0 ± 0.8 volts" and substitute "+6.0 ± 0.8 volts in Delay 1 through 5 with CAL 2 depressed".

Paragraph 4.6.2.1.1: Delete "172 ± 3" and substitute "172 ± 4".

Paragraph 4.6.2.1.2, Line 1: Delete "At" and substitute "Over the range of".

Paragraph 4.6.2.1.2, Line 2: Delete "172 ± 4" and substitute "172 ± 5".

FSC 1290

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:48Z
Check the source to verify that this is the current version before use.

Paragraph 4.6.2.2 Indicator Accuracy, Line 5: Delete "110 KHz" and substitute "110 KHz ± .001% KHz".

Paragraph 4.6.2.6 Test Points: Change test point subparagraphs as follows:

* a. J1: Delete "+2.3" and substitute "+6.0".

b. J2, Line 4: Delete "86 ± 3" and substitute "86 ± 4 milliseconds at 75°F ± 15°F and 86 ± 5 milliseconds, over the range of -50°F ± 3°F to +140°F ± 3°F".

d. J4, Line 3: Delete "0.12%" and substitute "0.012%".

e. J5, Line 5: Delete "126.8" and substitute "127.1"; Line 7: Delete "82.98" and substitute "84.28".

f. J6, Line 3: Delete "11.5 ± 0.7" and substitute "+18.2 ± 1.9".

h. J8, Line 5: Delete "85.64" and substitute "107.0"; Line 7: Delete "42.82 + n 42.82 ± 0.1" and substitute "64.18 + n 42.82 ± 0.1".

i. J9, Line 3: Delete "sine wave" and substitute "clipped sine wave".

Paragraph 4.6.3.1: Change "3.4.1" to "3.5.1".

*The outside margins have been marked to indicate where additions to the previous amendment have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in this notation. Bidders and contractors are cautioned to evaluate the requirement of this document based on the entire content as written irrespective of the marginal notation and relationship to the last previous amendment.

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1290-A282

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:48Z
Check the source to verify that this is the current version before use.