MILITARY SPECIFICATION

SAFETY AND ARMING DEVICE, GUIDED MISSILE: M114
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-S-14799B (MU) dated 4 September 1973.

PAGE 2

Change para. 3.4.1 to read as follows:

"3.4.1 Armed Condition - The electrical resistance between the brown lead of the two lead wires and the red lead of the three lead wires shall not be less than 750 ohms nor more than 15000 ohms when tested at ambient temperature."

PAGE 7

Para. 4.3.1- Add the following:

"Two lots of detonators from one manufacturer may be mixed in an S&A Device lot when one detonator lot is completely depleted and a second detonator lot is required to complete the S&A Device lot."

PAGE 9

Para. 4.3.2.4- Delete Minor 201, and change Minor category AQL from "1.00" to "0.65".

Para. 4.3.2.5- Delete Major defect 101 and change AQL to 0.65 percent.

PAGE 10

Para. 4.3.2.7-
Add Major Defect 104 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.

"104. Detonators leads not across head of pin latch (as viewed through pin, latch hole in rotor).....Visual 07005"

PAGE 13

Para. 4.3.2.13- Delete Major defect 106.

PAGE 18

Add the following paragraphs:

4.3.2.27 Spacer, Pallet (see dwg. 9295018 covering a detail of 9231438).

Categories	Defects	Method of Inspection	Code No.
Major: 101.	AQL 0.40 Percent Width of spacer, max.	Gage	32001

4.3.2.28 Leaf "G" Sensing Assembly (see dwg. 9311016)

Categories	Defects	Method of Inspection	Code No.
Major: 101	"G" weight not flush or below after riveting	Visual	34001

Para. 4.3.3.1.2- Delete para. 4.3.3.1.2 and renumber subsequent paragraphs.

PAGE 19

Table I, Test VI Change:

VI	Electrical resistance	4.4.6.1	Major	23017
to				
VI	Electrical resistance	4.4.6.1	For Information only	23017

PAGE 21

Delete para. 4.3.3.2.2 and renumber subsequent paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.

PAGE 22

Delete para. 4.3.3.2.8 and change to read as follows:

"4.3.3.2.8 Environmental Functioning and Destructive Testing (see 3.8). Testing shall be in accordance with Table I using equipment in accordance with 4.3.4. Sampling shall be in accordance with Figures 2 through 5. Temperature conditioning shall be at the required temperature plus or minus 5 degrees F. for two (2) hours, minimum.

The lot shall be rejected if:

a. Any unit fails the acceptance criteria specified in MIL-STD-331.
b. Two (2) or more units fail to arm.
c. Any unit fails the minimum arming time requirement.
d. Any unit fails the electrical functioning requirement.
e. The sample average plus or minus 2 sigma fails the arming time requirements of 3.5.1 at ambient.
f. The sample average plus or minus 2 sigma fails the arming time requirements of 3.5.2 at low temperature (-25 degrees F).

In the event of one (1) electrical function failure at minus 25 degrees F. (in lots of 1201-10000 units) 60 additional units shall be selected, conditioned at minus 25 degrees F. for 2 hours minimum, and then functioned. If a total of two (2) electrical function failures occur at cold temperature, the lot shall be rejected. In the event of an electrical function failure at minus 25 degrees F. for lots less than 1201 units, the lot shall be rejected.

In the calculation for sample average and sample standard deviation, two long arming times may be excluded from the total lot test sample, provided neither of the long times exceed 500 milliseconds. The two times may be excluded from either the cold test group or the ambient test group, or one long time may be excluded from each test group."

PAGE 27

Delete para. 4.4.2 and renumber subsequent paragraphs.

Paragraph 4.4.4.2, 1st sentence-

Change "an electrical pulse of two (2) amperes maximum" to "an electrical pulse of 2.0 to 2.1 amperes".

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.

PAGE 34

Para. 5.1.1- Change "level A" to "level C"

Para. 5.2.1- Change "level A" to "level C"

Custodian:
Army-AR

Preparing Activity:
Army-AR

Project Number: 1336-A364

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.