MIL-S-14799B (AR)
Amendment 2
30 SEPTEMBER 1982
SUPERSEDING
AMENDMENT 1
15 SEPTEMBER 1980

MILITARY SPECIFICATION

SAFETY AND ARMING DEVICE, GUIDED MISSILE: M114
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-S-14799B (MU) dated 4 September 1973, and is approved for use by the U.S. Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

3.4.1 Delete paragraph in its entirety and substitute the following:

"3.4.1 Armed Condition - The electrical resistance between the brown lead of the two lead wires and the red lead of the three lead wires shall not be less than 750 ohms nor more than 15000 ohms when tested at ambient temperature."

PAGE 7

4.3.1 - Add the following:

"Two lots of detonators from one manufacturer may be mixed in an S&A Device lot when one detonator lot is completely depleted and a second detonator lot is required to complete the S&A Device lot."

PAGE 9

4.3.2.4 - Delete Minor 201, and change Minor category AQL from "1.00" to "0.65."

4.3.2.5 - Delete Major defect 101 and change AQL to 0.65 percent.

PAGE 10

4.3.2.7 - Add Major Defect 104 as follows:

"104. Detonators leads not across head of pin latch (as viewed through pin, latch hole in rotor).....Visual 07005"

PAGE 13

4.3.2.13 - Delete Major defect 106.

FSC: 1336

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.

Add the following paragraphs:

4.3.2.27 Spacer, Pallet (see dwg. 9295018 covering a detail of 9231438).

Categories	Defects	Method of Insp.	Code No.
Major: 101.	AQL 0.40 Percent Width of spacer, max.	Gage	32001

4.3.2.28 Leaf "G" Sensing Assembly (see dwg. 9311016)

Categories	Defects	Method of Insp.	Code No..
Major: 101	"G" weight not flush or below after riveting	Visual	34001

4.3.3.1.2 - Delete paragraph

Table I, Test VI Change:			
VI Electrical resistance	4.4.6.1	Major	23017
to			
VI Electrical resistance	4.4.6.1	For Info. only	23017

4.3.3.2.2 Delete paragraph

4.3.3.2.8 Delete paragraph in its entirety and substitute the following:

"4.3.3.2.8 Environmental Functioning and Destructive Testing (see 3.8). Testing shall be in accordance with Table I using equipment in accordance with 4.3.4. Sampling shall be in accordance with Figures 2 through 5. Temperature conditioning shall be at the required temperature plus or minus 5 degrees F. for two (2) hours, minimum.

The lot shall be rejected if:

a. Any unit fails the acceptance criteria specified in MIL-STD-331.

b. Two (2) or more units fail to arm.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.

c. Any unit fails the minimum arming time requirement.

d. Any unit fails the electrical functioning requirement.

e. The sample average plus or minus 2 sigma fails the arming time requirements of 3.5.1 at ambient.

f. The sample average plus or minus 2 sigma fails the arming time requirements of 3.5.2 at low temperature (-25 degrees F).

In the event of one (1) electrical function failure at minus 25 degrees F. (in lots of 1201-1000 units) 60 additional units shall be selected, conditioned at minus 25 degrees F. for 2 hours minimum, and then functioned. If a total of two (2) electrical function failures occur at cold temperature, the lot shall be rejected. In the event of an electrical function failure at minus 25 degrees F. for lots less than 1201 units, the lot shall be rejected.

In the calculation for sample average and sample standard deviation, two long arming times may be excluded from the total lot test sample, provided neither of the long times exceed 500 milliseconds. The two times may be excluded from either the cold test group or the ambient test group, or one long time may be excluded from each test group."

PAGE 27

4.4.2 Delete paragraph

4.4.4.2, 1st sentence -

Change "an electrical pulse of two (2) amperes maximum" to "an electrical pulse of 2.0 to 2.1 amperes."

PAGE 28

* 4.4.5: Delete paragraph in its entirety and substitute the following:

"4.4.5 Non-Arming. - The Safety and Arming Mechanism Assembly shall be mounted to the test equipment in accordance with 4.3.4. Orientation of the assembly shall be such that acceleration simulates missile flight. The equipment shall subject the assembly to a constant load of 10.0 g's + 0.0 g's - 1.0 g's at the center of gravity of the assembly for a minimum of three (3) seconds. Upon attaining the constant "g" load condition, the "g" sensing leaf shall be unlocked by mechanically removing the restraint from the "g" leaf. The "g" sensing leaf shall remain unlocked until the safe condition has been verified. The safe condition shall be verified by orientation of the rotor shaft and "g" sensing leaf retaining the latching leaf. This test shall be performed at ambient temperature."

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.

5.1.1 - Change "level A" to "level C"

5.2.1 - Change "level A" to "level C"

"The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment."

Custodian:
Army-AR

Preparing Activity
Army-AR

(Project 1336-A442)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T04:46Z
Check the source to verify that this is the current version before use.