INCH-POUND
MS21351G
w/Amendment 1
21 March 2017
SUPERSEDING
MS21351G
5 October 2011

DETAIL SPECIFICATION SHEET

SWITCH, TOGGLE, POSITIVE BREAK, SPECIAL CIRCUIT, MINIATURE TOGGLE SEALED, SOLDER LUG, SINGLE POLE, .469 MOUNTING BUSHING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification sheet and MIL-DTL-8834.




FIGURE 1. Dimensions and configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:36Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.002	0.05	.032	0.81	.364	9.25
.003	0.08	.045	1.14	.432	10.97
.005	0.13	.052	1.32	.438	11.13
.010	0.25	.072	1.83	.469	11.91
.012	0.30	.169	4.29	.572	14.53
.016	0.41	.240	6.10	.687	17.45
.024	0.61	.338	8.59	.706	17.93
.025	0.64	.351	8.92		
.030	0.76				

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerances are ±.010 (0.25 mm) on decimals and ±5° on angles.

FIGURE 1. Dimensions and configuration - Continued.

REQUIREMENTS:

For hardware detail specifications, see appendix of MIL-DTL-8834.

In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

Shock: Method I and method II (high impact). The switch shall be electrically and mechanically operative at the conclusion of the shock test except there can be mechanical transfer of the contact mechanism at all levels when tested in accordance with method II (high impact).

Toggle seal test: Method II.

Weight: .0429 pound maximum (19.4 grams).

Strength of terminals: 5 pounds pull perpendicular to mounting plane and 2 pounds in other planes.

Dielectric withstanding voltage: 1,200 V rms at sea level.

Altitude: 50,000 feet.

115 V ac, 60 hertz electrical endurance tests are to performed at room temperature and pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:36Z
Check the source to verify that this is the current version before use.

TABLE I. Detail requirements.

MS dash no 1/	Circuit made between terminals as indicated with the toggle lever in these positions: 2/			Current capacity in amperes						Life low current level switching 5 mV
				Resistive load			Inductive load			
				28 volts dc	115 volts		28 volts dc	115 volts		
	Opposite keyway side	Center position	Keyway side		60 Hertz ac	400 Hertz ac		60 Hertz ac	400 Hertz ac	
-321	None	2-3 on	1-2 mom-on	5	2	3	1 3/	1	2	25 µA 4/

1/ Delayed action of the switch toggle lever may cause circuit to close or open before snap action mechanism trips.
2/ Direction of movement of internal mechanism is opposite to the direction of the toggle movement.
3/ With time constant of .020 ±.002 second.
4/ Contact resistance not to exceed 50Ω during life, low current level switching.

Referenced documents:
MI-DTL-8834

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy – AS
Air Force - 85
DLA - CC

Review activities:
Army - AR, MI
Air Force - 99

Preparing activity:
DLA – CC

(Project 5930-2017-020)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/ .

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:36Z
Check the source to verify that this is the current version before use.