INCH-POUND

MS24183M
25 August 2021
SUPERSEDING
MS24183L
15 April 2003

DETAIL SPECIFICATION SHEET

RELAYS, ELECTROMAGNETIC, 200 AMPERES, 1 PST (N.O.), TYPE I, HERMETICALLY SEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the relay described herein shall consist of this specification and the latest issue of MIL-PRF-6106.





FIGURE 1. Dimensions and configurations.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:49Z
Check the source to verify that this is the current version before use.



CIRCUIT D1

Inches	mm	Inches	mm
.010	0.25	.969	24.56
.031	0.79	1.375	34.93
.063	1.60	1.500	38.10
.095	2.41	1.844	46.84
.193	4.90	2.065	52.45
.266	6.76	2.647	67.25
.312	7.92	2.957	75.11
.320	8.13	3.000	76.20
.453	11.51	3.282	83.36
.750	19.05	3.672	93.27
.844	21.44		

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.031.
4. Referenced Government documents of the issue listed in that issue of the Acquisition Streamlining and Standardization Information System (ASSIST) specified in the solicitation forms a part of this specification sheet to the extent specified herein.
5. Coil and auxiliary terminals may use an additional flat washer for terminal seat.
6. Cadmium or cadmium compounds are prohibited on external hardware. A transition period to non-cadmium hardware is authorized for up to 1 year from the date of this revision.
7. Spring washer on drawing is a spring lock washer.
8. MS27243-2 is a part identified in MS27243.

FIGURE 1. Dimensions and configurations - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:49Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configurations: See figure 1.

PIN's and general characteristics: See table I.

Contact data:

Load ratings: See table II.

Maximum contact drop:

Initial: 0.150 volt.

After life test: 0.175 volt.

Overload current (NO): 1,600 amperes.

Rupture current (NO): 2,000 amperes.

Coil data: See table III.

Duty rating: Continuous.

Electrical data:

Minimum insulation resistance:

Initial: 100 megohms.

After life or environmental test: 50 megohms.

Dielectric strength: Sea level, 2-5 seconds:

	Initial		After life tests	
	28 V dc	115 V ac	28 V dc	115 V ac
Coil to case	1,250 V rms	1,500 V rms	1,000 V rms	1,125
All other points	1,250 V rms	1,500 V rms	1,000 V rms	1,125

Dielectric strength (altitude): 1 minute.

	28 V dc	115 V ac
Coil to case	500 V rms	500 V rms
All other points	500 V rms	500 V rms

Environmental characteristics:

Temperature range: -70°C to + 71°C.

Max altitude rating: 80,000 feet.

Shock, g-level: 25 g's.

Duration: 6-9 ms.

Maximum duration contact opening: 2 ms.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:49Z
Check the source to verify that this is the current version before use.

Vibration, (sinusoidal): See table IV.

Vibration (random) and high shock: Not applicable.

Acceleration: 15 g's.

TABLE I. PIN's and general characteristics. 1/

PIN MS24183-	Type	Coil	Terminal type	Mounting or mating socket	Auxiliary contacts	Maximum weight (pounds) 2/
D1	I	dc	Stud	Flange	None	1.7

1/ A1 and A2 have been canceled without replacement. D2 has been superseded by MS24142-D2.
2/ Weights include covers and barriers.

TABLE II. Rated contact load (amperes per pole) case grounded. 1/

Type of load	Life operating cycles x 10^3	28 V dc				115 V ac, 1 phase				115/200 V ac, 3 phase 2/			
		Main		Aux		Main		Aux		Main		Aux	
		NO	NC	NO	NC	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz	400 Hz	60 Hz
Resistive	50	200				200							
Inductive	10	100											
Motor	50	200				150							
Mechanical life reduced current	100	50				50							
Mixed loads	50	20	Applicable per MIL-PRF-6106			10							

1/ Absence of value indicates parameter is not applicable to this specification.
2/ Absence of value indicates relay is not rated for three phase application.

TABLE III. Operating characteristics.

PIN MS 24183-	Coil data											Time - milliseconds max 1/					
	Coil	Rated			Max		Max pick-up voltage			Hold voltage 1/	Drop out voltage 1/	Operate 3/	Release 4/	Contact Bounce 5/			
														Main		Aux 5/	
		Volts 2/	Freq Hz	Ω Res +15% -10	Volts	Amp	Normal 1/	High temp test	Cont current test					NO	NC	NO	NC
D1	X1,X2	28	dc	64.5	29	.55	18	21	22.5	7.0	1.0	30	10	4.0	---	---	---

1/ Over the temperature range.
2/ CAUTION: Use of any coil voltage less than rated coil voltage will compromise the operation of the relay.
3/ With rated coil voltage.
4/ From rated coil voltage.
5/ Absence of value indicates parameter is not applicable to this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:49Z
Check the source to verify that this is the current version before use.

TABLE IV. Vibration levels.

Part number MS24183-	5-10 Hz	10-55 Hz	55-250 Hz	250-500 Hz	500-1,500 Hz
D1	.08 DA	.06 DA	8 g's	8 g's	5 g's

Qualification by similarity: See MIL-PRF-6106.

Part or Identifying Number (PIN): MS24183-D1.

For government logistical purposes, use MS24183-D1 in lieu of the MS25033-1.

Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the previous issue.

Referenced documents. In addition to MIL-PRF-6106, this document references the following:
MS24142 MS27243

Custodians:
Navy - AS
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5945-2021-025)

Review activity:
Navy - EC

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T14:49Z
Check the source to verify that this is the current version before use.