FED. SUP CLASS 5305

REVIEWER: AV, IS
USER: AS, AT, MC, ME, OS, SH, WT, YD




TABLE I

NOMINAL SIZE		.086	.112	.138	.164	.190	.250	.3125	.375
THREADS PER INCH, UNF-2A		64	48	40	36	32	28	24	24
D BODY DIAMETER	MAX	.0860	.1120	.1380	.1640	.1900	.2500	.3125	.3750
	MIN	.0733	.0954	.1184	.1424	.1658	.2225	.2806	.3430
A HEAD DIAMETER	MAX	.140	.183	.226	.270	.313	.414	.518	.622
	MIN	.124	.166	.208	.250	.292	.389	.490	.590
H HEAD SIDE HEIGHT	MAX	.062	.079	.096	.113	.130	.170	.211	.253
	MIN	.055	.072	.099	.106	.123	.161	.201	.242
O TOTAL HEAD HEIGHT	MAX	.083	.107	.132	.156	.180	.237	.295	.355
	MIN	.070	.094	.118	.141	.165	.219	.276	.333
J SLOT WIDTH	MAX	.031	.039	.048	.054	.060	.075	.084	.094
	MIN	.023	.031	.039	.045	.050	.064	.072	.081
T SLOT DEPTH	MAX	.030	.036	.045	.065	.075	.102	.130	.154
	MIN	.022	.030	.035	.054	.064	.087	.110	.134
E DRILL LOCATION	NOM	.026	.035	.043	.043	.043	.062	.078	.094
F DRILLED HOLE DIA	NOM	.031	.037	.046	.046	.046	.062	.070	.070
R RADIUS Ⓑ	MAX	.013	.017	.021	.025	.028	.038	.047	.056
TENSILE STRENGTH, LBS-MIN Ⓑ		240	400	620	900	1,240	2,250	3,600	5,430

L LENGTH	TOLERANCE	DASH NO.*	DASH NO.*	DASH NO.*	DASH NO.*	DASH NO.	DASH NO.	DASH NO.	DASH NO.
.12 .19 .25 .31 .39 .44 .50 .62 .75 .88 1.00	+.00 -.03	1 2 3 4 5 6 7 8 9 10	11 12 13 14 15 16 17 18 19 20 21	24 25 26 27 28 29 30 31 32 33 34	39 40 41 42 43 44 45 46 47 48 49	58 59 60 61 62 63 64 65 66 67	76 77 78 79 80 81 82 83	92 93 94 95 96 97 98	107 108 109 110 111
1.25 1.50 1.75 2.00	+.00 -.06		22 23	35 36 37 38	50 51 52 53	68 69 70 71	84 85 86 87	99 100 101 102	112 113 114 115
2.25 2.50 2.75 3.00	+.00 -.09				54 55 56 57	72 73 74 75	88 89 90 91	103 104 105 106	116 117 118 119

Ⓑ * Dash numbers 1 thru 57 are INACTIVE FOR NEW DESIGN AFTER 6 March 1974.

Ⓑ FOR CHANGES SEE SHEETS 1 AND 2.

APPROVED 9 FEB 1954 REVISED Ⓐ 18 JUN 1962 Ⓑ 6 MAR 1974

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document.

P.A. MC
Other Cust 82

TITLE: SCREW, MACHINE-DRILLED FILLISTER HEAD, SLOTTED, ALUMINUM ALLOY, UNF-2A

MILITARY STANDARD
MS35278

PROCUREMENT SPECIFICATION FF-S-92

SUPERSEDES MS35361 in part; MS35366 in part

SHEET 1 OF 2

DD FORM 672-1 (COORDINATED)

Source: https://assist.dla.mil -- Downloaded: 202610-23T17:14Z
Check the source to verify that this is the current version before use.

FED. SUP CLASS 5305

NOTES:

(B) 1. MATERIAL: Aluminum alloy, 2024, in accordance with QQ-A-200/3 or QQ-A-225/6. The minimum ultimate tensile strength shall be 62,000 PSI.

2. PROTECTIVE COATING: Anodized in accordance with MIL-A-8625, Type I or II, Class 1.

3. THREADS: The threads shall be in accordance with Screw-Thread Standards for Federal Services, Handbook H28.

4. DIMENSIONS: All dimensions in Table I are in inches.
All dimensions in Table II are in millimetres.

5. PART NUMBER: The MS part number consists of the MS number, plus the dash number.
Example: MS35278-58.

(B) 6. THREAD LENGTH: Full form threads shall extend to within 2 threads or less of head bearing surface for lengths thru 2.00 inches/50.80 millimetres. Longer lengths shall have a minimum full form thread length of 1.50 inches/38.10 millimetres.

7. The drilled hole shall be approximately at a right angle to the slot and may be permitted to break through the bottom of the slot. All burrs and sharp edges shall be removed.

8. Referenced documents shall be of the issue in effect on date of invitations for bid.

9. For design feature purposes, this standard takes precedence over procurement documents referenced herein.

REVIEWER: AV, IS
USER: AS, AT, MC, ME, OS, SH, WY, YD

(B)
TABLE II
METRIC TRANSLATION OF TABLE I

NOMINAL SIZE			2.18	2.84	3.51	4.17	4.83	6.35	7.94	9.52
THREAD PITCH			.40	.53	.64	.71	.79	.91	1.06	1.06
D BODY DIAMETER		MAX	2.18	2.64	3.51	4.17	4.83	6.35	7.94	9.52
		MIN	1.86	2.42	3.01	3.62	4.21	5.65	7.13	8.71
A HEAD DIAMETER		MAX	3.56	4.65	5.74	6.86	7.95	10.52	13.16	15.80
		MIN	3.15	4.22	5.28	6.35	7.42	9.88	12.45	14.99
H HEAD SIDE HEIGHT		MAX	1.57	2.01	2.44	2.87	3.30	4.32	5.36	6.43
		MIN	1.40	1.63	2.26	2.69	3.12	4.09	5.11	6.15
O TOTAL HEAD HEIGHT		MAX	2.11	2.72	3.35	3.96	4.57	6.02	7.49	9.02
		MIN	1.78	2.39	3.00	3.58	4.19	5.56	7.01	8.46
J SLOT WIDTH		MAX	.79	.99	1.22	1.37	1.52	1.90	2.13	2.39
		MIN	.58	.79	.99	1.14	1.27	1.63	1.83	2.06
T SLOT DEPTH		MAX	.76	.97	1.14	1.65	1.90	2.59	3.30	3.91
		MIN	.56	.76	.89	1.37	1.63	2.21	2.79	3.40
E DRILL LOCATION		NOM	.66	.89	1.09	1.09	1.09	1.57	1.98	2.39
F DRILLED HOLE DIA		NOM	.79	.94	1.17	1.17	1.17	1.57	1.78	1.78
R RADIUS		MAX	.33	.43	.53	.64	.71	.97	1.19	1.42

L LENGTH	TOLERANCE	DASH NO.*	DASH NO.*	DASH NO.*	DASH NO.*	DASH NO.	DASH NO.	DASH NO.	DASH NO.
3.05	+.00 -.76	1	11	24	39				
4.83		2	12	25	40	58			
6.35		3	13	26	41	59			
7.87		4	14	27	42	60	76		
9.65		5	15	28	43	61	77	92	
11.18		6	16	29	44	62	78	93	
12.70		7	17	30	45	63	79	94	107
15.75		8	18	31	46	64	80	95	108
19.05		9	19	32	47	65	81	96	109
22.35		10	20	33	48	66	82	97	110
25.40			21	34	49	67	83	98	111
31.75	+.00 -1.52		22	35	50	68	84	99	112
38.10			23	36	51	69	85	100	113
44.45				37	52	70	86	101	114
50.80				38	53	71	87	102	115
57.15	+.00 -2.29				54	72	88	103	116
63.50					55	73	89	104	117
69.85					56	74	90	105	118
76.20					57	75	91	106	119

* Dash numbers 1 thru 57 are INACTIVE FOR NEW DESIGN AFTER 6 March 1974.

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection of all new engineering and design applications and for repetitive use shall be made from this document.

(B) FOR CHANGES SEE SHEETS 1 AND 2

(A) REVISED 18 JUN 1962

APPROVED 9 FEB 1954

P.A. WC Other Cust 82	TITLE SCREW, MACHINE-DRILLED FILLISTER HEAD, SLOTTED, ALUMINUM ALLOY, UNF-2A	MILITARY STANDARD MS 35278
PROCUREMENT SPECIFICATION FF-S-92	SUPERSEDES: MS35361 in part; MS35366 in part	SHEET 2 OF 2

DD FORM 672-1 (Continued)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:14Z
Check the source to verify that this is the current version before use.