FED. SUP CLASS
6850

REVIEWER: GL MD MI MR PS

USER: MO SM

PART NUMBER	PACKAGING
MS36420-1	5 gal pail
MS36420-2	55 gal drum

SAFETY PRECAUTIONS:

DANGER! HARMFUL OR FATAL IF SWALLOWED.
CAUTION! CAUSES SEVERE BURNS. RAPIDLY ABSORBED THROUGH SKIN.
CAUTION! VAPOR IRRITATING

The ingredient materials used in the manufacture of this compound are toxic and caustic, and proper precautions should be taken to prevent contact with skin and clothing and to avoid inhalation of the vapors. If eye contact should occur, flush thoroughly with plentiful amounts of water for at least 15 minutes. If eye contact should occur, or if the compound is accidently swallowed, call a physician immediately. If skin contact should occur, remove clothing and wash affected skin area with plentiful amounts of water.

INTENDED USE: For use in softening and removing carbon and fuel gum deposits from engine parts by immersion in solution heated to 140 degrees Fahrenheit. Rinse with water or petroleum solvent.

MATERIAL: Liquid. Ready to use.

REQUIREMENTS: Chemical composition is given below. For ingredient properties, see Sheet #2. Minimum flash point, 160 degrees Fahrenheit.

CHEMICAL COMPOSITION

Ingredient material	Percent by volume	Percent by weight
Orthodichlorobenzene (min)		53
Cresylic acid (100% acid basis) (min)		23
Potassium oleate (anhydrous basis)		
maximum		12
minimum		10
Water (max)		5
Inhibitors and other material (max)		5

NOTE: 1. Reference documents shall be of the issue in effect on date of invitations for bid.

APPROVED 12 March 1965 REVISED

This standard approved by the Munitions Command Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

P.A. MU Other Cust	TITLE CARBON REMOVING COMPOUND orthodichlorobenzene	MILITARY STANDARD MS36420(MU)
Procurement Specification MIL-C-25107	SUPERSEDES:	SHEET 1 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.

REVIEWER: GL MD MI MR PS
USER: MO SM

Properties of Orthodichlorobenzene

Property	Requirement
Distillation range 5% to 95% point	175° to 184°C
Specific Gravity (25°/25°C) (min)	1.29
Free acid (HCl) (max)	0.01% by wt
Flash point (closed cup) (min)	68°C

Properties of Cresylic Acid

Property	Requirement
Distillation range	Initial point 180°C min 50% point 200°-220°C 90% point 230°C max
Tar acids (percent by weight)	95 min

Shall be an isometric mixture of cresols, free of suspended matter when examined by transmitted light, colorless to brown-yellow or pink in color. Shall have the characteristic spicy phenolic odor; shall contain no mercaptans or other odoriferous compounds in such quantity as to produce obnoxious odors under service conditions.

Properties of Oleic Acid (distilled red oil)

Property	Requirement
Acid number (min)	182
Saponification number	197 - 203
Iodine number	80 - 93
Titer	6° to 10°C
Rosin or rosin soap	None

Properties of Potassium Hydroxide

Property	Requirement
Actual KOH (min)	83%
KCl as Cl (max)	0.04%
Iron as FE (max)	0.01%

This standard approved by the Munitions Command Department of the Army and is mandatory for use by that activity. All other military activities are required to employ this standard where suitable.

APPROVED 12 March 1965 REVISED

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T17:40Z
Check the source to verify that this is the current version before use.