INCH-POUND

MS51811G
30 March 2022
SUPERSEDING
MS51811F
3 April 2018


DETAIL SPECIFICATION SHEET

TEE, TUBE, FLARELESS TYPE HYDRAULIC

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Reactivated after 3 April 2018 and may be used for new and existing designs and acquisitions.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-18866.



See notes at end of figure.

FIGURE 1. Tee, tube.

AMSC N/A
FSC 4730

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

Standard sizes

Dash number (see note 6)		Tube OD inches (mm)	B (See note 5)	D dia. Drill inches (mm)	M inches (mm) ±.03 (0.8)
Assembly	Body				
1	31	.1250 (3.175)	.3125 - 24UNF	.093 (2.36)	.77 (19.56)
2	32	.1875 (4.763)	.3750 - 24UNF	.125 (3.18)	.83 (21.08)
3	33	.2500 (6.350)	.4375 - 20UNF	.203 (5.16)	.89 (22.61)
5	35	.3125 (7.936)	.5000 - 20UNF	.234 (5.94)	.95 (24.13)
8	38	.3750 (9.525)	.5625 - 18UNF	.281 (7.14)	1.05 (26.67)
15	45	.5000 (12.700)	.7500 - 16UNF	.422 (10.72)	1.25 (31.75)
17	47	.6250 (15.875)	.8750 - 14UNF	.500 (12.70)	1.42 (36.07)
18	48	.7500 (19.050)	1.0625 - 12UN	.656 (16.66)	1.58 (40.13)
19	49	.8750 (22.225)	1.1875 - 12UN	.718 (18.24)	1.66 (42.16)
22	52	1.0000 (25.400)	1.3125 - 12UN	.875 (22.23)	1.73 (43.94)
27	57	1.2500 (31.750)	1.6250 - 12UN	1.093 (27.76)	1.89 (48.01)
28	58	1.5000 (38.100)	1.8750 - 12UN	1.344 (34.14)	2.02 (51.31)
29	59	2.0000 (50.800)	2.5000 - 12UN	1.813 (46.05)	2.45 (62.23)

See notes at end of figure.

FIGURE 1. Tee, tube - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

Nonstandard sizes

Dash number (see note 6)		Tube OD nom ends		
Assy	Body	End 1	End 2	End 3
4	34	.3750 (9.525)	.3750 (9.525)	.2500 (6.35)
6	36	.3750 (9.525)	.3125 (7.950)	.3125 (7.95)
7	37	.3125 (7.950)	.3125 (7.950)	.3750 (9.53)
9	39	.5000 (12.700)	.3750 (9.525)	.3750 (9.53)
10	40	.5000 (12.700)	.5000 (12.70)	.3750 (9.53)
11	41	.625 (15.875)	.3750 (9.525)	.3750 (9.53)
12	42	1.2500 (31.750)	1.250 (31.75)	.3750 (9.53)
13	43	.3750 (9.525)	.3750 (9.525)	.5000 (12.70)
14	44	.5000 (12.700)	.3750 (9.525)	.5000 (12.70)
16	46	1.0000 (25.400)	1.0000 (25.400)	.5000 (12.70)
20	50	1.5000 (38.100)	.8750 (22.225)	.8750 (22.23)
21	51	1.5000 (38.100)	1.5000 (38.100)	.8750(22.23)
23	53	1.2500 (31.750)	1.0000 (25.400)	1.0000 (25.40)
24	54	1.0000 (25.400)	1.0000 (25.400)	1.2500 (31.75)
25	55	1.000 (25.400)	1.2500 (31.750)	1.2500 (31.75)
26	56	1.2500 (31.750)	.6250 (15.875)	1.2500 (31.75)

See notes at end of figure.

FIGURE 1. Tee, tube - Continued.

Dash number (see note 6)		Ends			B (See Note 5)
Assy	Body	1	2	3	
4	34	X	X		.5625 - 18UNF
				X	.4375 - 20UNF
6	36	X			.5625 - 18UNF
			X	X	.5000 - 20UNF
7	37	X	X		.5000 - 20UNF
				X	.5625 - 18UNF
9	39	X			.7500 - 16UNF
			X	X	.5625 - 18UNF
10	40	X	X		.7500 - 16UNF
				X	.5625 - 18UNF
11	41	X			.8750 - 14UNF
			X	X	.5625 - 18UNF

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

12	42	X	X		1.6250 - 12UN
				X	.5625 - 18UNF
13	43	X	X		.5625 - 18UNF
				X	.7500 - 16UNF
14	44	X		X	.7500 - 16UNF
			X		.5625 - 18UNF
16	46	X	X		1.3125 - 12UN
				X	.7500 - 16UNF
20	50	X			1.8750 - 12UN
			X	X	1.1875 - 12UN
21	51	X	X		1.8750 - 12UN
				X	1.1875 - 12UN
23	53	X			1.6250 - 12UN
			X	X	1.3125 - 12UN
24	54	X	X		1.3125 - 12UN
				X	1.6250 - 12UN
25	55	X			1.3125 - 12UN
			X	X	1.6250 - 12UN
26	56	X		X	1.6250 - 12UN
			X		.8750 - 14UNF

See notes at end of figure.

FIGURE 1. Tee, tube - Continued.

Nonstandard sizes - continued

Dash number (see note 6)		D dia. Drill inches (mm)	M inches (mm) ±.03 (0.8)	Dash number (see note 6)		D dia. Drill inches (mm)	M inches (mm) ±.03 (0.8)
Assy	Body			Assy	Body		
4	34	.281 (7.14)	1.05 (26.67)	14	44	.422 (10.72)	1.25 (31.75)
		.203 (5.16)	1.03 (26.16)			.281 (7.14)	1.14 (28.96)
6	36	.281 (7.14)	1.05 (26.67)	16	46	.875 (22.23)	1.73 (43.94)
		.234 (5.94)	1.03 (26.16)			.422 (10.72)	1.58 (40.13)
7	37	.234 (5.94)	1.03	20	50	1.344 (34.14)	2.02

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

			(26.16)
		.281 (7.14)	1.05 (26.67)
9	39	.422 (10.72)	1.25 (31.75)
		.281 (7.14)	1.14 (28.96)
10	40	.422 (10.72)	1.25 (31.75)
		.281 (7.14)	1.14 (28.96)
11	41	.500 (12.70)	1.42 (36.07)
		.281 (7.14)	1.24 (31.50)
12	42	1.093 (27.76)	1.89 (48.01)
		.281 (7.14)	1.63 (41.40)
13	43	.281 (7.14)	1.14 (28.96)
		.422 (10.72)	1.25 (31.75)

			(51.31)
		.718 (18.24)	2.02 (51.31)
21	51	1.344 (34.14)	2.02 (51.31)
		.718 (18.24)	2.02 (51.31)
23	53	1.093 (27.76)	1.89 (48.01)
		.875 (22.23)	1.89 (48.01)
24	54	.875 (22.23)	1.89 (48.01)
		1.093 (27.76)	1.89 (48.01)
25	55	.875 (22.23)	1.89 (48.01)
		1.093 (27.76)	1.89 (48.01)
26	56	1.093 (27.76)	1.89 (48.01)
		.500 (12.70)	1.81 (45.97)

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Break all sharp edges, remove all burrs, and slivers.
4. Dimensions and tolerances not shown shall be in accordance with SAE-J514.
5. Threads shall be in accordance with ASME B1.1.
6. Assemblies are only furnished to this specification (body, nut, and sleeve). Bodies are not to be stocked, stored, or issued.
7. The drawing is for identification purposes only and is not intended to restrict designs and shapes not dimensioned.

FIGURE 1. Tee, tube - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:


Tee, tube shall be as specified on figure 1.

Materials and finish designators shall be in accordance with MIL-DTL-18866.

Unless otherwise specified in MIL-DTL-18866, all platings shall be capable of meeting a minimum of 96 hours salt spray test in accordance with ASTM B117. The fittings shall show no evidence of red corrosion after 96 hours of salt spray. Fluid passages, other openings and internal threads shall not be subject to the plating thickness requirement and may have bare areas provided they are protected with a light film of oil.

Maximum operating pressure. Maximum operating pressure shall be in accordance with SAE-J514.

PIN: The PIN consists of the letters “MS”, the specification number, a dash, number for tee tube assembly/body size, and a letter for material finish designator.



PIN example: MS51811-10 indicates a tee, tube assembly, end one .5000 inch (12.700 mm), end two .5000 inch (12.700 mm), and end three .3750 inch (9.525 mm), ends one and two have .7500 - 16UNF threads, end three has .5625 - 18UNF threads, steel cadmium plated.

Marking shall be in accordance with MIL-DTL-18866.

Class I and II ozone depleting substances (ODS) shall not be used in MS51811 or any referenced procedures.

Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Referenced documents shall be of the issue in effect on date of invitations for bid.

NOTE: The following restrictions do not apply to manufacturers of the fittings and is applicable only to OEM’s and users.

Cadmium is not recommended. To the users of this document, it is recommended that the use of carbon steel material with cadmium plating be used only when other materials and finishes specified in this document cannot meet performance requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

Army and Marine ground vehicle applications using zinc plating. PIN codes FC, FD, Z, and ZC finishes have a chromate conversion coating which includes hexavalent chromium and are not recommended for Army and Marine ground systems. The use of coatings depositing hexavalent chromium for Army vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement. For new designs PIN codes FC, FD, Z, and ZC are not to be supplied to Army and Marine ground forces. PIN code KA (MIL- PRF- 32647 Type K20) is intended as a hazardous free plating material and is a direct replacement for zinc plating with a hexavalent chromium conversion coating. PIN code KA has equivalent torque/tension behavior as the zinc plating it replaces.

Army and Marine ground vehicles. The use of cadmium plating for Army and Marine ground vehicles is prohibited unless otherwise explicitly stated in the contract as a requirement.

Army and Marine ground vehicle applications using cadmium plating. Pin code J or KB may be substituted for cadmium ("Blank" PIN code) for Army ground vehicle applications. PIN code KB (MIL-PRF-32647 Type K16) is intended as a hazardous free plating material and is a direct replacement for cadmium plating ("Blank" PIN code). PIN code KB has an equivalent torque/tension behavior as the cadmium plating it replaces.

NAVSEA shipboard owned equipment. Cadmium is prohibited from use in NAVSEA-owned shipboard systems in accordance with the requirements of T9070-AL-DPC-020/077-2, unless otherwise approved by NAVSEA.

Table II provides a detail reference data listing for MS39198 to MS51811. This table contains coordination of equivalent tube sizes, in both compression and hydraulic type tees'. Assembly replacement is authorized.

TABLE II. Assembly equivalency (for information only).

Compression	Hydraulic	Compression	Hydraulic	Compression	Hydraulic
MS39198	MS51811	MS39198	MS51811	MS39198	MS51811
-1	-1	-11	-10	-21	-20
-2	-2	-12	-11	-22	-21
-3	-3	-13	-12	-23	-22
-4	-4	-14	-13	-24	-23
-5	-5	-15	-14	-25	-24
-6	-6	-16	-15	-26	-25
-7	-7	-17	-16	-27	-26
-8	-8	-18	-17	-28	-27
-9	None	-19	-18	-29	-28
-10	-9	-20	-19		

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue, due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-18866, this document references the following:

MS39198
MS51825
MS51823
ASME B1.1
ASTM B117
MIL-PRF-32647
SAE-J514
T9070-AL-DPC-020/077-2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army - AT
Navy - SH
Air Force – 71
DLA - CC

Preparing activity:
DLA - CC

(Project 4730-2022-003)

Review activities:
Army - AR, MI
Navy - AS, CG, SA

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T18:08Z
Check the source to verify that this is the current version before use.