
FED SUP CLASS
5306



SECTION THRU THREAD PROFILE

OPTIONAL SHAPE OF HEAD

TABLE I DASH NUMBER AND DIMENSIONS

DASH NO.	L	K +.000 -.060	APPROX WEIGHT LBS/100
-06	.938	1/	8.41
-07	1.000	1/	8.70
-08	1.062	1/	8.99
-09	1.125	1/	9.28
-10	1.188	1/	9.57
-11	1.250	1/	9.86
-12	1.312	1/	10.15
-13	1.375	.125	10.45
-14	1.438	.188	10.74
-15	1.500	.250	11.04
-16	1.562	.312	11.33
-17	1.625	.375	11.63
-18	1.688	.438	11.92
-19	1.750	.500	12.22
-20	1.875	.625	12.81
-21	2.000	.750	13.41
-22	2.125	.875	14.00
-23	2.250	1.000	14.61
-24	2.375	1.125	15.21
-25	2.500	1.250	15.82
-26	2.625	1.375	16.42
-27	2.750	1.500	17.01
-28	2.875	1.625	17.61
-29	3.000	1.750	18.22
-30	3.125	1.875	18.83
-31	3.250	2.000	19.43
-32	3.375	2.125	20.04
-33	3.500	2.250	20.65
-34	3.625	2.375	21.26
-35	3.750	2.500	21.86
-36	3.875	2.625	22.47
-37	4.000	2.750	23.07
-38	4.125	2.875	23.68
-39	4.250	3.000	24.29
-40	4.375	3.125	24.89
-41	4.500	3.250	25.50
-42	4.625	3.375	26.11
-43	4.750	3.500	26.71
-44	4.875	3.625	27.32
-45	5.000	3.750	27.92
-46	5.125	3.875	28.53
-47	5.250	4.000	29.13
-48	5.375	4.125	29.74
-49	5.500	4.250	30.35
-50	5.625	4.375	30.95
-51	5.750	4.500	31.56
-52	5.875	4.625	32.16
-53	6.000	4.750	32.77

1/ THREAD TO HEAD. MAXIMUM TWO IMPERFECT THREADS.

REQUIREMENTS:

1. MATERIAL: STEEL AMS 6322.
2. THREADS: THREADS IN ACCORDANCE WITH MIL-S-7742. INCOMPLETE THREADS NOT TO ENTER FILLET.
3. HARDNESS: 26-32 HRC
4. FINISH: BLACK OXIDE TREATMENT IN ACCORDANCE WITH AMS 2485.
5. DIMENSIONING AND TOLERANCING: DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
6. WRENCHING CONFIGURATION: WRENCHING CONFIGURATION IN ACCORDANCE WITH AS 870.
7. SURFACE TEXTURE : SURFACE TEXTURE, UNLESS OTHERWISE SPECIFIED, SHALL BE 125 MICROINCHES EXCEPT UPSET HEAD IN ACCORDANCE WITH ANSI B46.1.
8. MAGNETIC PARTICLE INSPECTION: MAGNETIC PARTICLE INSPECTION IN ACCORDANCE WITH AMS 2640.

APPROVED 5 AUG 57 REVISED (A) 6 MAY 87

(A) ENTIRE STANDARD REVISED

P.A.	INTERNATIONAL INTEREST	TITLE	
NAVY-AS		BOLT-MACHINE,STEEL, DRILLED 12 POINT HEAD, .500-20,BLACK OXIDE	MILITARY STANDARD
Other Cust			MS9174
AIR FORCE-11			
PROCUREMENT SPECIFICATION: AMS 7452	SUPERSEDES:		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5306-1168

USER ACTIVITIES:

REVIEWER ACTIVITIES: DLA-IS

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited. This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:12Z
Check the source to verify that this is the current version before use.

9. TOLERANCES : UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSIONS ±.010, ANGULAR DIMENSIONS ±5°.

10. EDGES : BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.

11. PART NUMBER : THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9174-06

DASH NUMBER

BASIC MS NUMBER

MS9174-06 INDICATES: BOLT-MACHINE, STEEL, DRILLED 12 POINT HEAD, .500-20, BLACK OXIDE, .938 LONG.

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBERS.
3. IN THE EVENT OF A CONFLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE SAE AEROSPACE PROPULSION DIVISION.
6. AS AND AMS ARE SAE PUBLICATIONS.

USER ACTIVITIES:

REVIEWER ACTIVITIES:
DLA-IS

APPROVED 5 AUG 57 REVISED (A) FOR CHANGES SEE PAGES 1 AND 2

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable.

P.A. NAVY-AS	INTERNATIONAL INTEREST	TITLE BOLT-MACHINE, STEEL, DRILLED 12 POINT HEAD, .500-20, BLACK OXIDE	MILITARY STANDARD
Other Cust AIR FORCE-11			MS9174
PROCUREMENT SPECIFICATION AMS 7452	SUPERSEDES:		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:12Z
Check the source to verify that this is the current version before use.