MILITARY SPECIFICATION SHEET

CONDUIT, FLEXIBLE, WEATHERPROOF, 45 DEGREE CONDUIT FITTING

This amendment forms a part of MIL-C-24758/3(SH), dated 5 August 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

Table I. Delete and substitute.

"TABLE I. Dimensions.

CONDUIT SIZE CODE	FITTING DIMENSIONS							
	B THREAD CODE (Class 2B)	G +.01 -.02	S ±.06	R BEND RADIUS ±.06	W WALL THICK. (Min.)	L CONE LENGTH ±.12	E KNURL LENGTH ±.06	M DIA. (Max.)
02	0.4375 - 28 UNEF	0.14	0.37	0.43	0.028	0.75	0.50	0.93
03	0.5625 - 24 UNEF	0.17	0.37	0.56	0.028	0.75	0.50	1.12
04	0.6875 - 24 UNEF	0.17	0.37	0.75	0.028	0.75	0.62	1.25
05	0.8125 - 20 UNEF	0.23	0.37	0.87	0.028	0.75	0.62	1.43
06	0.9375 - 20 UNEF	0.23	0.37	1.06	0.028	0.75	0.75	1 62
08	1.250 - 18 UNEF	0.29	0.43	1.37	0.028	1.00	0.75	1.81
10	1.5625 - 18 UNEF	0 29	0 43	1.68	0.028	1.00	0.87	2 18
12	1.875 - 16 UN	0.35	0.43	2.06	0.058	1.00	0.87	2.56
16	2.375 - 16 UN	0.35	0 43	2 68	0.058	1.00	1.00	3.06
20	2.875 - 16 UN	0.35	0.43	3.31	0.058	1.00	1.00	3.68
24	3.375 - 16 UN	0.35	0.50	4 50	0.058	1.00	1.00	4.38

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:46Z
Check the source to verify that this is the current version before use.

Preparing activity:
Navy - SH
(Project 5975-N086)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:46Z
Check the source to verify that this is the current version before use.