MILITARY SPECIFICATION SHEET

CONDUIT, FLEXIBLE, WEATHERPROOF, 90 DEGREE CONDUIT FITTING

This amendment forms a part of MIL-C-24758/4(SH), dated 5 August 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I: Delete and substitute:

"TABLE I. Dimensions.

CONDUIT SIZE CODE	FITTING DIMENSIONS								
	B THREAD (Class 2B)	G +.01 -.02	Q ±.06	R BEND RADIUS ±.06	W WALL THICK. (Min.)	L CONE LENGTH ±.06	E KNURL LENGTH ±.06	M DIA (Max.)	N DIA (Max.)
02	0.4375 - 28 UNEF	0.14	0.81	0.43	0.028	0.75	0.50	0.93	0.70
03	0.5625 - 24 UNEF	0.17	0.93	0.56	0.028	0.75	0.50	1.12	0.82
04	0.6875 - 24 UNEF	0.17	1.12	0.75	0.028	0 75	0.62	1.25	0.97
05	0 8125 - 20 UNEF	0.23	1 25	0.87	0.028	0.75	0.62	1.43	1.12
06	0.9375 - 20 UNEF	0.23	1.47	1.06	0.028	0.75	0.75	1.62	1.22
08	1 250 - 18 UNEF	0.29	1.81	1.37	0.028	1.00	0.75	1.81	1.53
10	1.5625 - 18 UNEF	0.29	2.12	1.68	0.028	1.00	0.87	2.18	1.81
12	1.875 - 16 UN	0.35	2.50	2.06	0.058	1.00	0.87	2.56	2.12
16	2.375 - 16 UN	0.35	3.12	2.68	0.058	1.00	1.00	3.06	2.20
20	2.875 - 16 UN	0.35	3.75	3.31	0.058	1.00	1.00	3.68	3.12
24	3.375 - 16 UN	0.35	5.00	4.50	0.058	1.00	1.00	4.38	3.62

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:46Z
Check the source to verify that this is the current version before use.

Preparing activity:
Navy - SH
(Project 5975-N087)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:46Z
Check the source to verify that this is the current version before use.