MILITARY SPECIFICATION SHEET

CONDUIT, FLEXIBLE, WEATHERPROOF, CONDUIT-TO-PANEL FITTING

This amendment forms a part of MIL-C-24758/5(SH), dated 5 August 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I: Delete and substitute:

"TABLE I. Dimensions.

	FITTING DIMENSION					
	A	D	P	L	E	M
SIZE CODE	THREAD (Class 2A)	DIA (Min.)	DIA (Min.)	CONE LENGTH ±.06	KNURL LENGTH ±.06	DIA (Max.)
02	0.625 - 24 UNEF	0.25	0.87	0.75	0.50	0.93
03	0.750 - 20 UNEF	0.37	1.00	0.75	0.50	1.12
04	0.875 - 20 UNEF	0.50	1.12	0.75	0.56	1.25
05	1.000 - 20 UNEF	0.62	1.25	0.75	0.56	1.43
06	1.1875 - 18 UNEF	0.75	1.43	0.75	0.62	1.62
08	1.4375 - 18 UNEF	1 00	1 68	1.00	0.62	1.81
10	1.750 - 16 UNEF	1.25	2.00	1.00	0.68	2.18
12	2.000 - 16 UN	1.50	2.25	1.00	0.68	2.56
16	2.500 - 16 UN	2.00	3.00	1.00	0.75	3.06
20	3.000 - 16 UN	2.50	3.50	1.00	0.75	3.68
24	3.500 - 16 UN	3.00	4.00	1.00	0.75	4.38

"

AMSC N/A FSC 5975

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:46Z
Check the source to verify that this is the current version before use.

NOTES:

1. The function of the MIL-C-24758/5 fitting is to terminate flexible shielding conduit directly to a panel. Two nuts are to be supplied with this fitting. One nut secures the fitting to the panel, and a second nut acts as a lock nut to the first.
2. Dimensions are in inches.
3. Dimensions and configurations: See figure 1 and table I.
4. Material, finish and markings: See MIL-C-24758(SH).

Preparing activity:
Navy - SH
(Project 5975-N093)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:46Z
Check the source to verify that this is the current version before use.