MILITARY SPECIFICATION SHEET

CONDUIT, FLEXIBLE, WEATHERPROOF, CONDUIT-TO-PIPE EXTERNALLY THREADED (TAPERED) FITTING

This amendment forms a part of MIL-C-24758/6(SH), dated 5 August 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 2

TABLE I: Delete and substitute:

"TABLE I Dimensions.

CONDUIT SIZE CODE	FITTING DIMENSIONS				
	A PIPE THD (Class 2A)	D DIA (Min.)	L CONE LENGTH ±.06	M DIA (Max.)	P DIM (Min.)
02	0.25 - 18.0 NPT	0.25	0.75	0.93	0.75
03	0.375 - 18.0 NPT	0.37	0.75	1.12	0.87
04	0.50 - 14.0 NPT	0.50	0.75	1.25	0.96
05	0.75 - 14.0 NPT	0.62	0.75	1.43	1.18
06	0.75 - 14.0 NPT	0.75	0.75	1.62	1.37
08	1.0 - 11 50 NPT	1.00	1.00	1.81	1.50
10	1.25 - 11.50 NPT	1.25	1 00	2.18	1 81
12	1.50 - 11.50 NPT	1.50	1.00	2.56	2.12
16	2.0 - 11.50 NPT	2.00	1.00	3.06	2.62
20	2.50 - 8.0 NPT	2.50	1.00	3.50	3.25
24	3.0 - 8.0 NPT	3.00	1.00	4.38	3.872

"

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:47Z
Check the source to verify that this is the current version before use.

Preparing activity:
Navy - SH
(Project 5975-N088)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:47Z
Check the source to verify that this is the current version before use.