INCH-POUND

MIL-V-24740(SH)
AMENDMENT 1
11 June 1993

MILITARY SPECIFICATION

VALVE, SAFETY: BOILER, REMOTE PILOT OPERATED, FOR SHIPBOARD USE

This amendment forms a part of MIL-V-24740(SH), dated 31 May 1990 and is approved for use by the Naval Sea Systems Command, Department of the Navy and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 7

3.3.1.2, line 3 after "table II" add "for superheater valves and table II-1 for low drum valves".

PAGE 10

TABLE II, Style 18, Delete Ship hull number "AE 27-29" and substitute "AE 26-29, AS 39-41".

TABLE II, Style 22, Delete Ship hull number "AOE 5-7" and substitute "AOR 1-7".
TABLE II, Style 23, Add "AD 41-44" to applicability.

PAGE 11

TABLE II, Style 25, Add "LHD 1-5" to applicability.

PAGE 12

Add new pages 12a, 12b, 12c and 12d blank.

Delete page 12 and substitute page 12e with changes marked in right margin.

PAGE 16

3.4.2.1.2, Add to end of paragraph: "Each pilot valve shall be supplied with a gag."

PAGE 17

3.5.2.1, line 4: Delete "3.5 percent" and substitute "2 percent".

PAGE 19

4.3, line 2: Delete "class and style" and substitute "contract".

PAGE 21

4.6.2(b), last line: Delete "that specified" and substitute "33 cc/hour from either the safety valve or the pilot valve".

Preparing activity:
Navy - SH
(Project 4820-N092)

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:38Z
Check the source to verify that this is the current version before use.

TABLE II-1. Dimensional and design data (low drum safety valve).

Style	Inlet flange type (ANSI B16.5)	Inlet flange size (inch)	Outlet flange type (ANSI B16.5)	Outlet flange size (inch)	Drain flange type (ANSI B16.5)	Drain flange size (inch)	Drain flange location w/regard to outlet (degrees)	Flow rate (lb/hr)	Pop pressure (lb/in^2)	Steam temperature (°F)	Center to inlet (inch, plus or minus 1/16)	Center to outlet (inch, plus or minus 1/16)	Center to drain (inch, plus or minus 1/8)	Inlet to drain (inch, plus or minus 1/8)	Ship hull number
40	Class 1500	2-1/2	Class 300	4	Class 300	1/2	180	61,500	1400	590	7-3/4	7	6-11/16	6-3/32	CV 60-62
41	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	59,500	1430	590	7-3/4	7	6-1/4	4-9/16	CV 67
42	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	65,000	1400	590	7-3/4	7	6-1/4	4-9/16	CG 26-28 CG 32, 34
43	Class 900	4	Class 300	6	Class 300	1/2	180	169,200	785	520	7-3/4	8-3/4	7-1/8	5-1/8	LHA 1-5 LHD 1-5
44	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	65,000	1385	590	7-3/4	7	6-1/4	4-9/16	CG 19-24
45	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	67,500	1425	590	7-3/4	7	6-1/4	4-9/16	CG 29-31 CG 33
46	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	65,000	1375	590	7-3/4	7	6-1/4	4-9/16	DDG 37-39
47	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	54,900	1385	590	7-3/4	7	6-1/2	5-3/32	FF 1052 CL B&W BOILER
48	Class 2500	2-1/2	Class 300	4	Class 300	1/2	180	58,400	1345	590	7-3/4	7	7-1/4	5-1/6	CV 63, 64
49	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	54,900	1350	590	7-3/4	7	6-1/8	5-3/32	DDG 4-6, 8, 14, 15-19, 23, 24
50	Class 1500	2-1/2	Class 300	4	Class 300	1/2	180	63,800	1400	590	7-3/4	7	7-3/4	5-1/16	CG 16-18 DDG 40-46
51	Class 1500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	54,900	1385	590	7-3/4	7	6-1/2	5-3/32	FF 1052 CL CE BOILER
52	Class 2500	2-1/2	Class 300	4	Class 300	1/2	90 CCW	57,000	1440	590	7-3/4	7	6-1/2	5-3/32	CV 66

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:38Z
Check the source to verify that this is the current version before use.

TABLE II-1. Dimensional and design data (low drum safety valve). (Continued)

Style	Inlet flange type (ANSI B16.5)	Inlet flange size (inch)	Outlet flange type (ANSI B16.5)	Outlet flange size (inch)	Drain flange type (ANSI B16.5)	Drain flange size (inch)	Drain flange location w/regard to outlet (degrees)	Flow rate (lb/hr)	Pop pressure (lb/in^2)	Steam temperature (°F)	Center to inlet (inch, plus or minus 1/16)	Center to outlet (inch, plus or minus 1/16)	Center to drain (inch, plus or minus 1/8)	Inlet to drain (inch, plus or minus 1/8)	Ship hull number
53	Class 600	2-1/2	Class 300	4	Class 300	1/2	180	61,100	725	520	5-5/16	6	6-1/2	3-11/32	CV 59
54	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	42,500	700	520	6-1/2	6-3/16	6-25/32	3-27/32	AS 33, 34 AD 37, 38
55	Class 600	2-1/2	Class 300	4	Class 300	1/2	90 CCW	43,668	720	520	6-1/2	6	6-3/4	3-13-16	LKA 113-116
56	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	43,200	710	520	6-1/2	6	6-3/4	3-13/16	LPD 1-15
57	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	43,300	720	520	6	6	6-1/2	3-11/32	AE 27-29 AS 36-37 AS 39-41 LSD 36-40 LKA 117 LCC 19-20 LPH-12 AD 41-44
58	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	43,300	715	520	6	6	6-1/2	3-11/32	AE 32-35
59	Class 900	2	Class 150	3	Class 300	1/2	90 CCW	43,623	715	520	6-11/16	6-3/8	6-1/2	3-11/32	AFS 1-7
60	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	59,800	750	520	6	6	6-3/4	3-5/16	AOE 1-3
61	Class 600	2-1/2	Class 300	4	Class 300	1/2	180	57,800	750	590	5-5/16	6	6-11/16	6-9/16	AOE 4
62	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	43,688	715	520	6-1/2	6-3/16	6-1/2	3-11/32	LPH 2,3,7 10,11

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:38Z
Check the source to verify that this is the current version before use.

TABLE II-1. Dimensional and design data (low drum safety valve). (Continued)

Style	Inlet flange type (ANSI B16.5)	Inlet flange size (inch)	Outlet flange type (ANSI B16.5)	Outlet flange size (inch)	Drain flange type (ANSI B16.5)	Drain flange size (inch)	Drain flange location w/regard to outlet (degrees)	Flow rate (lb/hr)	Pop pressure (lb/in^2)	Steam temperature (°F)	Center to inlet (inch, plus or minus 1/16)	Center to outlet (inch, plus or minus 1/16)	Center to drain (inch, plus or minus 1/8)	Inlet to drain (inch, plus or minus 1/8)	Ship hull number
63	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	45,300	745	530	6	6	6-1/2	3-11/32	AO 177 CL
64	Class 600	2-1/2	Class 300	3-1/2	Class 300	1/2	90 CCW	43,800	715	530	5-5/16	6	6-1/2	3-11/32	LPH-9

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:38Z
Check the source to verify that this is the current version before use.

THIS PAGE INTENTIONALLY LEFT BLANK

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:38Z
Check the source to verify that this is the current version before use.