METRIC
MIL-F-24734/2(NAVY)
31 August 1989

MILITARY SPECIFICATION SHEET

FIBERSCOPE, FIBER OPTIC
TYPE R, STYLE 4, CLASS 1, OPTIONS S (METRIC)

This specification is approved for use by the Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-F-24734.

CLASSIFICATION

Type: R (Rigid fiberscope).
Style: 4 (5.0 mm, working diameter).
Class: 1.
Options: S (90 degree axial viewing angle, 40 degree viewing field).

DESIGN AND CONSTRUCTION

Light source: N/A.
Weight: ≤ 6.8 kg (fiberscope only).
≤ 18.2 kg (carrying case including fiberscope and accessories).

AMSC N/A FSC 6035
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:35Z
Check the source to verify that this is the current version before use.

Ancillary equipment:

(a) Off-set angle adapter with 30 degrees of off-set.
(b) Angle adapter leg 25 cm long.
(c) 35-mm camera adapter.
(d) Video camera adapter.

PERFORMANCE REQUIREMENTS

Eyepiece magnification: 1X.

ENVIRONMENTAL REQUIREMENTS

Temperature range: 1 (minus 54 to plus 85°C, operating;
minus 62 to plus 85°C, storage).

PART OR IDENTIFYING NUMBER: D24734/2-001.

PART DESIGNATOR: R41S.

Review activities:
Navy - AS, EC, YD

Preparing activity:
Navy - SH
(Project 6035-N001-02)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T01:35Z
Check the source to verify that this is the current version before use.