MIL-C-21522 (Wep)
AMENDMENT - 2
1 August 1961

Superseding
AMENDMENT - 1
23 August 1960

# MILITARY SPECIFICATION
# CYLINDERS, LOCKOUT
# FOR
# SHOCK ABSORBER, MISSILE LAUNCHER
# MARK 2 MOD 0

This amendment forms a part of Military Specification MIL-C-21522 (Wep), 16 February 1960, and has been concurred in by the Bureau of Naval Weapons.

Page 6, paragraph 3.3.1.1: Delete and substitute:

3.3.1.1 Vertical Lockout Cylinder - The vertical lockout cylinder, when energized with an air pressure of 4,000 psig, shall return the piston rod from the extreme extended position to the median position and while at the median position shall resist, without displacement (except material deflection and accumulated clearances), a force of 28,700 pounds acting to extend the piston rod, shall show no damage, and thereafter shall meet all performance requirements of this specification.

Page 6, paragraph 3.3.1.2: Delete and substitute:

3.3.1.2 Horizontal Lockout Cylinder - The horizontal lockout cylinder, when energized with an air pressure of 4,000 psig, shall return the piston rod from the extreme travel positions to the median position and while at the median position shall resist, without displacment (except material deflection and accumulated clearances), a force of 11,000 pounds acting to move the piston rod in either direction, shall show no damage, and thereafter shall meet the performance requirements of this specification.

Page 6, paragraph 3.3.2.1: Delete

FSC 1440

Source: https://assist.dla.mil -- Downloaded: 20261O-19T09:47Z
Check the source to verify that this is the current version before use.

3.1.2 Packing (See 6.11).

Page 6, paragraph 3.3.2.2: Delete and substitute:

3.3.2.2 Lockout Cylinder - The lockout cylinder, assembled, shall withstand a hydrostatic proof pressure of 6,750 psig for 10 minutes, shall show no damage, and thereafter shall meet all performance requirements of this specification.

Page 6, paragraph 3.3.3: Delete and substitute:

3.3.3 Leakage - After being energized twice by air at 4,000 psig, the lockout cylinder, when actuated by air at 4,000 psig and allowed to stand with no replenishment, shall show no pressure loss in excess of 200 psig per hour from the 4,000 psig pressure or shall show no leakage in 30 seconds which is in excess of 3 cubic inches of free air for the horizontal cylinders or 6 cubic inches of free air for the vertical cylinders.

Page 13, paragraph 4.5.4.2: Delete and substitute:

4. .4.2 Hydrostatic Test - Each lockout cylinder, assembled, shall be subjected to a hydrostatic proof pressure of 6,750 psig for 10 minutes to meet the requirements of 3.3.2.2.

Page 13, paragraph 4.5.4.3: Delete "and allowed to stand for 1 hour,"

Page 13, paragraph 4.5.4.4.1: Delete and substitute:

4.5.4.4.1 Vertical Lockout Cylinder - Each vertical lockout cylinder, energized with an air pressure of 3,900 ± 100 psig and subjected to a maximum force of 26,200 pounds acting to extend the piston rod from the median position, shall meet the requirements of 3.3.1.1.

Page 13, paragraph 4.5.4.4.2: Delete and substitute:

4.5.4.4.2 Horizontal Lockout Cylinder - Each horizontal lockout cylinder, energized with an air pressure of 3,900 ± 100 psig and subjected to a maximum force of 10,200 pounds acting to move the piston rod from the median position, shall meet the requirements of 3.3.1.2.

Page 13, paragraph 4.6.4: Delete



Source: https://assist.dla.mil -- Downloaded: 20261O-19T09:47Z
Check the source to verify that this is the current version before use.