MIL-C-21526B(Wep)
8 February 1963
Superseding
MIL-C-21526A (Weps)
29 March 1961

MILITARY SPECIFICATION

CONTROL ASSEMBLY, EJECTOR

This specification has been approved by the
Bureau of Naval Weapons, Department of the Navy

1. SCOPE

1.1 Scope - This specification states the requirements for the Ejector Control Assembly for the Ejector Group, Missile, Mark 2 Mod 0 and Mark 4 Mod 0.

2. APPLICABLE DOCUMENTS

2.1 Documents - The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-621	Boxes, Wood, Nailed and Lock-Corner

MILITARY

MIL-P-116	Preservation, Methods of
MIL-S-90l	Shockproof Equipment, Class HI (High-Impact), Shipboard Application, Tests for

FSC 1440

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

2.1 (Cont)

MIL-E-5272	Environmental Testing, Aeronautical and Associated Equipment, General Specification for
MIL-F-18870	Fire Control Equipment, Naval Ship and Shore: General Specification

NAVY DEPARTMENT

BUREAU OF NAVAL WEAPONS, Code ldent 10001

MIL-V-21509	Valve, Explosive
MIL-V-21517	Valve, Blocking

STANDARDS

MILITARY

MIL-STD-129	Marking for Shipment and Storage
MIL-STD-167	Mechanical Vibrations of Shipboard Equipment

DRAWINGS

NAVY DEPARTMENT

BUREAU OF NAVAL WEAPONS, Code Ident 10001

LD 419520	Ejector Control Assembly
2024896	Switch - Pressure
2254290	Dummy Explosive Valve
2254291	Dummy Blocking Valve

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

2.1 (Cont)

PUBLICATIONS

NAVY DEPARTMENT

BUREAU OF NAVAL WEAPONS

NAVWEPS OP 400	General Instructions for the Design, Manufacture, and Inspection of Naval Ordnance Equipment
NAVWEPS OP 2230	Workmanship and Design Practices for Electronic Equipment
NAVORD INST 4355.1	Equipment for Use by Government Inspector in Final Inspection of Naval Ordnance Items
BUWEPS INST 4355.5	Bureau of Naval Weapons Calibration Program
Standards Laboratory	Information Manual

BUREAU OF SHIPS — General Specifications for Building Ships of the United States Navy, Section S9-1, Welding and Allied Processes

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should-be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

2.2 Other Publications - The following documents fern a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply:

NATIONAL BUREAU OF STANDARDS

Handbook H28	Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of 'Documents, Government Printing Office, Washington 25, D.C)

CONSOLIDATED CLASSIFICATION COMMITTEE

Uniform Freight Classification Rules

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Description - The ejector control assembly is a unit assembly of piping, control valves, relief valve, and air-actuated switches which connect the ejector group as a whole to the air supply line. The ejector control assembly provides means for recharging the air system, distributes air at the proper rate to the operating components, releases excess air from the components, provides protection against accidental launching, prevents launching under abnormal air pressure conditions, and electrically signals the existence of normal or abnormal air pressure conditions within the components,

3.1.1 Components - The ejector control assembly shall consist of the assemblies and connecting parts shown on BuWep LD 419520. Of the components included on BuWep LD 419520, the following are covered by separate specification:

Blocking Valve	MIL-V-21517(Wep)
Explosive Valve	MIL-V-21509(Wep)

3.2 General Requirements

3.2.1 Preproduction Samples - Unless otherwise specified in the contract or order, preproduction samples of the ejector control assembly shall be manufactured using the methods and procedures proposed for the production lot. These samples will be tested as specified in section 4 herein and are for the purpose of determining that the production item meets the requirements of this specification (refer to 4.2.1). At the discretion of the procuring agency, the requirement for a preproduction sample may be waived and shall then be satisfied by substitution of a production unit chosen at random by the Government Inspector.

3.2.2 Materials - Unless otherwise specified in the contracts requisition, or order, all materials and purchased parts entering into the final assembly of the ejector control assembly shall conform strictly to the detailed requirements indicated on the drawings and specifications listed in BuWep LD 419520.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

3.2.3 Finishes, Coatings, Construction, and Dimensions - Finishes, coatings, construction, and dimensions for the ejector control assembly shall be in accordance with the applicable drawings, specifications, and publications listed in BuWep LD 419520.

3.2.4 Marking - Marking of assemblies, subassemblies, and parts shall be in accordance with the applicable drawings listed in BuWep LD 419520.

3.2.5 Interchangeability - Individual assemblies and piece parts of assemblies fabricated in agreement with their applicable drawings and specifications shall be interchangeable with like numbered parts,

3.2.6 Gages - The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, requisition, or order, the Government will furnish drawings of pertinent Navy Final Inspection Gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not" serve to relieve the contractor of his responsibility in the design and manufacture of such gages as may be required for the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy Final Inspection Gages.

3.2.7 Threads - Unless otherwise specified, all threads shall be in accordance with the National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings.

3.2.8 Request for Deviations - The procedures for requesting deviations from this specification or any specification, publications material, or process specified herein shall be as set forth in NAVWEPS OP 400.

3.2.9 Conflicting Requirements - In the event of conflict between this specification and any specification, publication, or drawing referenced herein, this specification shall govern.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

3.2.10 Tolerances - Unless otherwise specifically noted, tolerances and accuracies stated herein are absolute.

3.3 Performance Requirements

3.3.1 Hydrostatic Pressure

3.3.1.1 Ejector Control Assembly - The ejector control assembly shall withstand a hydrostatic proof pressure of 740 to 760 psig for 5 minutes, shall show no leakage or damage, and thereafter shall be capable of meeting all performance requirements of this specification.

3.3.1.2 High-Pressure Section, Ejector Control Assembly The high-pressure section of the ejector control assembly shall withstand a hydrostatic proof pressure of 6,650 to 6,850 psig for 5 minutes, shall show no leakage or damage, and thereafter shall be capable of meeting all performance requirements of this specification.

3.3.2 Air Pressure

3.3.2.1 Ejector Control Assembly - The ejector control assembly shall withstand an air pressure of 240 to 260 psig for 5 minutes, shall show no leakage or damages and thereafter shall be capable of meeting all performance requirements of this specification.

3.3.2.2 High-Pressure Section, Ejector Control Assembly - The high-pressure section of the ejector control assembly shall withstand an air pressure of 4,300 to 4,500 psig for 5 minutes, shall show no leakage or damage, and thereafter shall be capable of meeting all performance requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

3.3.2.3 High-Pressure Valves - The following valves, in the closed position, shall withstand an air pressure of 4,300 to 4,500 psig for 5 minutes, shall show no leakage or damage, and thereafter shall be capable of meeting all performance requirements of this specification:

(a) Launch Air Flask Pressure Switch Shutoff Valve

(b) Launch Air Flask Pressure Switch and Gage Shutoff Valve

(c) Launch Air Flask Charging Valve

(d) Dome Charging Valve

(e) Air Vent Valve

(f) Air Supply Valve

3.3.2.4 Low-Pressure Valves - The following valves, in the closed position, shall withstand an air pressure of 240 to 260 psig for 5 minutes, shall show no leakage or damage, and thereafter shall be capable of meeting all performance requirements of this specification:

(a) Dome Pressure Switch Shut-off Valve

(b) Dome Pressure Switch and Gage Shutoff Valve

3.3.3 - Electrical Requirements

3.3.3.1 Dielectric Strength - The dome pressure switch and the air-flask pressure switch shall withstand a potential of 325 volts (rms), 60-cycle AC applied between the mutually insulated portions of a component part, and between insulated portions and the case of the equipment for 1 minute, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

3.3.3.2 Insulation Resistance - The dome pressure switch and the air-flask pressure switch shall show an insulation resistance of at least 3 megohms between the mutually insulated portions of the equipment, and between insulated portions and the case of the equipment under a potential of 500-volts DC, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

3.3.4 Operation

3.3.4.1 Dome Pressure Switch - When subjected to an increasing hydrostatic pressure, the dome pressure switch in the ejector control assembly shall actuate and electrically signal actuation at 136 to 150 psig; shalls on a decreasing hydrostatic pressure, deactuate and electrically signal deactuation at not less than 125 psig.

3.3.4.2 Air-Flask Pressure Switch

3.3.4.2.1 Ejector Group, Missile, Mark 2 Mod O - When subjected to an increasing hydrostatic pressure, the air-flask pressure switch in the ejector control assembly shall actuate and electrically signal actuation at not more than 2,400 psig; shall, on decreasing hydrostatic pressure, deactuate and electrically signal deactuation at 2,000 to 2,100 psigs

3.3.%2.2 Ejector Group, Missile, Mark 4 Mod O - When subjected to an increasing hydrostatic pressure, the air-flask pressure switch in the ejector control assembly shall actuate and electrically signal actuation at not more than 2,200 psig; shall, on decreasing hydrostatic pressure, deactuate and electrically signal deactuation at 1,800 to 1,900 psig.

3.3.4.3 Dome Relief Valve - When subjected to an increasing hydrostatic pressures the dome relief valve in the ejector control assembly shall open at 500 to 550 psig; shall, on decreasing hydrostatic pressures close at not less than 475 pig.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

3.4 Environmental Conditions

3.4.1 Vibration, Operating Condition - The ejector control assembly shall withstand steady-state vibration in accordance with Standard MIL-STD-167, Type I, in the range of 5 to 25 cycles-per-seconds shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

3.4.2 Vibration, Shipping Condition - The ejector control assembly, packaged and packed in accordance with section 5 herein, shall withstand the following vibration conditions, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification:

VIBRATION CRITERIA (MAX) FOR PACKAGING

Type of Transportation	Vertical cps	g	Longitudinal cps	g	Lateral cps	g
Truck	200	2.5	150	1.5	200	1.0
	10	1.0	10	1.0	10	1.0
Rail	60	2.0	60	1.0	30	1.0
	10	1.0	10	0,5	10	0.5
Aircraft	60-100	1.0	60-100	1.0	60	1.0
	100-200	0.5			100	0.5
Ship (surface)	30	0.5	Negligible		10	0.25
	10	1.5			30	0.75

3.4.3 Shock, Operating Condition - The ejector control assembly shall withstand shock in accordance with Specification MIL-S-901, Type A for Grade I medium-weight equipment, shall show no damages and thereafter shall be capable of meeting all performance requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

3.4.4 Temperature and Humidity

3.4.4.1 Temperature, Normal - The ejector control assembly shall withstand continuous exposure to air temperatures between +65 and +85 degrees Fahrenheit, with a relative humidity of 50 percent at +78 degrees Fahrenheit, shall show no damages and thereafter shall be capable of meeting all performance requirements of this specification.

3.4.4.2 Low Temperature - The ejector control assembly shall withstand an air temperature of +28 $\pm$ 4 degrees Fahrenheit for 4 hours, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

3.4.4.3 High Temperature - The ejector control assembly shall withstand air temperatures between +95 and +105 degrees Fahrenheit with a relative humidity of 95 to 98 percent for 24 hours, shall show no damages and thereafter shall be capable of meeting all performance requirements of this specification.

3.4.4.4 Humidity - The dome pressure switch and the air-flask pressure switch shall withstand a humidity test in accordance with Procedure I of Specification MIL-E-5272, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

3.4.5 Fungus - The dome pressure switch and the air-flask pressure switch shall withstand a fungus test in accordance with Procedure I of Specification MIL-E-5272, shall show no damages and thereafter shall be capable of meeting all performance requirements of this specification.

3.4.6 Corrosive Atmosphere - The ejector control assembly shall withstand a salt spray test in accordance with Procedure I of Specification MIL-E-5272, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

3.4.7 Inclination - The ejector control assembly, with the low-pressure section charged to an air pressure of 125 ± 6 psig and with the dome pressure switch in operation, shall withstand 120 cycles of transverse inclination and 120 cycles of longitudinal inclination at the rate of 4 cycles-per-minute, shall show no damage, and thereafter shall be capable of meeting all performance requirements of this specification.

NOTE

A cycle of inclination shall consist of a 60-degree angular displacement from the vertical, return to vertical, a 60-degree angular displacement in the opposite direction, and return to vertical, all within 15 seconds.

3.4.8 Operating Life - The ejector control assembly shall withstand 100 cycles of operation, shall show no damage, and thereafter shall. be capable of meeting all performance requirements of this specification.

3.5 Cleanup - Prior to and after final assembly, all parts, components, and the assembly shall be thoroughly cleaned of metal chips and other foreign matter, Burrs and sharp edges shall be removed.

3.6 Workmanship - The equipment, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with this specification, Particular attention shall be paid to neatness and thoroughness of works marking of parts and assemblies, painting, welding, and freedom of parts from burrs and sharp edges, Welding shall conform to the requirements of Section S9-1 of the General Specifications for Building Ships of the United States Navy, NAVWEPS OP 2230 shall be used as a guide for determining acceptable workmanship of electrical parts.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's Inspection - Unless otherwise specified herein, the contractor is responsible for the performance of all inspection requirements prior to submission for Government inspection and acceptance. Except as otherwise specified, the contractor may utilize his own facilities or any commercial laboratory acceptable to the Government, Inspection records of the examinations and tests shall be kept complete and available to the Government as specified in the contract or order.

4.2 Government Inspection - The Government Inspector will make such inspections as are necessary to determine that components and assemblies are in accordance with the requirements of the contract, pertinent drawings, and specifications. Unless otherwise specified, these inspections will be conducted in accordance with NAVWEPS OP 400. Production tests of final assemblies shall be on a 100-percent basis. No sampling is permitted for acceptance inspection purposes. Only those assemblies which pass final inspection shall be accepted by the Navy; a rejected assembly may be reworked and submitted in accordance with NAVWEPS OP 400. Failed parts and components shall be submitted to the Material Review Board for disposition.

4.2.1 Preproduction Sample - The preproduction sample specified in 3.2.1 shall be submitted to the Government inspector for preproduction tests at an activity designated in the contract or by the procuring activity for the purpose of determining compliance with the requirements of the contract, specifications, and drawings. Further production of the item by the contractors prior to approval of the contracting activity or the completion of tests on the preproduction sample, shall be at the contractor 's risk. Preproduction samples accepted will be applied as part of the quantity specified by the contract or order.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

4.3 Classification of Tests - The inspection and testing of the ejector control assembly shall be classified as follows:

4.3.1 Production Tests - These tests are to be accomplished on each ejector control assembly submitted for acceptance under the contract. Production tests shall be either performed by the manufacturer. and witnessed by the Government Inspector, or these tests may be conducted by the Government Inspector. These tests are detailed in 4.5.

4.3.2 Preproduction Tests - Preproduction tests are those which are accomplished on samples selected as specified in 4.2.1, which are representative of the production of the ejector control assembly, to determine that the production meets the requirements of this specification. These tests are detailed in 4.5 and 4.6. Acceptance shall be based on no defects in the sample. Failure of the sample to comply with these requirements will result in the cessation of production until determination of cause of failure is made and the appropriate correction approved by the procuring activity.

4.3.3 Tests After Delivery - Unless otherwise specified in the contract, the Government reserves the right to conduct any or all of the tests specified herein as deemed necessary after installation of the ejector control, assembly. Any defects discovered before, during, or after these tests due to the contractor's failure to comply with drawings or specifications for this equipment shall be corrected by the contractor at no expense to the Government, provided the contractor is notified of such defects within the guarantee period of the contract.

4.4 Special Test Equipment - The following items of special test equipment are required:

Dummy Explosive Valve	BuWep Dwg 2254290
Dummy Blocking Valve	BuWep Dwg 2254291

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

4.5 Production Tests

4.5.1 Responsibility - The contractor or Government Inspector shall conduct production tests as specified in 4.3.1 to assure that the ejector control assembly is in compliance with the requirements of 3.3.1 through 3.3.4.3.

4.5.2 Test Conditions - The ejector control assembly shall be subjected to production tests under the following conditions:

Temperature:	Room ambient, +65 to +85 degrees Fahrenheit
Altitude:	Normal ground atmospheric pressure
Vibration:	None
Humidity:	Relative humidity of 50 percent or less at +78 degrees Fahrenheit

4.5.3 Test and Inspection Equipment and Facilities - The manufacturer shall furnish and maintain all necessary test equipment, facilities, and personnel for performing all production tests. The test equipment shall be adequate in quantity and, unless definite requirements are specified, shall be of sufficient accuracy and quality to permit performance of the required production tests,

4.5.3.1 Calibration - Measuring equipment and instrumentation shall be calibrated as required by NAVORD INST 4355.1, BUWEPS INST 4355.5, and in accordance with the policies specified in the Standards Laboratory Information Manual issued by the Bureau of Naval Weapons Representative, Pomona, California.

4.5.4 Test Procedures

4.5.4.1 Materials and Dimensions - Each ejector control assembly shall be inspected for conformance to the requirements of 3.2.2 and 3.2.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

4.5.4.2 Hydrostatic Pressure Tests

4.5.4.2.l Ejector Control Assembly Test - Each ejector control assembly shall be subjected to a hydrostatic proof pressure of 740 to 760 psig for 5 minutes to meet the requirements of 3.3.1.1.

4.5.4.2.2 High-Pressure Section Test - Using test fixtures (BuWep Dwg 2254290 and 2254291), the high-pressure section of each ejector control assembly shall be subjected to a hydrostatic proof pressure of 6,650 to 6,850 psig for 5 minutes to meet the requirements of 3.3.1.2.

4.5.4.3 Air Pressure Tests

4.5.4.3.1 Ejector Control Assembly - Each ejector control assembly shall be subjected to an air pressure of 240 to 260 psig for 5 minutes to meet the requirements Of’ 3.3.2.1.

4.5.4.3.2 High-Pressure Section Test - Using test fixtures (BuWep Dwg 2254290 and 2254291), the high-pressure section of each ejector control assembly shall be subjected to an air pressure of 4,300 to 4,500 psig for 5 minutes to meet the requirements of 3.3.2.2.

4.5.4.3.3 High-Pressure Valve Test - Using test fixtures (BuWep Dwg 2254290 and 2254291), the high-pressure valves of each ejector control assembly shall be subjected to an air pressure of 4,300 to 4,500 psig for 5 minutes to meet the requirements of 3.3.2.3.

4.5,4.3.4 Low-Pressure Valve Test - The low-pressure valves of each ejector control assembly shall be subjected to an air pressure of 240 to 260 psig for 5 minutes to meet the requirements of 3.3.2.4.

4.5.4.4 Electrical Tests

4.5.4.4.1 Dielectric Strength Test - Each dome pressure switch and air-flask pressure switch shall be subjected to a potential of 325 volts (rms), 60-cycle AC applied between mutually insulated portions of the part, and between insulated portions and the case of the equipment for 1 minute, in accordance with Specification MIL-F-18870, to meet the requirements of 3.3.3.1.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:48Z
Check the source to verify that this is the current version before use.

4.5.4.4.2 Insulation Resistance Test - Each dome pressure switch and air-flask pressure switch shall be subjetted to a potential of 500-volts DC applied between the mutually insulated portions of the part, and between insulated portions and the case of the equipment, in accordance with Specification MIL-F-18870, to meet the requirements of 3.3.3.2.

4.5.4.5 Operational Tests

4.5.4.5.1 Dome. Pressure Switch Test - To meet the requirements of 3.3.4.1, each ejector control assembly shall be subjected to an increasing hydrostatic pressure until the dome pressure switch actuates and a decreasing hydrostatic pressure until the switch deactuates.

4.5.4.5.2 Air-Flask Pressure Switch Tests

4.5.4.5.2.1 Switch for Ejector Group, Mark 2 Mod O - To meet the requirements of 3.3.4.2.1, each ejector control assembly shall be subjected to an increasing hydrostatic pressure until the air-flask pressure switch (Item 3, BuWep Dwg 2024896) actuates and a decreasing hydrostatic pressure until the switch deactuates.

4.5.4.5.2.2 Switch for Ejector Group, Mark 4 Mod 0 - To, meet the requirements of 3.3.4.2.2 each ejector control assembly shall be subjected to an increasing hydrostatic pressure until the air-flask pressure switch (Item 4, BuWep Dwg 2024896) actuates and a decreasing hydrostatic pressure until the switch deactuates.

4,5.4.5,3 Dome Relief Valve Test - To meet the requirements of 3.3.4.3, each ejector control assembly shall be subjected to an increasing hydrostatic pressure until the dome relief valve opens and a decreasing hydrostatic pressure until the valve closes.

Source: https://assist.dla.mil -- Downloaded: 2026l0-19T09:48Z
Check the source to verify that this is the currentversion before use.

4.6 Preproduction Tests

4.6.1 Vibration Test, Operating Condition - One ejector control assembly, mounted in a suitable test fixture, shall be subjected to vibration in accordance with Standard MIL-STD-167, Type I, in the range of 5 to 25 cycles-per-second, to meet the requirements of 3.4.1.

4.6.2 Vibration Test, Shipping Condition - One ejector control assembly, packaged and packed in accordance with section 5 herein and mounted in a suitable test fixture, shall be subjected to vibration to meet the requirements of 3.4.2.

4.6.3 Shock Test, Operating Condition - One ejector control assembly, mounted in a suitable test fixture, shall be subjected to shock in accordance with Specification MIL-S-901 to meet the requirements of 3.4.3.

4.6.4 Temperature and Humidity Tests

4.6.4.1 Normal Temperature Test - One ejector control assembly shall be subjected to air temperatures between +65 and +85 degrees Fahrenheit, with a relative humidity of 50 percent or less at +78 degrees Fahrenheit, to meet the requirements of 3.4.4.3.

4.6.4.2 Low Temperature Test - One ejector control assembly shall be subjected to an air temperature of +28 $\pm$ 4 degrees Fahrenheit for 4 hours to meet the requirements of 3.4.4.2.

4.6.4.3 High Temperature Test - One ejector control assembly shall be subjected to an air temperature of +95 to +105 degrees Fahrenheit, with a relative humidity of 95 to 98 percent for 24 hours, to meet the requirements of 3.4.4.3.

4.6.4.4 Humidity Test - One each of the dome pressure switches and the air-flask pressure switches shall be subjetted to humidity in accordance with Specification MIL-E-5272, Procedure I, to meet the requirements of 3.4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

4.6.5 Fungus Test - One each of the dome pressure switches and the air-flask pressure switches shall be subjected to fungus in accordance with Specification MIL-E-5272, Procedure I,to meet the requirements of' 3.4.5.

4.6.6 Corrosive Atmosphere Test - One ejector control assembly shall be subjected to the salt spray test in accordance with Specification MIL-E-5272 to meet the requirements of 3.4.6.

4.6.7 Inclination Test. - One ejector control assembly, with the low-pressure. section charged to an air pressure of 125 ± 6 psig and with the dome pressure switch in operation, shall be subjected to 120 cycles of transverse inclination and 120 cycles of longitudinal inclination at the rate of 4 cycles-per-minute, to meet the requirements of 3.4.7.

4.6.8 Operating Life Test - One ejector control assembly, mounted in a suitable test fixtures shall be subjected to 100 cycles of operation to meet the requirements of 3.4.8. One cycle of operation shall consist of charging the assembly to operating pressure and discharging to atmospheric pressure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

5. PREPARATION FOR DELIVERY

NOTE

The following instructions apply to the ejector control assembly less explosive valve and blocking valve. The blocking valve component is prepared for delivery in accordance with Specification MIL-V-21517. The explosive valve is prepared for delivery in accordance with Specification MIL-V-21509. The ejector control assembly is shipped with the dummy explosive valve BuWep Dwg 2025896 and the dummy blocking valve (BuWep Dwg 2254291 installed:

5.1 Preservation and Packaging

5.1.1 Level A - Level A packaging shall be such as to assure adequate protection to prevent corrosion, deterioration, or physical damage during shipment, handling, indeterminate storage, and world-wide distribution of the item.

5.1.1.1 Cleaning - Unless otherwise specified, the ejector control assembly shall be cleaned in accordance with Method C-1 of Specification MIL-P-116.

5.1.1.2 Drying - Unless otherwise specified, the ejector control assembly shall be dried in accordance with one or more of the methods given in Specification MIL-P-116, provided the method is not injuries to the item.

5.1,1.3 Preservative Application - None

5.1.1.4 Unit Packaging - Unit packaging of the ejector control assembly shall be in accordance with Method 1A-8X of Specification MIL-P-116. The unit package shall CONTAIN one service package.

5.1.1.5 Intermediate Package - Not applicable

5.1.1.6 Cushioning - The unit package and pack shall incorporate sufficient cushioning material, bracing, or other adequate shock-absorbing devices, to ensure the ejector control assembly be protected against shock and vibration incident to handling and transportation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.

5.1.2 Level P - Not applicable

5.1.3 Level C- Level C packaging shall be such as assure adquate protection to prevent corrsion, deteri-crition, and physical damage during shipmentfrom supply source to the first receiving activity for immediate use.

5.1.3.1 Cleaning and drying- Cleaning and Drying shall be in accordance with 5.1.1.1 and 5.1.1.2.

5.1.3.2 Preservation and Packaging - Preservation and packaging may be accomplished in accordance with the sup-plier's commercial practice when such practice meets the requirenents of 5.1.3 or is in accordance with the require-ments specified for Level A.

5.2 Packing

5.2.l Level A - Level 1. packing shall be such as to assure adequate protection to prevent damage during shipment, handling, indeterminate storage, and world-wide distribution.

5.2.1.1 Exterior Containers - The ejector control assembly shall be packed in a close-fitting wooden box conforming to Specification PPP-B-621, Class 2.

5.2.1.2 Level B - Not applicable

5.2.1.3 Level C - The ejector control assembly, pack-aged as specified in 5.1.3.2, shall be packed to afford Protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. Shipping containers shall conform to the Uniform Freight Classification Rules or other rules and regulations applicable to the mode of transportation.

5.3 Marking - In addition to any special marking required by the contract or order, unit packages and ship ping containers shall be marked in accordance with the re-quirements of Standard MIL-STD-129,including serial numbers.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended Use - The ejector control assembly is intended for use as a component of the Ejector Group, Missile, Mark 2 Mod O and Mark 4 Mod O to monitor and regulate the air supply.

6.2 Ordering Data - Procurement documents should specify the following:

(a) Title, number, and date of specification.

(b) Exceptions to the specification, applicable drawings, and other documents.

(c) Selection of' applicable levels of preservation, packaging, and packing.

NOTICE: When Government drawings, specications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specificatications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET
NAVWEPS FORM 4121/3 (8-62)

FORM APPROVED
BUDGET BUREAU NO. 45-R309

INSTRUCTIONS

This sheet is to be filled out by Government or contractor personnel involved in the use of this specification in procurement of products for ultimate use by the activity shown on the reverse of this sheet.

This sheet is provided for obtaining information which will aid the activity shown in insuring that through use of this specification suitable products can be procured with a minimum amount of delay and at the least cost.

Comments and the return of this sheet will be appreciated.

Fold on dotted lines on reverse side, staple in corner, and send to the activity shown.

SPECIFICATION *(No. and abbrev. title)*

ORGANIZATION	CITY	STATE

CONTRACT NUMBER	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A DIRECT GOVERNMENT CONTRACT ☐ OR A SUBCONTRACT ☐

1. HAS ANY PART OF THIS SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?
(If so, give paragraph number and wording, and recommendations for correcting the deficiencies.)

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?
☐ YES ☐ NO IF YES, IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If additional papers are attached, send this form and papers in an envelope. This form is addressed for use in window envelope when appropriate.)*

SUBMITTED BY *(Print name and title)*	DATE

B-11134

Source: https://assist.dla.mil -- Downloaded: 202640-19T09:48Z
Check the source to verify that this is the current version before use.