MILITARY SPECIFICATION

DETONATOR ASSEMBLY

This amendment forms a part of Military Specification MIL-D-21524A(WEP) dated 11 August 1961 and has been approved for use by the Naval Ordnance Systems Command, Department of Navy.

By this amendment, MIL-D-21524A(WEP) is changed to MIL-D-21524A(OS).

1. Page 3, paragraph 2.2 delete in its entirety and substitute:

"2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation of bids shall apply.

Code of Federal Regulations

49 CFR 171-178	Hazardous Materials Regulations, Department of Transportation

MANUALS

Department of Defense

4145.26M	DOD Contractor's Safety Manual for Ammunition Explosives and Related Dangerous Material

(Applications for copies of the above publications should be addressed to Superintendent of Documents, Government Printing Office, Washington, D.C. 20402.)"

2. Page 4, paragraph 3.2.1: Delete and substitute:

"3.2.1 Preproduction Samples. Unless otherwise specified in the contract or order, preproduction samples of the detonator assembly shall be manufactured using the methods and procedures proposed for the production lot. These samples will be tested as specified in section 4 herein and are for the purpose of determining that the production item meets the requirements of this specification (refer to 4.2.1)."

3. Page 9, add new paragraph 3.7 as follows:

"3.7 Safety Precautions. The supplier shall observe the safety precautions of DOD 4145.26M, as applicable."

4. Page 17, paragraph 4.5.4.4.3: Delete and substitute:

Source: https://assist.dla.mil -- Downloaded: 202610-19T09:48Z
Check the source to verify that this is the current version before use.

"4.5.4.4.3 Air/Watertightness Test. Each detonator shall be immersed in water with a suitable wetting agent added (Monsanto Sterol-AJ, or equal) and subjected to an absolute pressure of 2.5 inches of mercury for not less than 15 minutes followed by a pressure of 130 ± 5 psig for not less than 30 minutes. After the pressure is reduced to atmospheric, the detonator shall be removed from the water then air dried for a minimum of 6 hours and then weighed. An increase in weight in excess of 0.025 percent shall cause rejection of the detonator but shall not cause rejection of the lot. However, any detonator which has previously passed this test, which is subsequently discovered to be a leaker on retesting shall cause rejection of the lot."

5. Page 18, paragraph 4.6.2.2.1: Delete and substitute:

"4.6.2.2.1 Impact Test. Thirty-two detonators, packaged and packed as specified in section 5 herein, shall be placed on the wood platform of a package tester. The platform shall be oscillated in a circular path in the vertical plane with a peak-to-peak amplitude of 1 inch. The frequency vibration (normally 4 to 5 cps) shall be set at the point where the pack jostles against the fence and momentarily leaves the platform by approximately 3/16 inch. The pack shall be vibrated on each of 6 faces for 30 minutes."

6. Pages 23 through 26, delete section 6.2.

Preparing Activity:
NAVY - OS
(Proj. No. 1375-N414)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T09:48Z
Check the source to verify that this is the current version before use.