MILITARY SPECIFICATION
BULLET, CALIBER .30 CARBINE, REFERENCE

1. SCOPE

1.1 This specification covers a bullet to be used for calibration purposes in caliber .30 carbine proof testing equipment.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

STANDARDS

Military

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109	- Quality Assurance Terms and Definitions
MIL-STD-636	- Visual Inspection Stanards for Small Arms Ammunition Through Caliber .50
MIL-STD-644	- Visual Inspection Standards and Inspection Procedures for Inspection of Packaging, Packing and Marking of Small Arms Ammunition

DRAWINGS

Munitions Command

C8595413	- Bullet, Caliber .30 Carbine, Reference
D8596106	- Carton
F8595883	- Packing and Marking Bullets, 7.62MM, NATO Reference; Cartons; Box, Ammunition, M2A1
F8595884	- Packing and Marking Bullets, 7.62MM, NATO Reference; Cartons; Box, Ammunition, M2A1; Box, Wirebound
SK FSA 7079	- Method of Packing Bullets, Ball, Carbine, Cal. .30 in Cartons
IEL-8595413	- Inspection Equipment List for Bullet, Caliber .30 Carbine Reference

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 General.- The bullet shall comply with the requirements specified on drawing C8595413, referenced specifications and the following:

3.2 Workmanship.- The requirements for workmanship are as specified on the applicable drawings, referenced specifications and the following:

3.2.1 Metal defects.- The bullet shall be free of dents, scratches, splits, scaly metal and other defects.

3.2.2 Foreign matter.- The bullet shall be free of corrosion, stains, discolorations, dirt, oil, or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.- Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.- Reference shall be made to MIL-STD-109 for definition of quality assurance terms.

4.2 Inspection provisions

4.2.1 Lot

4.2.1.1 Submission of product.- The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Lot identification.- Each lot of bullets shall be identified as to type, caliber, and model, as well as with a lot number and the supplier's identification as assigned by the procuring activity.

4.2.2 Examination.- Examination for major and minor defects shall be performed on a class basis in accordance with the classification of defects, Table I, using applicable sampling plans and acceptance criteria of MIL-STD-105. The AQL for the major class shall be 0.25 percent and the AQL for the minor class shall be 1.50 percent.

4.2.2.1 Classification of defects.- The classifications of defects shall be as specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

4.2.2.1 (Cont'd)

TABLE I

No.	Defect and Method of Inspection	Major	Minor
	Visual 1/		
18	Dent		X
19	Scratch		X
20	Split bullet jacket	X	
22	Scaly metal		X
23	Upset (crooked) point		X
25	Flat point		X
26	Chamfer at base incorrect		X
27	Base crimp of jacket improper		X
28	Foreign matter		X
	Gaging		
29	Profile of ogive		X
30	Diameter of body	X	
31	Total length	X	
	Weighing		
32	Weight	X	

1/ Refer to MIL-STD-636 for Visual Standards for defects 18 through 25. In the event of conflict between Table I of this specification and MIL-STD-636 as to defect classification, the classification specified in Table I shall apply.

4.2.3 Tests.- None required.

4.2.4 Packaging, packing and marking inspection.- Inspection for packaging, packing and marking shall be in accordance with MIL-STD-644 as applicable.

4.2.5 Inspection equipment.- The examination and tests shall be made using the equipment listed on IEL-8595413.

4.3 Test methods and procedures.- None required.

5. PREPARATION FOR DELIVERY

5.1 Packaging.- Bullets shall be packaged in cartons, drawing D8596106 in accordance with method shown on drawing SK FSA 7079. The cartons shall be packaged in M2A1 ammunition box in accordance with drawing F8595883.

5.2 Packing.- The M2A1 boxes shall be packed in wirebound crate in accordance with drawing F8595884.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.

5.3 Marking.- Each carton, ammunition box and wirebound crate shall be marked on the outside surface with the bullet nomenclature, quantity, manufacturer's identification and assigned lot number.

6. NOTES

6.1 Ordering Data.- Invitations for bids or request for proposal and contracts or orders will specify the following:

6.1.1 Title, number and date of this specification.

6.1.2 Type and level of packing.

6.1.3 Provision for the submission of acceptance inspection reports containing final inspection results for each lot of bullets presented to the Government.

6.1.4 Requirement for contractor to provide and maintain an inspection system in accordance with MIL-I-45208, Inspection System Requirements.

Custodian:

ARMY - MU

Preparing Activity:

ARMY - MU

Project No. 1305 - A483

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:49Z
Check the source to verify that this is the current version before use.