INCH-POUND
MIL-DTL-55302/25F
w/AMENDMENT 2
1 June 2022
SUPERSEDING
MIL-DTL-55302/25F
w/AMENDMENT 1
10 July 2017

DETAIL SPECIFICATION SHEET

CONNECTORS, PRINTED CIRCUIT SUBASSEMBLY AND ACCESSORIES: RECEPTACLE, 120, 150, 160, AND 180 CONTACT POSITIONS, FOR PRINTED WIRING BOARDS (.075 SPACING)

This specification is approved for used by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-55302.

Style 1 (internal keying) connectors are hereby canceled and superseded by style 2 (external keying) connectors, see table I for supersession data.




FIGURE 1. Connectors, receptacle, .075 (1.90 mm) spacing.

AMSC N/A FSC 5935

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Dash 1/ numbers	Number of contacts	Type	Dimensions					Contact identification numbers
			A	B	C	D	E	
17 18 19 20	120	I II III IV	5.380 (136.65)	5.090 (129.29)	59	4.425 (112.40)	4.690 (119.13)	1 - 60 61 - 120
21 22 23 24	150	I II III IV	6.505 (165.23)	6.215 (157.86)	74	5.550 (140.97)	5.815 (147.70)	1 - 75 76 - 150
25 26 27 28	160	I II III IV	6.880 (174.75)	6.590 (167.39)	79	5.925 (150.50)	6.190 (157.23)	1 - 80 81 - 160
29 30 31 32	180	I II III IV	7.630 (193.80)	7.340 (186.44)	89	6.675 (169.55)	6.940 (176.28)	1 - 90 91 - 180

1/ Dash numbers 17 through 32 are for style 2 (external keying) connectors.

FIGURE 1. Connectors, receptacle, .075 (1.90 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.




FIGURE 1. Connectors, receptacle, .075 (1.90 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Inches	mm	Inches	mm	Inches	mm
.003	0.08	.050	1.27	.136	3.45
.004	0.10	.0625	1.588	.140	3.56
.005	0.13	.063	1.60	.171	4.34
.006	0.15	.065	1.65	.175	4.45
.010	0.25	.067	1.70	.180	4.57
.012	0.30	.073	1.85	.185	4.70
.014	0.36	.075	1.90	.200	5.08
.015	0.38	.080	2.03	.235	5.97
.018	0.46	.081	2.06	.242	6.15
.019	0.48	.083	2.11	.248	6.30
.020	0.51	.085	2.16	.250	6.35
.022	0.56	.087	2.21	.255	6.48
.025	0.64	.096	2.44	.260	6.60
.027	0.69	.101	2.57	.298	7.62
.028	0.71	.108	2.74	.300	7.62
.030	0.76	.109	2.77	.305	7.75
.031	0.79	.113	2.87	.315	8.00
.032	0.81	.125	3.18	.330	8.38
.040	1.02	.130	3.30	.332	8.43
.045	1.14	.135	3.43	.340	8.64
				.400	10.16

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for information only.
3. Unless otherwise specified, tolerances are ±.005 (0.13 mm) on three place decimals and ±.2° on angles.
4. These connectors mate with connectors specified in MIL-DTL-55302/23.
5. Use printed circuit boards with the type III receptacle.
6. Minimum pad length on printed circuit board.
7. Termination layout on .025 (0.64 mm) modular grid.
8. Numbers indication, every 5 cavities marked or molded on side (except 10 position). Numbers indicating end cavities and lines indicating every 5 cavities molded or marked on mating face.
9. Location indicators embossed on surface.

FIGURE 1. Connectors, receptacle, .075 (1.90 mm) spacing - Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design and construction:

Dimensions and configuration: See figure 1.

Material:

Insulator body: Insulator material shall be in accordance with MIL-DTL-55302 or type GLCP-30F in accordance with ASTM D5138 or MIL-M-24519.

Contact material: Contact material in accordance with MIL-DTL-55302 or beryllium copper alloy C17400 in accordance with ASTM B768.

Plating:

Engagement area: Gold in accordance MIL-DTL-55302 for .100 length, over nickel all over in accordance with MIL-DTL-55302.

Termination area: Tin lead over nickel in accordance with MIL-DTL-55302 for the lengths:

.165 minimum length for type I, .200 minimum length for type II.

.300 minimum length for type III, .140 minimum length for type IV.

Contact identification: See figure 1.

Contact rating: 3.0 amperes maximum per contact, 2.25 amperes continuous per contact at 75° F.

Keying: See MIL-DTL-55302/31.

Oversized pin exclusions (sockets only): .0465 diameter pin.

Contact separation force: The connector shall meet the requirements of MIL-DTL-55302/29.

Wire size: Number 26 AWG maximum with type II, solder eyelet contact for wire termination.

Resistance to test probe damage: The connector shall meet the requirements of MIL-DTL-55302/30.

Mating and unmating: The maximum mating force in pounds shall the number of contacts multiplied by .25 and the withdrawal force in pounds shall be a minimum of .025 times the number of contacts and shall not exceed the measured insertion force.

Contact resistance: The average contact resistance of all contact measured shall not exceed .015 ohm, and no individual contact pair shall have a resistance exceeding .020 ohm.

Contact retention: Not applicable.

Dielectric withstanding voltage:

Sea level: 900 volts rms.

High altitude: 200 volts rms.

Replacement contacts: See MIL-DTL-55302/32.

Contact removal tool: SAE-AS81969/9-01.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Part or Identifying Number (PIN): M55302/25-(dash number from figure 1).

Patent number 3,404,367. The Government has a royalty free license under this patent for the benefit of manufacturers of the item either for the Government or for use in equipment to be delivered to the Government.

Supersession data: See table I.

TABLE I. Style 1 (internal keying) supersession data.

Style 1 (internal keying) PIN	Superseding style 2 (external keying) PIN 1/
M55302/25-01	M55302/25-17
M55302/25-02	M55302/25-18
M55302/25-03	M55302/25-19
M55302/25-04	M55302/25-20
M55302/25-05	M55302/25-21
M55302/25-06	M55302/25-22
M55302/25-07	M55302/25-23
M55302/25-08	M55302/25-24
M55302/25-09	M55302/25-25
M55302/25-10	M55302/25-26
M55302/25-11	M55302/25-27
M55302/25-12	M55302/25-28
M55302/25-13	M55302/25-29
M55302/25-14	M55302/25-30
M55302/25-15	M55302/25-31
M55302/25-16	M55302/25-32

1/ Style 2 (external keying) receptacles can be mated to existing style 1 (internal keying) plugs.

Group qualification: See table II.

TABLE II. Group qualification.

Qualification of any of the following connectors 1/, 2/	Qualifies the following connectors	Retains qualification on the following
M55302/24-**	M55302/24-**	M55302/24-** M55302/25-** M55302/27-**
M55302/25-**	M55302/24-** M55302/25-** M55302/27-**	
M55302/27-**	M55302/24-** M55302/27-**	

1/ For initial qualification, connectors with the largest number of contact positions from the left hand column shall be used to obtain qualification for parts in corresponding center column.
2/ For qualification retention, data may be supplied on any two parts from the left hand column in order to retain qualification for the parts listed in the right hand column.
** Signifies number of contacts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where modifications from this amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-55302, this document references the following:

MIL-DTL-55302/23
MIL-DTL-55302/29
MIL-DTL-55302/30
MIL-DTL-55302/31
MIL-DTL-55302/32
MIL-M-24519
SAE-AS81969/9
ASTM B768
ASTM D5138

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5935-2022-104)

Review activities:
Army - AR, AT, AV, CR4, MI
Navy - AS, MC, OS, SH
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T22:45Z
Check the source to verify that this is the current version before use.