MILITARY SPECIFICATION

COOLER-DEWAR GROUP, OR-336/A, OR-337/A

This specification is approved for use by USACECOM, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers only the cooler-Dewar group to be used in the AN/ASQ-170 Target Acquisition Designation Sight (TADS) and the AN/AAQ-11 Pilot Night Vision Sensor (PNVS).

2. APPLICABLE DOCUMENTS

2.1 Government Documents.

2.1.1 Specifications, standards and handbooks. The following specifications, standards and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the Department of Defense Index of Specification and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-P-11268	- Parts, Materials, and Processes Used in Electronic Equipment
MIL-C-49175	- Cooler, Cryogenic, Mechanical HD-1033B/UA and HD-1033C/UA
MIL-D-49298	- Detector-Dewar DT-637/U

STANDARDS

MILITARY

MIL-STD-252	- Classification of Visual and Mechanical Defects for Equipment, Electronic, Wired, and Other Devices

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: HQ, USA Communications-Electronics Command ATTN: AMSEL-ED-TO, Fort Monmouth, NJ 07703 by using the self addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5855

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:02Z
Check the source to verify that this is the current version before use.

MIL-STD-454	- Standard General Requirement for Electronic Equipment
MIL-STD-810	- Environmental Test Methods
MIL-STD-2073-2	- Packaging Requirement Codes

HANDBOOKS

MIL-HDBK-742	- Waste Disposal Methods for Military Packaging Materials

(Unless otherwise indicated , copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government documents, drawings and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

PURCHASE DESCRIPTION

PD-0182-001A(CR)	- Cooler, Cryogenic, Long Life One Watt Integral HD-1033D/UA

DRAWINGS

USACECOM

54490	5008644	- Cooler-Dewar Subassembly, 180 Element
54490	5008608	- Mounting Requirements
54490	5008606	- Test Fixture Assembly Microphonics, Standard

(Copies of Specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Order of Precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specification, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Item Definition. The cooler-Dewar group is a component of the AN/ASQ-170 TADS and the AN/AAQ-11 PNVS. The group consists of a 180 element infrared detector-Dewar (DT-637/U), a one watt Cryogenic Cooler (HD-1033B/UA, HD-1033C/UA or HD-1033D/UA), a thermal conductor and associated fastening hardware. This group requires further alignment prior to installation in TADS/PNVS.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:02Z
Check the source to verify that this is the current version before use.

3.1.1 Common module selection. The detector and cooler shall meet all requirements of their respective specifications and be inspected in accordance with the Quality Assurance Provisions of these specifications prior to assembly of the cooler-Dewar group, OR-336/A, OR-337/A. The group shall be constructed in accordance with drawing 5008644.

Detector-Dewar	DT-637/U	MIL-D-49298(CR)
Cooler, Cryogenic Mechanical	HD-1033B/UA OR HD-1033C/UA	MIL-C-49175B(CR)
OR		
Cooler, Cryogenic Long Life, One Watt Integral	HD-1033D/UA	PD-0182-001A(CR)

3.1.2 Thermal conductor. The bellows thermally connects the cooler cold finger to the detector-Dewar. The thermal conductor shall be defined on 5008644. The installation procedure of the thermal conductor shall be approved by the Government. (See 6.2.c).

3.2 Parts, materials and processes. general. Parts, materials and processes shall be in accordance with the applicable drawings. Parts, materials and processes not specified shall conform to the requirements of MIL-P-11268.

3.2.1 Construction. The cooler-Dewar group shall be constructed in accordance with 5008644.

3.3 First Article. When specified in the contract the contractor shall furnish first article assemblies in accordance with 4.3.

3.4 Performance requirements. The cooler-Dewar group shall meet the following performance characteristics.

3.4.1 Defective elements. Unless otherwise specified herein, the detector-Dewar shall be operated at 80K (+5, -20K). The detector-Dewar shall contain no more than 12 defective elements as defined in 6.3. Of the 12 defective elements, no more than 4 may be hard defects. In the central 18 elements of the array there shall be no hard defects and no more than 2 soft defects. The central 36 elements shall contain no hard defects and no more than 4 soft defects. A maximum of two hard defects may be located in elements 1-72 and a maximum of two may be located in elements 109-180. Hard defects shall be separated from one another by at least 4 elements and shall be electrically strapped to an adjacent element with common ground. Soft defects located within the central 36 elements shall be separated from any other defect by at least 4 non-defective channels. Soft defects shall not be strapped unless the strapping is from an adjacent hard defect at the end of a group of 5 commonly grounded elements. (See 6.3.4)

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:02Z
Check the source to verify that this is the current version before use.

3.4.2 Microphonics. When tested in accordance with paragraph 4.6.2, no elements of the detector array shall have any noise peaks greater than 6dB above the white noise reference value from 300 to 10,000 Hz and 10dB from 10,001 to 20,000 Hz.

3.4.3 Cooldown time. The cooldown time to reach a detector temperature of 80K shall be in accordance with Figure 2.

3.4.4 Cooler Input Power. The total input power to the cooler shall not exceed that shown in Figure 3 after detector temperature has reached at least 80K. The input voltage shall be 117 ± 2 volts alternating current (VAC), 400 ± 20 hertz (Hz) power source.

3.5 Environmental conditions.

3.5.1 Temperature extremes. The cooler-Dewar group shall not be damaged when operated at temperatures from -32°C to +60°C and stored at temperature from -54°C to +71°C (see 6.3).

3.5.2 Vibration exposure. The cooler-Dewar group shall not be damaged (see 6.3) when exposed to the vibration levels and amplitudes shown in Figure 1.

3.5.3 Temperature shock. The cooler-Dewar group shall not be damaged (see 6.3) by sudden changes in temperature between -54°C and +71°C.

3.6 Workmanship. All components and parts shall be manufactured and assembled to insure uniform quality and free from defects. Workmanship shall conform to all applicable portions of the equipment drawings and requirement 9 of MIL-STD-454.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the contractor may use his or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth where such inspections are deemed necessary to meet prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of section 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements of known defective material, either indicated or actual nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:02Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3)

b. Quality conformance inspection of equipment before packaging (see 4.5).

4.3 First article inspection. Unless otherwise specified in the contract, the first article inspection shall be performed by the contractor. Reliability testing is required only on the cooler for first article testing. (See 6.2.c)

4.3.1 Inspections. All materials, parts, processes and assemblies shall be examined for conformance to the applicable specification or drawing.

TABLE I. Inspections.

Inspection Requirement	Requirement paragraph	Inspection Criteria
Any part or component missing or damaged	3.2	MIL-STD-252
Workmanship not as specified	3.6	MIL-STD-454

4.3.2 Tests. Upon successful completion of the inspections specified in 4.3.1, four first article assemblies shall be subjected to all tests listed in Table II. The four first article coolers must successfully meet the requirements of the respective cooler specification. Tests may be conducted in any order. Failure of any test shall constitute first article failure. (See 6.2)

4.3.3 Disposition of first article samples. Sample units which have been subjected to and passed first article inspections may be accepted on the contract or purchase order provided all visible and known damage is repaired and the sample units are resubjected to and pass Group A inspections. The four reliability first article coolers shall not be considered as part of the procurement quantities.

TABLE II. First article inspection.

Inspection	Requirement paragraph	Test paragraph
Defective elements	3.4.1	4.6.1
Detector microphonics	3.4.2	4.6.2
Cooldown time	3.4.3	4.6.3
Cooler input power	3.4.4	4.6.4
Environmental conditions	3.5	4.7

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:02Z
Check the source to verify that this is the current version before use.

4.4 Inspection procedures for quality assurance provisions. Unless otherwise specified herein, the cooler-Dewar group shall meet specified performance requirements when operated at an ambient temperature at +23°C ± 5°C with detector temperature of 80K + 5K, -20K, and detector bias of +5.0 Vdc ± 0.2 Vdc and cooler power of 117 ± 2 Vac, 400Hz ± 20Hz.

4.5 Quality conformance inspection of equipment before packaging.

4.5.1 Inspection. Inspection shall be as specified in 4.3.1.

4.5.2 Tests.

4.5.2.1 Group A inspection. Group A inspection shall be conducted on all cooler-Dewar groups. Group A tests listed in Table III may be performed in any order. Failure of any test shall be cause for rejection of that unit.

TABLE III. Group A Inspection.

Inspection	Requirement paragraph	Test paragraph
Defective elements	3.4.1	4.6.1
Detector microphonics	3.4.2	4.6.2
Cooldown time	3.4.3	4.6.3
Cooler input power	3.4.4	4.6.4

4.5.2.2 Group B inspection. Not required.

4.5.2.3 Group C inspection. Group C inspection shall be conducted on cooler-Dewar groups selected from units which have passed the tests in 4.5.2.1. The environmental tests of 4.7 shall be performed on a sample quantity defined in 4.5.2.3.1.

4.5.2.3.1 Sampling for group C inspection. Unless otherwise specified, the sample quantity shall be defined below. The samples shall be randomly selected from units produced during the sampling period.

MONTHLY LOT SIZE	NUMBER OF UNITS MONTHLY
1-9	1
10-29	2
30-UP	3

4.5.2.3.2 Group C failures. Actions required relative to Group C failures shall be as specified in the contract or purchase order (see 6.2.e).

4.5.2.3.3 Re-inspection of conforming Group C samples. Unless otherwise specified, sample units which have been subjected to and passed Group C inspections may be accepted on the contract or purchase order provided all visible and known damage is repaired and the sample units are resubjected to and pass Group A inspections.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:02Z
Check the source to verify that this is the current version before use.

4.5.2.4 Group D inspection. Not required.

4.6 Test requirements. Unless otherwise specified, the group shall be interconnected and operated under standard ambient conditions (temperatures of 23°C ± 5°C and humidity not to exceed 90 percent). The detector shall be operated at +5.0 Vdc ± 0.2 Vdc. Each detector element shall be biased with current flow in the same direction. The cooler shall operate from a 117 Vac ± 2 Vac, 400 Hz ± 20 Hz power source.

4.6.1 Defective elements. The detector array shall be checked for continuity using an ohm meter (current limited to 1 mA). Lack of continuity indicates an open element and shall constitute failure of the tests. The Group A inspection test report on the detector shall be used to verify other requirements of paragraph 3.4.1.

4.6.2 Detector microphonics. The cooler-Dewar group shall be mounted to a microphonics test fixture, defined in drawing 5008606, accordance with the mounting requirements defined in drawing 5008608. All screw/bolt heads shall be torqued in accordance with the requirements specified in drawings 5008608 prior to the test. The cooler shall be activated and run throughout the duration of the microphonics test procedure. The detector shall be biased in accordance with the requirements of paragraph 3.6.10 of MIL-D-49298(CR). When the detector array reaches an operational temperature between 60 and 80K, the frequency spectral density of each detector element shall be measured using a noise power spectrum analyzer. The spectrum analyzer and any associated electronics/software shall be configured and operated to provide a frequency span of 0-20,000 Hz, a measurement window (filter) in the Flat Top configuration, and a Noise Equivalent Bandwidth of 360 Hz ± 10 Hz. A mimimum of 64 samples of the frequency spectrum shall be taken and averaged. The white noise reference level of a given detector element shall be determined by averaging the noise on that element from 12,000 to 20,000 Hz with the cooler power applied. Any detector element which fails to meet the requirements of paragraph 3.4.2 shall be considered a failure of this test.

4.6.3 Cooldown time. The required operating temperature shall be determined by measuring the voltage across the temperature sensor D1 installed in the detector-Dewar with a 1 mA ± .01 mA bias applied. The detector-Dewar shall be operated with bias voltage applied to all sample elements from cooler start up to when the above measurements are made. Failure to meet the requirements of 3.4.3 shall constitute failure of this test.

4.6.4 Cooler input power. Input power shall be measured using an AC wattmeter when the temperature sensor diode reaches 80K or less. Failure to meet requirements of 3.4.4 shall constitute failure of this test.

4.7 Environmental tests. The following tests shall be performed in the sequence presented in accordance with the General Requirements of MIL-STD-810. During the high and low operating temperature tests, the performance test of 3.4.1, 3.4.3, and 3.4.4 shall be accomplished and shall be successfully completed.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:02Z
Check the source to verify that this is the current version before use.

The performance tests of Table III shall be performed as a baseline before and after each of the following tests. Failure to meet the requirements of 3.4.1, 3.4.2, 3.4.3 and 3.4.4 after each environmental test shall constitute failure of that test. During vibration tests and performance tests 3.4.3 shall be performed and successfully completed.

4.7.1 High temperature. The cooler-Dewar group shall be tested in accordance with MIL-STD-810, Method 501.1, Procedure II, except that step 7 shall be +60°C for operating and +71°C for storage.

4.7.2 Low temperature. The cooler-Dewar group shall be tested in accordance with MIL-STD-810, Method 502.1, Procedure I, except that step 2 shall be -54°C and step 4 shall be -32°C.

4.7.3 Vibration. The cooler-Dewar group shall be tested in accordance with MIL-STD-810, Method 514.2, paragraph 4.5.2 and Procedure IIA, except that the curve shown in Figure 1 of this specification shall be used in lieu of MIL-STD-810 figure. The duration shall be 15 minutes in each of the three orthogonal axes.

4.7.4 Temperature shock. Temperature shock shall be in accordance with MIL-STD-810, Method 503.1, Procedure I, except that the temperature of step 2 shall be -54°C and the temperature for step 1 and 4 shall be +71°C. Failure to meet the requirements of Table III shall constitute failure of this test.

5. PACKAGING

5.1 Packaging requirements. The packaging requirements for the desired level(s) of protection shall be as specified by the acquisition activity (see 6.2).

5.1 Preservation. Preservation shall be as specified in MIL-STD-2073-2, Tables I through VII, coded as follows: 2M-1-00-00-NR-X-ED.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory).

6.1 Intended use. The cooler-Dewar group is intended for use in the TADS and PNVS.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:02Z
Check the source to verify that this is the current version before use.

b. Issue of DODISS to be cited in the solicitation and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2).

c. Thermal conductor assembly procedure shall be submitted to:

Director
Center For Night Vision and Electro-Optics
ATTN: AMSEL-RD-NV-TS
Fort Belvoir, VA 22060-5677

d. First article tests are required for inspection and approval, and the number of units required (see 3.3).

(1) Time frame for submission of first article test reports.

(2) Time frame for approval of first article test reports.

e. Production delivery schedule.

(1) Defined in terms of monthly lots.

(2) Actions required relative to Group C failures.

(3) Disposition/refurbishment of Group C samples.

f. MIL-STD-810C shall be used for environmental tests of 4.7.

g. The Contractor must order Group A detector inspection reports for use in validation of the requirements of paragraphs 3.4.1 and 4.6.1; Defective Elements. The Contractor must also validate conformance with Group A, C and D inspections for both the Detector-Dewar DT-637/U and the Cooler, Cryogenic, Long Life per paragraph 3.1.1, Common Module selection.

h. When first article rough handling tests are not required.

i. When first article packaging inspection reports require Acquisition Activity approval prior to production unit packing.

j. Specify drawing 5008644-1 for HD-1033B/UA, HD-1033C/UA Cooler or 5008644-2 for HD-1033D/UA.

k. Levels of preservation and packing (See section 5).

6.3 Definitions.

6.3.1 Damage. Any breakage, loosening, shifting, evidence of corrosion, failure of any finish, hardware, connection or components, or any deterioration in quality or failure to operate within the specification requirements.

6.3.2 Element. An element is defined as one channel in the 180 element detector array.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:02Z
Check the source to verify that this is the current version before use.

6.3.3 Inspection lot size. An inspection lot is defined as three months continuous production or 120 units, whichever comes first, of those groups which have successfully passed Group A inspection.

6.3.4 Strapping. Strapping is defined as electrically connecting a defective element to a nondefective element. The pair of strapped elements thus formed, exhibiting 100 percent crosstalk, shall be considered as a single defect.

6.3.5 Defective element. A defective element shall be defined as one which has failed the requirements of 3.6.5, 3.6.5.1, 3.6.6, 3.6.7 and 3.6.14 of MIL-D-49298(CR). A defective element may be classified as either hard or soft. A hard defect is an element which fails the requirements of 3.6.5.1, 3.6.6, 3.6.7 or 3.6.14 of MIL-D-49298(CR) or which has a 500K blackbody specific dectivity less than 6.0×10^9 cm $Hz^{\frac{1}{2}}W^{-1}$. Two elements shorted together are considered one hard defect. A soft defect is one which meets all requirements of 3.6.6, 3.6.7 and 3.6.14 of MIL-D-49298(CR) and has a 500K blackbody specific detectivity greater than or equal to $6.0 \times$ cm $Hz^{\frac{1}{2}}W^{-1}$, but less than 8.5×10^9 cm $Hz^{\frac{1}{2}}W^{-1}$.

6.4 Environmental pollution preventive. Disposal methods of packaging materials, to prevent environmental pollution, are contained in MIL-HDBK-742, the material specification, or may be obtained from the preparing activity of the applicable material specification.

6.5 Subject Term Keyword listing.


Bellows
Cooler
Dewar

CUSTODIAN:
Army - CR

PREPARING ACTIVITY:
Army - CR

Project 5855-A298

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:02Z
Check the source to verify that this is the current version before use.



NOTES: 1. Curve limiting PSD response to +3 db.
2. The RMS valve is 3.2g.

FIGURE 1. Random vibration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:02Z
Check the source to verify that this is the current version before use.




FIGURE 2. Cool down curve.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:02Z
Check the source to verify that this is the current version before use.




FIGURE 3. Input power with heat load applied.

Source: https://assist.dla.mil -- Downloaded: 20261022T20:027
Check the source to verify that this is the current version before use.

☆U.S. GOVERNMENT PRINTING OFFICE: 1989 - 604-033/0353

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

Cdr, CECOM
ATTN: AMSEL-ED-TO
Fort Monmouth, NJ 07703-9990

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 4966 Alexandria, VA

POSTAGE WILL BE PAID BY

Commander
U.S. Army Communications-Electronics Command
and Fort Monmouth
ATTN: AMSEL-ED-TO
Fort Monmouth, NJ 07703-9990

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:02Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-49309 (CR)	Cooler-Dewar Group, OR-336/A, OR-337/A

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE. HISA-FM 149-85

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:02Z
Check the source to verify that this is the current version before use.