MIL-D-63122B(AR)
14 January 1985
SUPERSEDING
MIL-D-63122A(AR)
17 December 1979

MILITARY SPECIFICATION

DISPENSER, GENERAL PURPOSE, AIRCRAFT: M130

This Specification is approved for use by the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This Specification covers the inspection and testing of the M130 Aircraft General Purpose Dispenser hereafter referenced to as the dispenser system.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-C-48890	-	Control Panel For M130 Dispenser System
MIL-D-63123	-	Dispenser Assembly
MIL-E-63124	-	Electronic Module Assembly
MIL-D-63199	-	Dispenser, General Purpose, Aircraft: M130 Repair Parts For

FSC 1095

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

8806652	-	Marking and Sealing For Cylindrical Containers
9272533	-	Dispenser Control Panel Assembly
9311430	-	M130 System
9311431	-	Module Electronic
9311434	-	Dispenser Assembly
9311451	-	Payload Module Assembly
9313708	-	Packing and Marking For Drum, Metal, Shipping for M130 Aircraft General Purpose Dispenser

INSPECTION EQUIPMENT DRAWINGS

9280370	-	Test Set-Up For Functional Test (Dispenser System)

U.S. ARMY ARMAMENT, MUNITIONS AND CHEMICAL COMMAND

19-48-4138/109-20 PA1000	-	Unitization Procedures For Boxed Ammunition and Components on Skidded Bases

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer).

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specification.

3.2 Assembly. The dispenser system shall comply with all requirements specified on Drawing (Dwg.) 9311430, and all associated drawings and applicable specifications.

3.3 Functioning. The dispenser system shall function as specified herein.

3.3.1 Arm. The dispenser shall respond to input signals only when a 22.5 to 30.0 volt, direct current (dc), arm signal is present.

3.3.2 Chaff/flare count. A chaff count signal or a flare count signal shall be generated each time a chaff or flare is dispensed. These signals shall be 20.0 to 30.0 volts dc.

3.3.3 Dispense output. Each of the thirty outputs of the dispenser shall provide 5.0 ± 0.75 amperes dc firing signal into a resistive load of 1.0 ± 0.1 ohm for 15 milliseconds minimum.

3.3.4 Flare misfire. Failure of a signal flare to eject or ignite shall result in firing of the next sequential flare within 85 milliseconds. This capability shall be limited to three flare dispense actions only.

3.3.5 Stray voltage. There shall be no stray voltage across a 3.0 + 0.5 ohm load between any of the 30 firing pins and ground when the Dispenser System is powered up. (Voltage readings of less than 1 volt for less than 3 seconds duration is acceptable.)

3.3.6 Power loss. In case of power loss, the system shall retain the position of the next payload to be fired.

3.4 Electronic module. The assembly shall be inspected and tested in accordance to MIL-E-63124.

3.5 Dispenser assembly. The assembly shall be inspected and tested in accordance to MIL-D-63123.

3.6 Dispenser control panel. The assembly shall be inspected and tested in accordance to MIL-C-48890.

3.7 Air leakage test. Each packaged dispenser system shall show no evidence of leakage when tested in accordance with 4.4.3.2.

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:16Z
Check the source to verify that this is the current version before use.

3.8 First article inspection. First article inspection shall be performed in accordance with the technical provisions in the applicable component specification (See 3.4, 3.5 and 3.6 and requirements of Table I). Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.9 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner, and all manufacturing, processing, and assembly operations shall be correctly performed. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, surface defects, chips, dirt, grease and oil (except where specifically required), corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part or assembly, nor shall they be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings and stampings shall be neat and sharply defined. Required packing shall be dry and packaging operations performed in a thorough workmanlike manner.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein, or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2 and 4.3.3. The first article sample shall consist of the following items in sample quantities as indicated below:

Part description	Drawings	Quantity
M130 System	9311430	2

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63122B(AR)

PARAGRAPH	TITLE: Dispenser, General Purpose, Aircraft: M130		SHEET 1 OF 1		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Dispenser, General Purpose, Aircraft M130 (Drawing 9311430)				
	Electrical tests	2		3.3	4.5.2
	Payload Module Assembly (Drawing 9311451)				
	Examination for defects (Note 1)	2		3.2	4.4.2.1
	Packing and Marking For Drum, Metal Shipping For M130 Aircraft General Purpose Dispenser (Dwg. 9313708)				
	Examination for defects	2		3.2	4.4.2.2
	Air leakage test	2		3.7	4.5.1

NOTES:
1. See MIL-D-63199, Paragraph 4.4.2.6.

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test Tables in this specification, sampling plans for major and minor defects shall be in accordance with MIL-STD-105. Equipment necessary for the performance of the inspection listed shall be in accordance with 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-63122B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Payload Module Assembly				9311451
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	(Dwg. 9311479 or 9335632)				
101	Squareness dimensions of payload holes (30)		0.40%	3.2	Gage
102	Position of payload holes (30)		0.40%	3.2	Gage
103	Wall thickness		0.40%	3.2	Gage
104	Overall length, width, height (Dwg. 9311446)		0.40%	3.2	Gage
105	Position of dowel pin holes		0.40%	3.2	Gage
106	Position of slots		0.40%	3.2	Gage
107	Overall length, width and thickness		0.40%	3.2	Gage
108	Any component loose, missing, or improperly mounted (All items)		0.40%	3.2	Visual
Minor	(Dwg. 9311479 or 9335632)				
201	Markings missing or illegible (Dwg. 9311479, 9335632, 9311446)		0.65%	3.2	Visual
202	Protective finish missing or inadequate		0.65%	3.2	Visual
203	Poor workmanship (All items)		1.00%	3.9	Visual
NOTES:					

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63122B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Dispenser, General Purpose Aircraft: M130				9311430
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Dispenser, General Purpose, Aircraft M130 (Dwg. 9311430)				
	Electrical test		0.40%	3.3	4.5.2
102	Payload Module Assembly (Dwg. 9311451)				
	Examination for defects		0.40%	3.2	Note 1
NOTES:	1. See MIL-D-63199, Para. 4.4.2.6.				

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-63122B(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Packing and Marking for Drum, Metal, Shipping for M130 Aircraft General Purpose Dispenser				9313708 NEXT HIGHER ASSEMBLY 19-48-4138/109
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cushions missing, torn or not secured		0.40%	3.2	Visual
102	Contents not thoroughly dry		0.40%	3.2	Visual
103	Any component missing, damaged or improperly assembled		0.40%	3.2	Visual
104	Cushions not proper density		0.40%	3.2	Visual
105	Air Leakage Test		100%	3.2	4.5.1
Minor					
201	Marking missing, incorrect or illegible		0.65%	3.2	Visual
202	Fillers insufficient, loose contents		0.65%	3.2	Visual
203	Metallic seal missing or not properly secured		0.65%	3.2	Visual
204	Poor workmanship		1.00%	3.9	Visual

NOTES:

DRSMC-QA (D) Form 160, 1 Aug 83 replaces edition of 1 Jul 77 which may be used until exhausted.

Source: https://assist.dla.mil -- Downloaded: 2026-02-23T02:16Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Electrical tests. Major Defect. A sample of 20 dispenser systems shall be selected from each lot and subjected to the electrical tests as specified in 4.5.2 using equipment in accordance with 4.4.4. The dispenser shall be conditioned for four (4) hours minimum at 25 ± 5°C (ambient). If any dispenser system fails to meet the requirements, the lot shall be rejected.

4.4.3.2 Air leakage test (See Dwg. 8806652). Major Defect. This test shall be performed 100% and as specified in 4.5.1 using equipment in accordance with 4.4.4. Any drum which fails the test shall be classified defective and removed from the lot.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the table starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.4 herein.

4.5 Method of inspection.

4.5.1 Air leakage test. The drums shall be tested using the procedures on drawing (Dwg) 8806652. (Non-Destructive Test)

4.5.2 Functioning. Each dispenser system selected for testing shall be subjected to testing utilizing the functioning test system and procedures in 9280370. (Non-Destructive Test)

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A. Preservation and packaging shall be in accordance with Dwg. 9313708.

5.2 Packing.

5.2.1 Level A. Packing shall be in accordance with Dwg. 9313708.

5.3 Marking.

5.3.1 Level A. Marking shall be in accordance with Dwg. 9313708.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

5.4 Unitization.

5.4.1 Level A. Unitization of the M130 Dispenser as packed in 5.2.1 shall be in accordance with Dwg. 19-48-4138/109-20 PA1000 (DARCOM Ammo Center).

6. NOTES

6.1 Intended use. The M130 Aircraft General Purpose Dispenser is intended to dispense chaff and flare countermeasures for Army aircraft.

6.2 Ordering data. Procurement documents shall specify the following:

a. Title, number and date of this specification.

b. Provisions for submission of first article samples.

c. Provisions of MIL-A-48078.

6.3 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, Picatinny Arsenal or ARRADCOM drawings. Technical data originally prepared by these activities is now under cognizance of ARDC.

6.4 Submission of inspection equipment designs for approval. (See MIL-A-48078). Submit equipment designs as required, to Commander, U.S. Army Armament Research and Development Center, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801.

6.5 Distribution of ammunition data cards. Distribution of data cards shall include the following: Commander, U.S. Army Armament Research and Development Center (ARDC), ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801.

6.6 Changes from previous issue. Asterisks are not used in this revision with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1095-A141)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-63122B (AR)	Dispenser, General Purpose, Aircraft: M130

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:16Z
Check the source to verify that this is the current version before use.