INCH-POUND
MIL-PRF-83383/2D
28 May 1999
SUPERSEDING
MIL-C-83383/2C
30 September 1987

PERFORMANCE SPECIFICATION SHEET

# CIRCUIT BREAKERS, REMOTE CONTROL, AC-DC, THERMAL, TRIP-FREE, SERIES TRIP, SINGLE POLE, AUXILIARY CONTACTS (5 TO 100 AMPERES)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification and MIL-PRF-83383.





FIGURE 1. Dimensions and configuration.


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:53Z
Check the source to verify that this is the current version before use.

| Current rating amperes | A | B +.015 -.000 | C | Nut | Lock washer | Flat washer |
|---|---|---|---|---|---|---|
| 5 to 25 | .190-32UNC-2A | .500 | .500 | AN315-3R | MS35338-43 | AN960-10L |
| 35 to 100 | .250-28UNF-2A | .610 | .610 | AN315-4R | MS35338-44 | AN960-416 |


| Inches | mm | Inches | mm | Inches | mm |
|---|---|---|---|---|---|
| .005 | 0.13 | .172 | 4.37 | .500 | 12.70 |
| .010 | 0.25 | .180 | 4.57 | .60 | 15.2 |
| .030 | 0.76 | .190 | 4.83 | .610 | 15.49 |
| .050 | 1.27 | .20 | 5.1 | .688 | 17.48 |
| .056 | 1.42 | .250 | 6.35 | 1.200 | 30.48 |
| .060 | 1.52 | .256 | 6.50 | 1.530 | 38.86 |
| .061 | 1.55 | .350 | 8.89 | 2.250 | 57.15 |
| .070 | 1.78 | .400 | 10.16 | 2.940 | 74.68 |
| .084 | 2.13 | .420 | 10.67 | 3.250 | 82.55 |
| .150 | 3.81 | .484 | 12.29 | 3.420 | 86.87 |
| | | | | 4.260 | 108.20 |

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Unless otherwise specified, tolerance is ±.015 (0.38 mm) for three decimal places and ±.03 (0.76 mm) for two decimal places.
4. Stiffening webs at mounting flanges shown for reference profile as required.
5. Current rating markings may be rotated 90 degrees from the type marking shown in order to accommodate large ampere ratings.

FIGURE 1. Dimensions and configuration – Continued.




Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:53Z
Check the source to verify that this is the current version before use.




NOTE: Terminals 5A and 5B shall be internally grounded to the mounting flange(s).

FIGURE 2. Schematic.




Note: Terminal junction system (TJS) module shall accept pin contacts P/N M39029/1-100 or -101.

FIGURE 3. Terminal junction system module.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:53Z
Check the source to verify that this is the current version before use.

TABLE I. Dash numbers and characteristics.

| Dash number | Current rating (amperes) | Tripping times from -54°C ±5°C to +71°C ±5°C (time in seconds) | | | | | |
|---|---|---|---|---|---|---|---|
| | | Percent rated current | | | | | |
| | | 200 | | 400 | | 1000 | |
| | | Min | Max | Min | Max | Min | Max |
| 01 | 5.0 | 7 | 40 | 1.2 | 6.4 | .3 | 1.2 |
| 02 | 7.5 | 11 | 40 | 2.4 | 6.8 | .33 | 1.1 |
| 03 | 10.0 | 12 | 42 | 2.8 | 8.5 | .42 | 1.05 |
| 04 | 15.0 | 13 | 45 | 1.7 | 8.3 | .35 | 1.2 |
| 05 | 20.0 | 14 | 46 | 2.9 | 7.6 | .4 | 1.15 |
| 06 | 25.0 | 15 | 50 | 2.6 | 8.7 | .4 | 1.3 |
| 07 | 35.0 | 16 | 55 | 2.8 | 8.3 | .35 | 1.3 |
| 08 | 40.0 | 16 | 55 | 2.9 | 9.2 | .36 | 1.3 |
| 09 | 50.0 | 13 | 55 | 2.9 | 10 | .4 | 1.25 |
| 10 | 60.0 | 13 | 60 | 2.6 | 13 | .26 | 1.8 |
| 11 | 75.0 | 13 | 60 | 2.5 | 13 | .26 | 1.8 |
| 12 | 80.0 | 14 | 60 | 2.7 | 12.5 | .3 | 2 |
| 13 | 100.0 | 17 | 63 | 3.5 | 13 | .35 | 1.9 |

REQUIREMENTS:

Interface and physical dimensions: See figure 1.

Weight:

5 to 25 amperes: 0.735 pound (334 grams), maximum.

35 to 50 amperes: 0.750 pound (341 grams), maximum.

60 to 100 amperes: 0.766 pound (348 grams), maximum.

Trip indication: See figure 1.

Terminals: See figures 1 and 2.

Auxiliary contact terminals:

Contact capacity at 28 V dc and 115 V ac, 400 Hz shall be 3 amperes resistive, 1.5 amperes inductive, and 0.5 ampere lamp load.

Voltage rating: 28 V dc or 115 V ac, 400 Hz.

Current ratings: See table I.

Tripping times: See table I.

Response time: 25 milliseconds, maximum.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:53Z
Check the source to verify that this is the current version before use.

Power requirements and response time at minimum voltage:

Standby current drain and actuation current:

Test voltage: 28 ±0.5 V dc to TJS module, then 115 ±2 V ac, 400 Hz to line terminal. Actuating current, 3.5 amperes dc and 11 amperes ac rms maximum.

Maximum operating time at minimum voltage:

Test voltage: 18 V dc then 104 V ac rms, 400 Hz, maximum.

Endurance:

Electrical:

5 to 25 amperes: 50,000 cycles resistive or inductive or motor load or lamp load.

35 to 50 amperes: 50, 000 cycles resistive or inductive or motor load or 25,000 cycles lamp load.

60 to 100 amperes: 50,000 cycles resistive or inductive load or 25,000 cycles motor load.

Interrupting capacities:

A - 3,600 amperes.

B - 3,600 amperes.

C - 3,600 amperes.

D - 3,600 amperes.

Other marking:

Current rating: See figure 1.

Line and load terminals: See figure 1.

Terminal junction system (TJS) module: See figure 3.

Position indication: See figure 1. Indication is provided by a lens over “open” and “closed” on red and green background.

Part number: M83383/02- (dash number from table I) (e.g., M83383/02-01).



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:53Z
Check the source to verify that this is the current version before use.

Indicator/control unit (I/CU): In order to maintain compatibility between the RCCB and the I/CU, the following must be observed when making an I/CU selection:

a. The I/CU must be a ½ ampere rated circuit breaker (MS22073-1/2 or MS26574-1/2, or equivalent).

b. The line impedance (terminal 3 to I/CU) plus the I/CU impedance plus I/CU to ground connection.

c. The I/CU must respond to a decreasing current pulse of $I^2t \leq 2$ throughout the temperature range.

CAUTION TO USERS:

Coordination between devices supplied by different manufacturers should be verified by the user.

Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - CR
Navy - AS
Air Force - 11
DLA - CC

Review activities:
Army – AT, AV, CR4
Air Force - 99

Preparing activity:
DLA - CC

(Project 5925-0272-02)



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:53Z
Check the source to verify that this is the current version before use.