MIL-P-28739(EC)
AMENDMENT 2
1 June 1970

SUPERSEDING 1/
MIL-P-28739(EC)
AMENDMENT 1
20 April 1970

MILITARY SPECIFICATION

PEDESTAL GROUP, ANTENNA, FOR IFF ANTENNAS AN/UPA-57

This amendment forms a part of Military Specification MIL-P-28739(EC), 7 April 1970.

Page 1

1.1, line 6: Delete "solidstate" and substitute "solid-state"

Page 4

3.5.14 Size and weight.

3.5.14.1 Pedestal group. The pedestal group shall be designed to mount on a flat, level surface. The base shall be covered and closed as the unit shall not require underneath access for maintenance and servicing. It shall be designed to mount at three or more points on a bolt

1/ Changes from previous issue. The outside margins of this document have been marked "#" to indicate where changes (deletions, additions, etc.) from the previous issue have been made. This has been done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content as written irrespective of the marginal notations and relationship to the last previous issue.

FSC 5985

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:06Z
Check the source to verify that this is the current version before use.

circle no greater than twenty-four inches diameter. The height shall not exceed twenty-six inches and the weight shall be no greater than 125 pounds.

3 5 14.2 Control power supply unit. This unit shall be designed for below-deck shelf mounting on the base by means of four bolts. The design shall permit withdrawal of the complete unit from the front of the cabinet. The unit shall not exceed the following:

(a) Width: 16-7/8 inches
(b) Depth: 16-1/2 inches
(c) Height: 13 inches
(d) Weight: 60 pounds

3 5.14.3 Manual antenna positioning control. This unit shall be designed to permit withdrawal of the complete unit from the front. Connection entrance shall be from the rear. The size of this unit shall not exceed 12 inches in height, 9 inches in width and 6 inches in depth The weight shall not exceed 8 pounds.

3.5.18, item (a): Delete and substitute:

"(a) Temperature: Class 1 for above deck units, except the upper limit is 125°C
Class 2 for below deck units".

3.6.1: Add "(The AS-2188 antenna is approximately 111 inches long, 19 inches high and 20 inches deep, weighing about 80 pounds. This antenna is slightly larger and heavier than the AT-352/UPA-22 antenna.

3.7 3: Delete and substitute:

"3.7.3 Synchro transmitters. Both a 1:1 and a 36:1 synchro transmitter shall be provided to supply azimuth information to an indicator when the pedestal is in the free running condition "

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:06Z
Check the source to verify that this is the current version before use.

3.7.4, line 1: Delete "capacity-type" and substitute "contact-type"; and line 4, delete "Hz" and substitute "cycle".

Page 8

3.8, line 4: Delete "fuseholders" and substitute "circuit breakers, test points".

3.8.3 Delete and substitute:

"3.8.3 Primary power line voltage and frequency. See 3.5.15.

3.8.4 Delete and substitute:

"3.8.4 Accessibility The equipment shall be completely removable from the front of the cabinet by means of slides provided for this purpose. These slides shall permit complete withdrawal of the unit from its case, with a lock for retention in this position. In this position provisions shall be made for turning the unit on its horizontal axis ± 90°, with locking provisions at 0°, ± 45° and ± 90°. Sufficient cable length shall be provided within the chassis to permit operation and troubleshooting in any and all of the above positions, the cable being supported by a horizontal spring-loaded arm or similar device approved by the command or agency concerned. The front panel layout, with its controls and test points, in accordance with MIL-STD-1472 shall be submitted for the approval of the command or agency concerned "

3.9 Delete and substitute:

"3.9 Manual antenna positioning control. A manual antenna positioning control shall be provided, to enable the operator to position the IFF antenna to any azimuth setting from a remote position. It shall have a dial showing the relative antenna bearing and a control to switch from slaved operation, to free running operation, or to manual operation. The performance of the system in the slaved or the free running operation shall not be impaired in any way should the manual antenna positioning

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:06Z
Check the source to verify that this is the current version before use.

control be disconnected. It shall be designed to mount on top, bottom, or either side, as desired."

4.2, line 1: Delete "all units" and substitute "one unit".

Page 12

4.5.5, line 1: Between "conducted" and "in" insert "on units noted in 3.5.1".

4.5.6.2: Item (a), delete "Class 2" and substitute "Class 1, with upper limit of 125°C"; and Item (b), delete "Class 4" and substitute "Class 2".

4.5.7, line 3: Delete "Hz" and substitute "cycle".

Preparing activity:
Navy - EC

(Project 5985-N345)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:06Z
Check the source to verify that this is the current version before use.