MIL-C-45459C (AR)
20 APRIL 1982
SUPERSEDING
MIL-C-45459B (MU)
23 August 1972

MILIARY SPECIFICATION

CARTRIDGE, 75MM, BLANK, M337A2
LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of cartridge designated as Cartridge, 75MM, Blank, M337A2 for Guns M3 and M6, and Howitzers and M1A1 and M3.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-223 - Powder, Black
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For
MIL-STD-105 - Sampling Procedures and Tables For Inspection by Attributes

DRAWINGS (see 6.5)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT AND PACKAGE DRAWINGS

7549268 - Box, Packing, Ammo., for 75MM Gun and Howitzer Ammo. Assembly, Details and Packing

FSC: 1315

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

7549269 - Container, Ammo., Fiber, M27A2, for 75MM Gun and Howitzer Ammo. Assembly, Details and Packing
7549273 - Cartridge, 75MM, Blank M337A2, for Gun M5 and Pack Howitzer M1A1, M1A1C Assembly

INSPECTION EQUIPMENT DRAWINGS

6510104 - Chamber
6518130 - Check, Alignment
6510196 - Check, Wear Limit
7304935 - Check, Alignment
6518145 - Check, Wear Limit

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specifications.

3.2 Components and assemblies. Components and assemblies shall comply with all requirements specified on Drawing (dwg) 7549273, and with all requirements specified in applicable specifications and standards.

3.3 Primers. The primers shall conform with the applicable primer drawing with respect to the number and location of flash holes.

3.4 Air pressure test of the primer and cartridge case assembly. The cartridge case, with primer assembled thereto, shall withstand a minimum air pressure of 3515 kilograms per square meter (kgs/sq m), 5 pounds per square inch (psi) for a minimum of 15 seconds without leaking, as evidenced by a drop in gage pressure of 7.032 kgs/sq m, (.01 psi) maximum when tested as specified in 4.5.3.

3.4.1 Air pressure test of cartridge assembly. The complete cartridge shall withstand a minimum air pressure of 3515 kgs/sq m (5 psi) for a minimum of 15 seconds without leaking as evidenced by a drop in gage pressure if 7.031 kgs/sq m (0.01 psi) maximum, when tested as specified in 4.5.4.

3.5 Functioning (proving ground test). The cartridge shall comply with the following requirements when tested as specified in 4.5.5.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the current version before use.

3.5.1 Safety. There shall be no misfires, hangfires in excess of 10 seconds or indications of metal parts failure in the gun bore during any of the proving ground tests conducted.

3.5.2 Sound level. The cartridge shall function with a sound level of 115 decibels minimum, when tested at ambient temperature as specified in 4.5.5.

3.5.4 Fragment. There shall be no fragments thrown more than 92 meters (300 feet) beyond the weapon muzzle. Metal part separation or breakup is excluded. No metal part failures are acceptable. If any metal part fails, the lot shall be rejected.

3.6 Workmanship

3.6.1 General. The cartridge and all components shall be free of cracks, burrs which can affect assembly, functioning or prove injurious to personnel handling the item; chips, dirt, grease, rust, corrosion or other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents.

3.6.2 Painting and marking. Prior to packaging of cartridges, painting and marking which may have been marred or obliterated during handling shall be restored by the contractor to meet requirements of applicable drawings.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspection. The followiing types of inspection shall be performed on this item:

a. First Article Inspection
b. Quality Conformance Inspection

4.3 First article inspection

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

4.3.1 Submission. The contractor shall submit a first artcle sample as designated by the contracting officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Cup, Closing	7549272	10 (Note a)
Wad, Closing	7549271	10
Case, Cartridge (M9A1)	8861524	10
Primer (M1A2)	8839453	10 (Note b)
Primer (M1B1A2)	8839474	10 (Note b)
Cartridge, 75mm Blank, M337A2 Assembly	7549273	45

NOTES:

a. Sample to consist of ten (10) consecutively produced cups from each cavity of each mold.
b. M1A2 or M1B1A2 as required by contract/order.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:04Z
Check the source to verify that this is the currentversion before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1		DRAWING NUMBER
	Cartridge, 75MM, Blank, M337A2 Assembly and Components			See Below
				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup, Closing Dwg. 7549272 Examination for Defects	10	(a)	3.2	4.4.2.1
	Wad Closing Dwg. 7549271 Examination for Defects	10		3.2	4.4.2.2
	Case Cartridge Dwg. 8861524 Examination for Defects	10		3.2	4.4.2.3
	Primer Dwg. 8839453 (M1A2) or 8839474 (M1B1A2) Examination for Defects	10		3.2	4.4.2.4
	Cartridge Assembly M337A2 Dwg. 7549273 Examination for Defects	45	(b)	3.2	4.4.2.5
	Proving Ground Test (Functioning) Dwg. 7549273	20	(b)	3.5	4.5.5

NOTES:
(a) Refer to Note a. in 4.3.1.
(b) After inspection as per 4.2.2.5, 20 of the 45 inspected assemblies shall be selected at random for Proving Ground Tests.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078 (see 6.6). In addition, inspection lots of Cartridge 75mm, Blank M337A2 for Howitzers shall contain:

a. Primer assemblies of one lot interfix number from one manufacturer.

b. Black powder of one lot interfix number from one manufacturer.

c. New or fired cartridge cases modified by one manufacturer from one lot interfix number.

d. Closing cups from one manufacturer in accordance with the same drawing and drawing revision.

e. Closing wads from one manufacturer in accordance with the same drawing and drawing revision.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 20260-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-C-45459C (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 7549272
4.4.2.1	Cup, Closing		NEXT HIGHER ASSEMBLY 7549273

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Cup Cracked, Broken, Punctured or Malformed		0.40%	3.2	Visual
102	Visible weld lines		0.40%	3.2	Visual
MINOR					
201	Outside Diameter		0.65%	3.2	Gage
202	Hole Missing		0.65%	3.2	Visual
203	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4 3.2	Wad, Closing		7549271
			NEXT HIGHER ASSEMBLY 7549273

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Outside Diameter, Minimum (Min.)		0.65%	3.2	Gage
202	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Case, Cartridge (Empty)		8861524
			NEXT HIGHER ASSEMBLY
			7549273

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Distance from Bottom of Primer Counterbore to Front of Seating Surface		0.40%	3.2	Gage
102	Crack or Split Extending through Sidewall or Bottom		0.40%	3.2	Visual
MINOR					
201	Total Length		0.65%	3.2	Gage
202	Incorrect Protective Finish (Applicable to Steel Cases Only)		0.65%	3.2	Visual
203	Evidence of Poor Workmanship		0.65%	3.6	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8839453 or 8839474
4.4.2.4	Primer, Prior to Assembling into Case				NEXT HIGHER ASSEMBLY 7549273
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
CRITICAL					
1	One or More Primer Flash Holes Missing		100%	3.2	Visual
MAJOR					
101	Assembly Incomplete or Improper		0.40%	3.3	Visual
102	Check Test for Deterioration	(a)			

NOTES:

(a) Refer to Paragraph 4.4.3.1.

DRDAR Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE	SHEET] OF]	DRAWING NUMBER
4.4.2.5	Cartridge, 75MM, Blank, M337A2 Assembly		7549273
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Assembly, Primer and Case				
CRITICAL 1	Primer above Flush		100%	3.2	Visual/Straight Edge
MAJOR 101	Primer Loose		0.40%	3.2	Visual/Manual
102	Air Pressure Test		0.40%	3.4	4.5.3
MINOR 201	Foreign Matter on Interior		0.65%	3.6	Visual
	Assembly Prior to Inserting Closing Wad				
CRITICAL	None defined				
MAJOR 101	Black Powder Moisture Content	1/		3.2	4.5.2
102	Black Powder Missing or Inadequate		0.40%	3.2	Visual
MINOR	None defined				

NOTES:

DRSAR QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 2 OF 3	DRAWING NUMBER
4.4.2.5	CONTINUATION SHEET		7549273
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Assembly After Inserting Wad and Closing Cup				
CRITICAL	None defined				
MAJOR					
101	Seal not Continuous or Groove not Filled with Cement		0.40%	3.2	Visual
102	Air Escape Hole not Filled with Cement		0.40%	3.2	Visual
MINOR	None defined				
	Assembly				
CRITICAL	None defined				
MAJOR					
101	Air Pressure Test of Cartridge Assembly		100%	3.4.1	4.5.4
102	Chamber Gage Failure (Profile and Alignment)		0.40%	3.2	Gage
103	Assembly Damaged or Improper		0.40%	3.2	Visual
104	Closing Cup Cracked, Loose or Damaged		0.40%	3.2	Visual/Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

MIL-C-45459C (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 3 OF 3	DRAWING NUMBER
4.4.2.5	CONTINUATION SHEET		7549273
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
MINOR					
201	Marking Incorrect or Unidentifiable		0.65%	3.2	Visual
202	Glue or Asphalt on Exterior of Cartridge		0.65%	3.2	Visual
203	Evidence of Poor Workmanship		0.65%	3.6	Visual
	Proving Ground Test (Functioning)				
CRITICAL	None defined				
MAJOR					
101	Functioning (First Three Lots)	20	2/	3.5	4.5.5
	Subsequent Lots	10	2/	3.5	4.5.5
MINOR	None defined				

1/ Select sample in accordance with MIL-P-223. Select 1 sample from each 8 hours production. Failure to comply with the specified requirement shall be cause for rejection of the 8 hours production represented by the sample.

2/ A quantity of 20 shall be fired for 1st Article and 20 from the 1st three consecutively-produced lots. If no failures occur, the sample size may be reduced to 10 for subsequent lots. If any subsequent lot contains failures, the 20 sample size shall be reinstated until such time as 3 consecutive acceptable lots are produced. The lots shall be rejected if any major defect occurs.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22 10:30 MST
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.6	Fiber Container		7549269
			NEXT HIGHER ASSEMBLY 7549268

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Unsealed Fiber Container				
CRITICAL	None defined				
MAJOR					
101	Packing Component Missing		0.40%	3.2	Visual
MINOR					
201	Round cannot be Removed by Hand		0.65%	3.2	Manual
202	Round Improperly Assembled in Container		0.65%	3.2	Visual
	Sealed Fiber Container				
CRITICAL	None defined				
MAJOR					
101	Tape Incomplete or Inner Layer not in Contact with the Surface of the Container for at Least 1/2 inch on Each Side of the Joint		0.40%	3.2	Visual
102	Metal End Loose or Distorted		0.40%	3.2	Visual/Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.6	CONTINUATION SHEET		7549269
			NEXT HIGHER ASSEMBLY 7549268

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
103	Container damaged through all impregnated asphalt layers as evidenced by removing each layer of suspected container		0.40%	3.2	Visual
104	DODIC marking missing or incorrect		0.40%	3.2	Visual
MINOR					
201	Length of Tear Tab, Min.		0.65%	3.2	Visual
202	Color of Tape Incorrect		0.65%	3.2	Visual
203	Marking Misleading or Unidentifiable		0.65%	3.2	Visual
204	Cut, Scuffs or Gouges in Outer Layer		0.65%	3.2	Visual
205	Gap between Body and Cover of Container Exceeding 1/8 Inch		0.65%	3.2	Visual/Gage (See 6.7)
206	Contents Loose Upon Shaking		0.65%	3.2	Manual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE	SHEET 1 OF 2	DRAWING NUMBER
4.4.2.7	Wood Box		7549268
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE INSPECTION METHOD
	Prior to Sealing				
CRITICAL	None defined				
MAJOR					
101	Incorrect Number of Components		0.40%	3.2	Visual
102	Containers Improperly Positioned		0.40%	3.2	Visual
103	Packing Material Insufficient		0.40%	3.2	Visual
MINOR	None defined				

NOTES:

DRD[illegible]A Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45459C (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.7	CONTINUATION SHEET				7549268
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECT ON METHOD
	Sealed Packing Box				
Critical	None defined				
MAJOR					
101	Strapping Missing or Loose		0.65%	3.2	Visual/Manual
102	Hardware Missing or Loose		0.65%	3.2	Visual/Manual
103	Contents of Box Exposed		0.65%	3.2	Visual
104	FSN and DODIC Marking Missing or Incorrect		0.65%	3.2	Visual
105	Board Broken or Split		0.65%	3.2	Visual
106	Metallic Seal Missing or Broken		0.65%	3.2	Visual
MINOR					
201	Hasp Improperly Engaged		0.65%	3.2	Visual/Manua
202	Strapping Improperly Assembled		0.65%	3.2	Visual/Manua
203	Marking Misleading or Unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Check test for possible deterioration of primers (see applicable primer specification). If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into complete cartridges exceeds two years or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the primer lot shall be subjected to and must satisfactorily pass the check test specified in the applicable primer loading specification immediately before the primer lot is assembled into cartridges. (See 6.4).

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Sections 6 of MIL-A-48078 and 6 herein.

4.5 Methods of inspection

4.5.1 Materials, components and processes. Compliance with all requirements of Section 3 of this specification shall be ascertained by current and continuing examination of inspection and test data to determine that all components (parts, subassemblies, and materials) have been inspected and tested and found to comply with their respective drawing and specification requirements, and that all specified manufacturing processes have been followed. (See 6.8).

4.5.1.1 Visual and mechanical inspections. The visual, manual and mechanical inspections and tests shall verify compliance with the requirements of Sections 3 and 5 of this specification in accordance with 4.4.2 herein and Table I.

4.5.2 Moisture content of black powder. The moisture content of the black powder shall be determined in accordance with the procedure specified in specification MIL-P-223.

4.5.3 Air pressure test of the primer and cartridge case assembly. The primer and cartridge case assembly shall be subjected to an air pressure test using testing equipment in accordance with 4.4.4. Observation shall be made for compliance with requirements of 3.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

4.5.4 Air pressure test of cartridge assembly. The complete cartridge shall be subjected to an air pressure test using test equipment in accordance with 4.4.4. Observation shall be made for compliance with requirements of 3.4.1.

4.5.5 Functioning. This test shall be performed by the government at a proving ground or as designated by the contracting officer. The cartridge test rounds shall be uniformly temperature conditioned at 21°C ± 1.5° (70°F ± 2.5°) for a minimum of 24 hours prior to testing. Compliance with the sound level requirement shall be determined using a General Radio Company impact noise analyzer Type 1556-A in conjunction with a Type 1551-B Sound-Level meter or equivalent. The pick-up microphone shall be located 30.48 meters (100 feet) from the gun muzzle on a line perpendicular to the axis of the tube. Observation shall be made for compliance with paragraph 3.5.

5. PACKAGING

5.1 Packaging requirements. Fiber container shall be packaged as specified on drawing 7549269.

5.2 Packing requirements. The box shall be packed as specified on drawing 7549268.

5.3 Marking. Marking shall be as specified on drawings 7549269 and 7549268, as applicable.

6. NOTES

6.1 Intended use. The Cartridge, 75MM Blank, M337A2 Assembly is intended for use in the family of 75MM artillery weapons.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals- See MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

6.4 Cost of primer check test. The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the primers or the contractor assembling the cartridge, and shall not constitute a basis

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the currentversion before use.

for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.6 Inspection lot size. It is noted that the size of inspection lots of components, assemblies or items of delivery required by this specification may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

6.7 Visual examination qualification. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic in question may be measured or gaged to determine acceptability.

6.8 Alternative testing procedures. Alternative testing procedures may be used by the contractor. The contractor shall describe these alternate procedures in a written proposal and shall demonstrate for the approval of the responsible Government technical agency that their effectiverness is equal to, or better than the quality assurance provisions specified herein.

6.9 Proving ground test summary

	SAMPLE SIZE	TEMP
First Article	20	$21^{\circ} \pm 1.5^{\circ}C$ ($70^{\circ} \pm 2.5^{\circ}F$)
First three lots	20	$21^{\circ} \pm 1.5^{\circ}C$
Subsequent lots	10	$21^{\circ} \pm 1.5^{\circ}C$

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the currentversion before use.

6.10 Submission of ballistic test data and ammunition data cards. In addition to the normal distribution of records for items procured by the Department of the Army two copies of all ballistic test data and ammunition data cards shall be forwarded to Commander, ARRADCOM, Dover, New Jersey 07801, ATTN: DRDAR-QAR-Q and DRDAR-LCU-CP.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1315-A375)

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-45459C CARTRIDGE, 75MM, BLANK, M337A2 LOADING, ASSEMBLING AND PACKING

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
ENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armamemnt R&D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.