MILITARY SPECIFICATION

CHARGE, PROPELLING, 175MM, M86A2B1 LOADING, ASSEMBLING, AND PACKING

This specification is approved by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of propelling charge designated as Charge, Propelling, M86A2B1 for 175MM Gun M113, A1.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposals form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-P-223	-	Powder, Black
MIL-C-12800	-	Cloth, Acrylic
MIL-C-13814	-	Cloth, Igniter
MIL-C-43157	-	Cloth, Spun Viscose Rayon Resin Impregnated
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-414	-	Sampling Procedures and Tables for Inspection by Variables for Percent Defective

FSC: 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

MIL-STD-1235 - Single and Multi-Level Continuous Sampling Procedures and Tables for Inspection by Attributes

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

PRODUCT AND PACKAGE DRAWINGS

8837905 - Charge, Propelling, 175MM, M86A2B1 for Gun M113,A1
8857288 - Packing for Container, Metal Ammo M460A2 for Charge, Propelling, 175MM, M86A2B1 for Gun M113
7548187 - Packing and Marking of Metal Containers for Propelling Charges
9219182 - Protective Assembly for Container Metal, Ammo M460A2B1 for Charge, Propelling 175MM, M86A2B1 and M199

3. REQUIREMENTS

3.1 Materials - Materials shall be in accordance with applicable drawings and specifications.

3.2 Propelling charge - The propelling charge shall comply with all requirements specified in applicable specifications.

3.3 Moisture content of black powder - The moisture content of the black powder at the loading station at the time of loading shall not exceed the amount specified in MIL-P-223.

3.4 Weights

3.4.1 Propellant weight - The propellant weight shall comply with the weight specified in the loading authorization within plus or minus 0.40 ounce for zone 2; and 0.40 ounce for zone 3.

3.4.2 Charge, propelling assembly weight - The charge, propelling assembly weight shall not differ by more than plus or minus 2.00 ounce from the total of the component weights.

3.5 Dimensional gages - The completed charge or zone shall freely enter the prescribed gage(s). The gage(s) shall be designed to inspect the maximum diameters of the zones and charge and total length of charge.

3.6 Proving ground - The muzzle velocity, pressure, and velocity standard deviation shall be as specified in Table I.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the current version before use.

Table I

Zone	Proj	Temp	Velocity (feet per second) Minimum	Maximum	Velocity Standard Deviation FPS	Individual Maximum Pressure PSI
3	M437A2	70°F	2940	3060	10.0	N/A
3	M437A2	145°F	(Differential Pressure)		-	58,000
3	M437A2	-65°F	(Differential Pressure)		-	N/A

3.7 Assembly torque - The test plug shall be assembled to withstand subsequent reapplication of the minimum assembly torque specified on the applicable drawing, without moving.

3.8 First article inspection - This specification contains technical provisions for the first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.9 Workmanship - All components shall be free of dirt, grease and other foreign material. There shall be no discoloration or deterioration of cloth and no evidence of rips, tears, or other cloth defects. All work shall be performed in a thorough workmanlike manner. Rips or tears in the eyelet area and stretching of cloth caused by lacing the charge is acceptable provided the lacing cord in the head is not broken.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions - Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification. Unless otherwise specified in the contract, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of inspection - The following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection

Source: https://assist.dla.mil -- Downloaded: 202640-22T03:04Z
Check the source to verify that this is the currentversion before use.

4.3.1 Submission - The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. This sample shall consist of the following:

Part Description	Drawing	Quantity
Strap, Tying	8837917	5
Igniter Core	8837911	10 of each part
End, Igniter	8337919	10 of each part
Base Pad and Igniter Core Assembly	8865060	10
Base Igniter and Igniter Core Assembly	8865061	10
Base Igniter and Igniter Core Loading Assembly	8865276	10
Igniter Core Loading Assembly	8837922	10 of each part
Igniter Core Assembly	8837923	10 of each part
Zone No. 2 Body Assembly	8837914	10
Zone No. 3 Body Assembly	8837915	10
Zone No. 2 Loading Assembly	8837906	10
Zone No. 3 Loading Assembly	8837908	10
Charge, Propelling, 175MM; M86A2B1 for Gun M113A1 (in sealed containers)	8837905	10
Containerized Charge	7548187	10
Cloth, Acrylic (if applicable)		4 square yards
Cloth, Spun Viscose Rayon, Resin Impregnated, Class I (if applicable)		4 square yards
Cloth, Igniter		4 square yards

4.3.2 Inspections to be performed - The First Article parts submitted in accordance with paragraph 4.3.1 will be subjected by the Government to any or all the requirements of the applicable drawings and specifications and to the inspections of Table II. All inspections listed in Table II shall be classified Major unless otherwise specified in referenced paragraphs and specifications.

4.3.3 Rejection - See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the current version before use.

TABLE II - FIRST ARTICLE INSPECTIONS

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 4		DRAWING NUMBER
	Propelling Charge Components and Assemblies				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Strap Tying (Dwg 8837917) Examination for defects	5		3.2	4.4.2.1
	Igniter Core (Dwg 8837911) Examination for defects	(b)		3.2	4.4.2.2
	End, Igniter (Dwg. 8837919) Examination for defects	(b)		3.2	4.4.2.3
	Base Pad and Igniter Core Assembly (Dwg. 8865060) Examination for defects	10		3.2	4.4.2.4
	Base Igniter and Igniter Core Assembly (Dwg. 8865061) Examination for defects	10		3.2	4.4.2.5
	Base Igniter and Igniter Core Loading Assembly (Dwg. 8865276) Examination for defects (Note a)	10		3.2	4.4.2.6

NOTES:

a. All defects except major defect 102.

b. 10 of each part number.

Source: https://assist.dla.mil -- Downloaded: 2020-10-22 10:30:42
Check the source to verify that this is the current version before use.

TABLE II FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 2 OF 4		DRAWING NUMBER
	CONTINUATION SHEET				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Igniter Core Loading Assembly (Dwg 8837922)				
	Examination for defects (Note c)	(d)		3.2	4.4.2.7
	Igniter Core Assembly (Dwg. 8837923)				
	Examination for defects	(d)		3.2	4.4.2.8
	Zone No. 2 Body Assembly (Dwg. 8837914)				
	Examination for defects	10		3.2	4.4.2.12
	Zone No. 3 Body Assembly (Dwg. 8837915)				
	Examination for defects	10		3.2	4.4.2.13
	Zone No. 2 Loading Assembly (Dwg 8837906)				
	Examination for defects	10		3.2	4.4.2.14

NOTES:

c. All defects except Major 102.
d. 10 of each part number.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

TABLE II - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 3 OF 4		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
	CONTINUATION SHEET				
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Zone No. 3 Loading Assembly (Dwg. 8837908)				
	Examination for defects	10		3.2	4.4.2.15
	Charge Propelling, 175MM; M86A2B1 for Gun M113A1 (in sealed containers) (Dwg. 8837905 and 9219182)	10			4.4.2.16/4.4.2.17 4.4.2.18/4.4.2.19
	Examination for defects (Note e)	10			4.4.2.20
	Containerized Charge (Dwg 9219182)				
	Examination for defects	10		3.2	4.4.2.21
	Cloth, Spun Viscose Rayon, Resin Impregnated Class 1 (if applicable)	Note f		Note g.	Note h

Notes

e. All defects except: Critical 2, paragraph 4.4.2.16, Major Defects 101, 105, 111, and 112, paragraph 4.4.2.16; Major defects 102 and 104, paragraph 4.4.2.18.

f. See Military Specification MIL-C-43157.

g. All physical characteristics listed in Table 1 in paragraph 3.5 of Military Specification MIL-C-43157.

h. See paragraph 4.3.1 of Military Specification MIL-C-43157.

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

TABLE II - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 4 OF 4		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	CONTINUATION SHEET				
	Cloth, Igniter	Note j		note k	Note m.
	Cloth, Acrylic	Note n		Note p	Note q

Notes

j. See Military Specification MIL-C-13814.

k. All physical characteristics listed in Table 1 in paragraph 3.14 of Military Specification MIL-C-13814.

m. See paragraphs 4.13, 4.14 and 4.15 of MIL-C-13814.

n. See Military Specifiction MIL-C-12800.

p. All physical characteristics listed in paragraphs 3.2.3, 3.2.4 and 3.2.7 of Military Specification MIL-C-12800.

q. See paragraphs 4.4.4, 4.4.5, and 4.4.8 of Military Specification MIL-C-12800.

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection

4.4.1 Inspection lot formation - Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of propelling charge assemblies shall contain:

a. Propellant from not more than one lot number from one manufacturer.

b. Black powder from not more than one interfix number from one manufacturer.

c. Tubes from not more than one interfix number from one manufacturer.

4.4.2 Examination - See MIL-A-48078.

a. Sampling plans - Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Strap, Tying	1 OF 1	8837917
			NEXT HIGHER ASSEMBLY: 8837914

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Cloth improper			3.1	4.5.5.2
Minor 201	Width	Note a		3.2	Scale

NOTES:

a. During the slitting process each roll will be inspected within the first ten feet and last ten feet, i.e., two measurements per roll.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Core, Igniter		8837911
			NEXT HIGHER ASSEMBLY
			8837922

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tie missing		100%	3.2	Visual
102	Minimum distance from edge of cloth to seam		100%	3.2	Visual
103	Cloth improper (tape)			3.1	4.5.5.2
104	Cloth improper			3.1	4.5.5.1
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837919
4.4.2.3	End, Igniter				NEXT HIGHER ASSEMBLY 8865060 or 8865061
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cloth improper			3.1	4.5.5.1
102	Diameter of igniter end		0.40%	3.2	Gage
Minor					
201	Marking missing, misleading, or unidentifiable		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Base Pad and Igniter Core Assembly				8865060
					NEXT HIGHER ASSEMBLY 8865061
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Location of igniter core bag assembly (including location of seam)		100%	3.2	Gage
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8865061
4.4.2.5	Base Igniter and Igniter Core Assembly				NEXT HIGHER ASSEMBLY 8865276
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of seam circle		0.40%	3.2	Scale
102	Quilting missing or improper (including length)		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Base Igniter and Igniter Core Loading Assembly				8865276
					NEXT HIGHER ASSEMBLY
					8837906
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly incorrect or damaged to the extent that black powder can escape (including any seams or openings incompletely stitched or broken threads)		100%	3.2	Visual/Manual
Major					
101	Weight of black powder	(a)	100%	3.2	4.5.1
102	Moisture content of black powder			3.3	4.5.3
103	Distance from end of igniter core to seam		0.40%	3.2	Scale
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

(a) See paragraph 4.4.3.2

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837922
4.4.2.7	Igniter Core Loading Assembly				NEXT HIGHER ASSEMBLY 8837923
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly incorrect or damaged to the extent that black powder can escape (including any seams or openings incompletely stitched or broken threads)		100%	3.2	Visual/Manual
Major					
101	Weight of black powder		100%	3.2	4.5.1
102	Moisture content of black powder	(a)		3.3	4.5.3
103	Minimum distance from end of igniter core to seam		0.40%	3.2	Visual
104	Tie missing		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES: (a) See paragraph 4.4.3.2

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837923
4.4.2.8	Igniter Core Assembly				NEXT HIGHER ASSEMBLY 8837906 or 8837908
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly incorrect or damaged to the extent that black powder can escape (including any seams or openings incompletely stitched or broken threads)		100%	3.2	Visual
2	Igniter core loading assembly missing, insecure, or improperly located in tube		100%	3.2	Visual
Major	None defined				
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	End				8837909
					NEXT HIGHER ASSEMBLY
					8837912
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cloth improper			3.1	4.5.5.2
Minor					
201	Established length		0.65%	3.2	Scale
202	Established width of straight section		0.65%	3.2	Scale

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837912
4.4.2.10	End Assembly				NEXT HIGHER ASSEMBLY 8837914 or 8837915
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Seam improper		0.40%	3.2	Visual/Manual
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Body, Zone				8837913
					NEXT HIGHER ASSEMBLY
					8837914 or 8837915
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Cloth improper			3.2	4.5.5.2
102	Lacing cord missing or improperly assembled (2 locations)		0.40%	3.2	Visual/Manual
Minor					
201	Marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.9	Visual
203	Any seam improper or incompletely stitched		0.65%	3.2	Visual/Manual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837914
4.4.2.12	Zone No. 2 Body Assemmbly				NEXT HIGHER ASSEMBLY 8837906
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Tying strap missing, incompletely stitched or improperly located		0.40%	3.2	Visual
102	Any seam improperly stitched		0.40%	3.2	Visual/Manual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 8837915
4.4.2.13	Zone No. 3 Body Assembly				NEXT HIGHER ASSEMBLY 8837908
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Any seam incompletely stitched		0.40%	3.2	Visual/Manual
Minor 201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Zone No. 2 Loading Assembly				8837906
					NEXT HIGHER ASSEMBLY
					8837905
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly incorrect or damaged to the extent that black powder can escape (including any seam or openings incompletely stitched or broken threads)		100%	3.2	Visual
2	Base igniter and igniter core loading assembly missing, improper or improperly assembled to body assembly		100%	3.2	Visual
3	Bell igniter tube improper or improperly assembled to body assembly		100%	3.2	Visual
Major					
101	True position of basepad		100%	3.2	Gage
102	Propellant weight			3.4.1	4.5.2
103	Dimensional Gage (diameter)		100%	3.5	Gage
104	Lacing missing, improper, or insecure		100%	3.2	Visual/Manual
105	Assembly damaged to the extent that propellant can escape (including any seams or openings incompletely stitched or broken threads)		100%	3.2	Visual
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.15	Zone No. 3 Loading Assembly				8837908
					NEXT HIGHER ASSEMBLY
					8837905
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly incorrect or damaged to the extent black powder can escape		100%	3.2	Visual
2	Igniter core assembly missing, improper, or improperly assembled to body assembly		100%	3.2	Visual
Major					
101	Propellant weight			3.4.1	4.5.2
102	Lacing missing, improper, or insecure		100%	3.2	Visual/Manual
103	Assembly damaged or improper to the extent that propellant can escape (including any seam or openings incompletely stitched or broken threads)		100%	3.2	Visual
104	Dimensional Gage (diameter)		100%	3.5	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.16	Charge, Propelling, 175MM; M86A2B1 for Gun M113, A1				8837905
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Assembly damaged or improper to the extent that black powder can escape		100%	3.2	Visual/Manual
	Proving Ground				
2	Pressure	(a)		3.6	4.5.6
Major					
101	Dimensional gage failure (maximum length and diameter)		100%	3.5	Gage
102	Igniter protector cap missing or improper (both ends)		0.40%	3.2	Visual
103	Propelling charge assembly weight		100%	3.4.2	4.5.8
104	Igniter tube above flush with propellant bed		100%	3.2	Visual

NOTES:

a. Samples monitored for muzzle velocity and muzzle velocity standard deviation and differential pressure will be monitored for pressure.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.16	CONTINUATION SHEET	2 OF 2	8837905
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
105	Zones insecurely tied at junction		100%	3.2	Visual/Manual
106	Assembly damaged or improper to the extent that propellant can escape		100%	3.2	Visual
107	Additive jacket missing, improper, or improperly assembled to charge		100%	3.2	Visual
108	Strap loose, broken or insecurely tied		100%	3.2	Visual/Manual
	Proving Ground				
109	Muzzle velocity and muzzle velocity standard deviation	10		3.6	4.5.6
110	Differential pressure (info)	20		3.6	4.5.6
Minor					
201	Evidence of poor workmanship		0.65%	3.9	Visual
202	Marking missing, misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Container, Prior to Insertion of Charge				8857288
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Foreign matter or rust in container		100%	3.2	Visual
102	Wrapper or bottom cushion missing or improperly located		100%	3.2	Visual
Minor					
201	Damaged container (to include dents protruding greater than 1/4" into container)		0.65%	3.2	Visual/Gage (see 6.4)

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil - 27 - Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER 7548187 and 8857288
4.4.2.18	Container, Prior to Sealing		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Primer missing on protector cap prior to sealing bag		100%	3.2	Visual
102	Bag missing or not taped shut		100%	3.2	Visual
103	Charge cannot be removed by hand	(a)		3.2	4.5.9
104	Top cushion missing or incorect type; i.e., cushion does not have hole		0.40%	3.2	Visual
Minor	None defined				

NOTES:

(a) One sample from each eight hours production.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 7548187
4.4.2.19	Container, Sealed				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Test plug missing		100%	3.2	Visual
102	DOD symbol missing, misleading or unidentifiable (if applicable)		0.40%	3.2	Visual
103	Test plug assembly torque		0.40%	3.7	Test
104	Air pressure test		100%	3.2	4.5.4
Minor					
201	Test plug not greased (to be checked after air pressure test and prior to reassembly)		0.65%	3.2	Visual
202	Metallic seal missing or incorrectly applied		0.65%	3.2	Visual
203	Marking missing, misleading, or unidentifiable		0.65%	3.2	Visual
204	Cover incompletely engaged		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9219182
4.4.2.20	Metal Container with Overpack				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Two or more nails missing		0.65%	3.2	Visual
202	Strapping missing or loose		0.65%	3.2	Visual
203	Nails protruding outward from protective assembly		0.65%	3.2	Visual
204	Marking missing, misleading or unidentifiable		0.65%	3.2	Visual

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45463E (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.21	Containerized Charge				9219182
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Note (a)	Tear Down Inspection	(b)	(c)		4.5.7
Notes:	(a) Category is critical or major dependent upon the category of the defect inspected. (b) See paragraph 4.4.3.1. (c) Requirement paragraph is dependent upon inspection performed.				

NOTES:

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Teardown inspection

4.4.3.1.1 Initial production lot sampling - In addition to the samples of 4.4.3.1.2, three completely assembled charges shall be randomly selected from each days production until three consecutive days production is found acceptable.

4.4.3.1.2 Lot sampling - Ten completely assembled charges shall be randomly selected from each lot. If there is a lapse in production in excess of ninety (90) days, or the previous lot was waived or rejected due to this inspection, sampling will return to initial production lot sampling.

4.4.3.2 Moisture content of black powder. At least one sample of black powder from each eight hours loading of igniter assemblies will be tested for moisture content.

4.4.4 Inspection equipment - The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and paragraph 6.3 of this specification.

4.5 Test methods and procedures

4.5.1 Weight of black powder - The inspections below are to be conducted by inspection personnel using equipment designated for inspection purposes and shall be clearly distinguished from production operations.

4.5.1.1 Base igniter and igniter core loading assembly - The weight of the black powder for each compartment will be inspected 100 percent. The weight of the black powder in the basepad will be determined by subtracting an average weight of the empty assembly or the actual weight as marked on the individual assembly from the loaded basepad, empty igniter core assembly weight. The weight of the black powder in the igniter core will be determined by subtracting the actual or average weight of the loaded basepad, empty igniter core assembly from the loaded base igniter and igniter core loading assembly weight.

4.5.1.2 Igniter core loading assembly - The weight of the black powder will be inspected 100 percent by subtracting

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

an average weight of the empty igniter core assembly or the actual weight as marked on the individual assembly from the loaded igniter core loading assembly weight.

4.5.2 Propellant weight (see 3.4) - The inspections below are to be conducted by inspection personnel using equipment designated for inspection purposes and shall be clearly distinguished from production operations. Any zone which fails to comply with the applicable requirement shall be classed defective and removed from the lot. Inspection equipment shall be in accordance with 4.4.4.

4.5.2.1 Method 1 - The loaded zones will be inspected 100 percent. The weight of the propellant will be determined by subtracting an average weight of the empty zone body assembly or the actual weight as marked on the individual zone body assembly from the loaded zone body assembly weight.

4.5.2.2 Method 2 - The propellant in a container shall be weighed and then checkweighed on a different balance and if performed manually, by another operator. In addition, the propellant weight of the loaded zone will be inspected using a sampling plan from MIL-STD-105 or MIL-STD-1235 with an AQL of 0.40 percent. The weight of the propellant will be determined by subtracting an average weight of the empty zone body assembly or the actual weight as marked on the individual zone body assembly from the loaded zone body assembly weight.

4.5.3 Moisture content of black powder - The moisture content of the black powder will be determined in accordance with MIL-P-223. If any sample fails to meet the specified requirement, the eight hours production represented by the sample shall be rejected.

4.5.4 Air pressure test - Each container shall be tested as specified on the appropriate drawing. A pressure drop equivalent to or greater than the applicable requirement shall be cause for rejection and removal from the lot.

4.5.5 Cloth

4.5.5.1 Cloth for ignition components - Any sample which fails to comply with the applicable requirement shall be cause for rejection of the cloth bolt represented by the sample. The method of inspection to be used during production is to be established by the contractor and approved by the Government.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

The method, as a minimum, shall contain positive assurance that the material being utilized has been verified for compliance with the specification requirements as stated above. (See 6.9)

4.5.5.1.1 Cloth, spun viscose rayon resin impregnated - Each roll, as a minimum, shall be tested for compliance with the physical characteristics listed in Table I in 3.5 of MIL-C-43157. Testing will be in accordance with 4.3.1 of MIL-C-43157.

4.5.5.1.2 Cloth, igniter - Each roll, as a minimum, shall be tested for compliance with the physical characteristics listed in Table 1 in 3.14 of MIL-C-13814. Testing will be in accordance with 4.13, 4.14, and 4.15 of MIL-C-13814.

4.5.5.1.3 Cloth, acrylic - Each roll, as a minimum, shall be tested for compliance with the physical characteristics of 3.2.3, 3.2.4, and 3.2.7 of MIL-C-12800. Testing will be in accordance with 4.4.4, 4.4.5, and 4.4.8 of MIL-C-12800.

4.5.5.2 Cloth - At the time cloth is introduced to the sewing and/or cutting operation, an identification will be made for each roll to verify that proper material is used. Any cloth failing to be identified as proper material in accordance with applicable drawings and specifications shall be rejected from the lot.

4.5.6 Proving ground (see 3.6) - This test shall be conducted at a Government Proving Ground in accordance with the applicable acceptance test procedure using M437A2 projectiles inert loaded within 0.1 pound of an as fired weight of 147.75 pounds using Primer, M82 and fired in cannon M113A1. Prior to firing, all charges shall be temperature conditioned in large conditioning boxes at the required temperature ($\pm 2^{o}F$) for a minimum of 24 hours and assurance will be made that, when fired, the charges are at the conditioning temperature (as indicated by thermocoupled control charges). Copper crusher gages (2) shall be used to measure the maximum chamber pressure of each charge. Velocity coils will be used to measure the muzzle velocity of each charge.

4.5.6.1 Muzzle velocity and muzzle velocity standard deviation - Determination of acceptance will be in accordance with MIL-STD-414, Section B, Table B3, AQL of 0.65%. All muzzle velocity and muzzle velocity standard deviation samples will be ballistic tested at $70^{o}F$. Ten (10) zone 3 charges will be fired for muzzle velocity and muzzle velocity standard

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:04Z
Check the source to verify that this is the currentversion before use.

deviation. If the sample is determined unacceptable the lot will be rejected. In addition, if the velocity standard deviation of the sample multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected. Ten (10) zone 3 calibration charges will be fired alternately with the test samples and the muzzle velocity and pressure of all test charges will be corrected to standard conditions.

4.5.6.2 Differential pressure - Two pressure-time gages at different locations (one in the spindle and one at the projectile base) will be used to record pressure-time traces. Differential pressure traces will be obtained by subtracting the projectile gage output from the spindle gage output. The maximum differential pressure of any charge will be defined as the maximum amplitude of the first negative wave of the differential pressure trace. Any trace which contains no amplitude in the negative direction will be considered to have a maximum differential pressure of zero. Ignition delay will be recorded for information on all differential pressure firings. Ten (10) zone 3 charges each will be conditioned to -65°F and 145°F for differential pressure firings. Ten (10) zone 3 calibration charges will be fired intermixed (five (5) at each temperature) with the test samples.

4.5.6.3 Pressure - If any propelling charge individual corrected maximum pressure exceeds the applicable requirement, the lot shall be rejected.

4.5.7 Teardown inspection - Each container and propelling charge will be subjected to each of the critical (except critical defect 2., paragraph 4.4.2.16) and 100 percent major (except major defects 101 and 102, paragraph 4.4.2.2; major defect 101, paragraph 4.4.2.6; major defects 101 and 102, paragraph 4.4.2.7; major defects 101, 102 and 103, paragraph 4.4.2.14; major defect 101, paragraph 4.4.2.15; major defect 103, paragraph 4.4.2.16) inspections defined in 4.4.2 of this specification. Samples may be accumulated or inspected upon selection providing the selection remains random and represents the lot. The inspections will be performed by the contractor and witnessed by the Government. The detection of any of the above defects shall be cause for rejection of the lot.

4.5.8 Charge, propelling, assembly weight - The average weight or the actual weight as marked on the individual assembly of the zone body assemblies, additive jacket, base igniter and igniter core assembly, igniter core for zone 3, bell igniter tubes plus the average weight of the lacing cords together with the nominal black powder and propellant weights shall be subtracted from the propelling charge assembly weight.

Source: https://assist.dla.mil -- Downloaded: 202640-22T03:04Z
Check the source to verify that this is the current version before use.

If the resulting weight deviation is greater than the requirement, the propelling charge will be classified defective and removed from the lot (see 6.8).

4.5.9 Charge removal from container - Each sample shall be tested for removal of the propelling charge from the container by hand. The charge may be pulled out by the tying straps or the container may be inverted and the charge either pulled out or slid out. Each charge tested shall be checked for damage to the tying straps (looseness, tears, etc.) and the charge will be repaired (retie the tying straps and relace the charge, if necessary). Each charge tested shall be rewrapped (may use the same wrapper if the wrapper is not badly damaged) and re-packed in accordance with this specification and the applicable drawings. Any charge that cannot be removed from the container using the above method shall be cause for rejection of the production represented by the sample.

5. PACKAGING

5.1 Packing and marking - The propelling charges shall be packed in accordance with the specified requirements of drawing 8857288. Containers will be closed, sealed, tested and marked in accordance with the specified requirements of 7548187. The protective assembly for the containers will be done in accordance with the specified requirements of 9219182.

6. NOTES

6.1 Intended use - The propelling charges covered by this specification are intended for use in the 175MM Gun, M113,A1.

6.2 Ordering data - See MIL-A-48078.

6.3 Submission of designs for approval - See 6.2.3 of MIL-A-48078. Submit equipment designs, as required, to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, New Jersey 07801.

6.4 Visual examination qualification - When compliance with the applicable requirement is in doubt as a result of visual examination the characteristic may be measured or gaged to determine acceptability.

6.5 Inspection lot size - It is noted that the size of inspection lots of components, assemblies, or terms of delivery may differ from the actual quantities contractually scheduled for delivery. However, in order to facilitate scheduling of tests or deliveries, inspection lots of items of delivery may be equivalent to such contract quantities provided all of the lot formation criteria and sampling provisions of this specification are maintained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

6.6 Proving ground - A copy of all proving ground data should be submitted to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-R and DRDAR-LCA-G Dover, New Jersey 07801.

6.7 Teardown inspection - A list of all defects found during teardown inspection shall be submitted to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-R, Dover, New Jersey 07801.

6.8 Charge, propelling assembly weight - This requirement applies to the load plant at the time of loading only. Due to subsequent change in tare weight of the components because of variation in material and moisture content, this test cannot be repeated after initial manufacture to the degree of accuracy required.

Weights to be Determined	Drawing or Part Number
Actual/Average Weight of - Bell Igniter Tube	8864105-3 8864105-4
Actual/Average Weight of- Additive Jacket	9217039
Actual/Average Weight of - Igniter Cores	8837911-3 8837911-4
Actual/Average Weight of - Base Igniter and Igniter Core Assembly	8865061
Actual/Average Weight of - Zone No. 2 Body Assembly	8837914
Actual/Average Weight of - Zone No. 3 Body Assembly	8837915
Average Weight of Cord	8837905 8837906 8837908

6.9 Method of inspection submission - Methods of inspection for cloth for ignition components and polyester thread shall be submitted to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-R, Dover, New Jersey 07801, for approval.

Source: https://assist.dla.mil -- Downloaded: 20261O-22T03:04Z
Check the source to verify that this is the currentversion before use.

6.10 Proving ground summary (see 4.5.6).

Temp	Sample Size	Number of Ref Rounds	Velocity	Maximum Individual Pressure	Differential Pressure
70° F	10	10	*	INFO	NA
145° F	10	5	INFO	58,000	INFO
-65° F	10	5	INFO	INFO	INFO

*See 4.5.6.1 and 3.6.

6.11 Test plug assembly torque - This requirement applies to the load plant at the time of loading only. Due to creep of the mechanical properties of the test plug washer, this test cannot be repeated after initial manufacture.

6.12 Changes from previous issue - Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number:
1320-A590

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-C-45463E CHARGE PROPELLING, 175MM, M86A2B1 LOADING, AND ASSEMBLING, PACKING

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:04Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament R & D Command
ATTN: DRDAR-QAR
Dover, New Jersey 07801

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:04Z
Check the source to verify that this is the current version before use.