MILITARY SPECIFICATION

CHARGE, SPOTTING, FOR WARHEAD, M38
FOR
762MM ROCKET
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-45474B (MU), dated 30 December 1969, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

PAGE 8

Add new paragraphs 4.3.3.4 and 4.3.3.5 as follows:

"4.3.3.4 Light measurement test. - A sample in accordance with inspection level S-1 of MIL-STD-105D shall be tested from each lot, and the integral light, peak light and duration time shall be recorded (see 6.4). The test shall be performed as specified in 4.4.5 using equipment in accordance with 4.3.4, for ten (10) consecutive lots after which time accept/reject criteria will be established and imposed by the technical agency.

4.3.3.5 Air pressure test (See dwg; 8833417) Major Defect, Code No. 10001. - Each spotting charge shall be subjected to this test. The test shall be performed as specified in 4.4.6 using equipment in accordance with 4.3.4."

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.

PAGE 9

Add new paragraphs 4.4.5 and 4.4.6 as follows:

"4.4.5 Light measurement test. - The sample shall be inserted into an item charge well assembled with item gasket and cover and secured to the test stand. Ignition system shall consist of pyrocare lead assembly (ei. Du Pond De Nemours Inc. PN X-822 or approved equivalent) and a XM-70 or T-60 detonator. The sample shall be ignited and the flash duration, peak intensity, and time to peak recorded using the equipment and procedures as contained in the applicable Equipment List.

4.4.6 Air pressure test. - The loaded spotting charge shall be placed in a chamber and a predetermined volume of air shall be introduced to produce the specified pressure into the chamber. The spotting charge shall satisfactorily pass this test if the pressure does not drop during the specified time interval. The equipment shall be calibrated on an approved periodic basis to confirm accuracy of the equipment. This is a non-destructive test. Parts so tested may be returned to the lot."

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A624)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.