MIL-C-45476B (MU)

24 APRIL 1964

SUPERSEDING
MIL-C-45476A (MU)
8 MARCH 1963

MILITARY SPECIFICATION

CHARGE, SPOTTING, FOR WARHEAD, M38 FOR 762MM ROCKET PARTS FOR

1. SCOPE

1.1 This specification covers the quality assurance provisions, and special requirements not covered by the drawings, for the parts for one type of pyrotechnic item designated as Charge, Spotting, for Warhead, M38 for 762MM Rocket.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids, or request for proposals, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 — Ammunition and Special Weapons; General Specification for.

MIL-P-10025 — Packaging, Packing and Marking for Interplant Shipment of Inert Ammunition Components; General Specification for.

MIL-I-45208 — Inspection Requirements; General Specification for.

MIL-I-45607 — Inspection Equipment, Supply and Maintenance of.

MIL-D-45608 — Designs and Drawings, Ordnance Inspection Equipment.

STANDARDS

MILITARY

MIL-STD-105 — Sampling Procedures and Tables for Inspection by Attributes.

MIL-STD-109 — Quality Assurance Terms and Definitions.

FSC 1340

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:07Z
Check the source to verify that this is the current version before use.

MIL–STD–1235 — Single and Multilevel Continuous Sampling Procedures and Tables for Inspection by Attributes.

DRAWINGS

ORDNANCE CORPS

8833418 — Spotting Charge, Metal Parts Assembly.

PUBLICATIONS

ORDNANCE CORPS

IEL–8833418 — Index of Inspection Equipment Lists.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Assemblies. The assemblies shall comply with all requirements specified on Drawing dwg. 8833418 and with all requirements specified in applicable specifications.

3.3 Soldering. The surfaces to be soldered shall be free of all foreign matter. The solder shall be smooth and continuous and shall not extend above the disc.

3.4 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, unblended radii, surface defects, dirt, grease, flux, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Surface coatings shall be continuous except for a few slight scratches not exposing base material. All required marking shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 General quality assurance provisions. Suppliers responsibility will be as specified in the contract or purchase order. Reference shall be made to Standard MIL–STD–109 in order to define terms used herein. The provisions of Specification MIL–A–2550 shall apply.

4.1.1 *Contractor quality assurance system.* The contractor shall provide and maintain an effective quality assurance system in compliance with the requirements of Specification MIL–I–45208.

4.1.2 *Submission of product.* At the time the completed lot of product is submitted to the Government for acceptance the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

(a) A statement that the lot complies with all quality assurance provisions of the approved current written description of the system.

(b) Number of units of product inspected.

(c) Results obtained for all inspection performed.

(d) Drawing, specification number and date, together with an identification and date of changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:07Z
Check the source to verify that this is the current version before use.

(e) Certificates of compliances on all material purchased by the contractor when such material is controlled by Government specifications referenced in any of the contractual documents.

(f) Number of items in the lot.

(g) Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.1.3 *Government verification.* Using the contractor's written quality assurance procedure, this detail specification, the applicable drawings and other contractual documents as a guide, the Government inspector shall verify at unscheduled intervals all quality assurance operations performed by the contractor. Verification will be in accordance with Specification MIL–I–45208 and will be performed to the extent necessary to assure compliance with the contractual requirements. Severity of Government inspection of individual characteristics will be directly related to the seriousness of the classification assigned. In no instance will a characteristic classified "critical" be accepted solely on the basis of the contractor's records.

4.2 **Initial production inspection.**

4.2.1 Prior to the start of regular production, the contractor shall submit an initial production sample to a Government approved facility as designated by the Contracting Officer (see 6.4) for evaluation in accordance with the provisions of 4.2.2. The initial production sample shall consist of 10 assemblies and 10 complete sets of parts (i.e., 10 each of every component and every subassembly) which have been produced by the contractor or furnished by a supplier and which have been manufactured using the same production processes, procedures and equipment which will be used in fulfilling the contract. All parts and materials, including packaging and packing shall be obtained from the same sources of supply as will be used in regular production. The sample shall be accompanied by certificates of compliance for materials. An initial production sample, or portion thereof, as directed by the Contracting Officer, shall also be submitted whenever there is a lapse in production for a period in excess of 90 days, or whenever a change occurs in manufacturing process, material used, drawing, specification or source of supply as to significantly affect product uniformity, as determined by the Government. Prior to submission the contractor shall inspect the sample to the degree necessary to assure that it conforms to the requirements of the contract and submit a record of this inspection with the sample. A sample containing known defects will not be submitted unless specifically authorized by the Contracting Officer.

4.2.2 *Inspections to be performed.* Assemblies and components will be subjected by the Government to any or all of the examinations or tests specified in 4.3.2 of this specification and any or all requirements of the applicable drawings.

4.2.3 *Rejection.* If any assembly or component fails to comply with any of the applicable requirements, the initial production sample shall be rejected. The Government reserves the right to terminate its inspection upon any failure of an assembly or component in the sample to comply with any of the stated requirements. In the event of rejection, the Government reserves the right to require the contractor to take corrective action and submit a new initial production sample, or portion thereof. Until an initial production sample is accepted, the duction sample is accepted, the contractor

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:07Z
Check the source to verify that this is the current version before use.

contractor is, in no way, authorized by the Government to initiate regular production unless otherwise directed by the Contracting Officer.

4.3 Inspection provisions.

4.3.1 *Lot formation.* A lot shall consist of assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification, and same specification revision. Drawing, specification, and process changes not affecting safety, performance or fit, as determined by the Government shall not necessitate changing the lot interfix number.

4.3.2 *Examination.* Sampling plans and procedures for the following classifications of defects shall be in accordance with Standard MIL–STD–105 except that inspection for critical defects, when listed, shall be 100 percent. Continuous sampling plans in accordance with Standard MIL–STD–1235 may be used if approved by the procuring activity. Also, at the option of the procuring activity, AQL's and sampling plans may be applied to the individual characteristics listed using an AQL of 0.25 percent for each major defect and an AQL of 0.40 percent for each minor defect. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.3.4.

4.3.2.1 Cup (see dwg. 8833416 covering a detail of dwg. 8833418).

Categories	*Defects*	*Method of inspection*	*Code No. (see 6.2)*
Critical: None defined.			
Major: None defined.			
Minor:	**AQL 1.50 percent**		
201.	Outside diameter, minimum (min.)	Gage	01001
202.	Inside diameter, maximum (max.)	Gage	01002
203.	Length, min.	Gage	01003
204.	Evidence of poor workmanship (see 3.4)	Visual	01004

4.3.2.2 Cap, bottom (see dwg. 8833419 covering a detail of dwg. 8833418).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined.			
Major:	**AQL 0.25 percent**		
101.	Wall thickness	Gage	02001
Minor:	**AQL 1.50 percent**		
201.	Height, min.	Gage	02002
202.	Inside diameter, max.	Gage	02003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:07Z
Check the source to verify that this is the current version before use.

203.	Diameter of hole, max.	Gage	02004
204.	Evidence of poor workmanship (see 3.4)	Visual	02005

4.3.2.3 Cap, top (see dwg. 8833420 covering a detail of dwg. 8833418).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Thickness	Gage	03001
Minor:	AQL 1.00 percent		
201.	Outside diameter	Gage	03002
202.	Evidence of poor workmanship (see 3.4)	Visual	03003

4.3.2.4 Disc (see dwg. 8833415 covering a detail of dwg. 8833418).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined.			
Major:	AQL 0.25 percent		
101.	Thickness	Gage	04001
Minor:	AQL 0.40 percent		
201.	Diameter	Gage	04002

4.3.2.5 Assembly (see dwg. 8833418).

Categories	*Defects*	*Method of inspection*	*Code No.*
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Disc solder inadequate or not continuous (see 3.3)	Visual	05001
102.	Interior coating missing or not continuous	Visual	05002
103.	Top cap solder inadequate or not continuous	Visual	05003
104.	Component loose	Manual	05004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:07Z
Check the source to verify that this is the current version before use.

Minor:	AQL 0.40 percent		
201.	Evidence of poor workmanship (see 3.4)	Visual	05005

4.3.3 *Inspection Equipment.* Index of Inspection Equipment Number IEL–8833418 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.3.3.1 *Government rights to documentation.* Inspection equipment drawings and lists provided and revised in accordance with the requirements of the IEL may be used by DOD activities for design, procurement, manufacture, testing, evaluation production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.3.3.2 *Supply and maintenance.* Supply and maintenance of the equipment listed on the IEL shall be in accordance with Specification MIL–I–45607.

4.3.3.3 *Government use of contractor's inspection and test equipment.* The contractor shall make available to the Government all inspection and test equipment necessary for determining conformance with contract requirements. Personnel for operating the equipment, and verification of its accuracy, shall be supplied by the contractor for the performance of examination or test by the Government.

5. PREPARATION FOR DELIVERY

5.1 Packing

5.1.1 *Level C.* The assemblies shall be packed in accordance with Specification MIL–P–10025.

5.2 **Marking.** Marking shall be in accordance with Specification MIL–P–10025.

5.3 **Data cards.** Data card information shall be prepared for each lot as specified in Specification MIL–A–2550.

6. NOTES

6.1 **Ordering data.** Procurement documents shall specify the following:

(a) Title, number and date of this specification.

6.2 **Inspection code numbers.** The five digit code numbers assigned to the inspections herein are to facilitate future date collection and analysis by the Government.

6.3 **Inspection equipment.** The contractor shall design inspection equipment as required by the referenced Inspection Equipment Lists (IEL) in accordance with the instructions of 6.3.1 through 6.3.7.

6.3.1 *Inspection Equipment Lists.* Inspection Equipment Lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (00 Form 1242-3) the numbers of drawings of existing equipment designs or codes as indicated in 6.3.2. Design action required of the contractor with respect to the different types of drawings that may be listed is described in 6.3.3 and 6.3.4. Action required by the contractor with respect to commercial inspection equipment is described in 6.3.5. The contractor will be required to prepare detailed drawings in accordance with 6.3.6 for all the equipment coded as "contractor design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procur-

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:07Z
Check the source to verify that this is the current version before use.

ing of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.2 *Inspection Equipment List codes.* The inspection equipment as defined in 6.3.3, 6.3.4, 6.3.5, and 6.3.6 will be designated in the Inspection Equipment List by the following codes:

CDAF — Contractor's design responsibility on Army format in accordance with Specification MIL–D–45608.

CDCF — Contractor's design responsibility on contractor format.

AD — Army design.

ADMU — Army design, mandatory for use.

CE — Commercial equipment.

SCD — Specification Control Drawing.

6.3.3 *Army designs.* Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory and non-mandatory. When an Inspection Equipment List references mandatory Army designs, the contractor shall comply with, and use these designs accordingly. The contractor may, however, in connection with non-mandatory designs and with the approval of the Government, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.7.

6.3.4 *Specification control drawings.* Specification control drawings depict the minimum equipment requirements in outline, descriptive, diagrammatic, or pictorial form only and specify the required performance or other characteristics. Contractors must prepare detailed drawings (see 6.3.6) of their designs in support of specification control drawings. These contractor prepared designs must be approved by the Government prior to the fabrication or procuring of the equipment. Commercial equipment meeting the requirements of specification control drawings may be approved if described in sufficient detail to permit identification and evaluation by the Government. Designs shall be submitted for approval as specified in 6.3.7.

6.3.5 *Commercial equipment.* Commercial equipment is inspection equipment that has universal application for a specific function. It is comprised of items commonly used by industry and government. Contractors are not required to furnish drawings of commercial inspection equipment but a list of such equipment must be approved by the Government. Lists shall be submitted for approval to the inspection element of the agency administering the contract.

6.3.6 *Contractor designs.* Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Contractor designs identified as CDCF may be developed on the format the contractor

Source: https://assist.dla.mil -- Downloaded: 202640-22T03:07Z
Check the source to verify that this is the current version before use.

normally employs in his equipment design procedure provided such format reflects the detail and information specified above. Contractor designs identified as CDOF shall comply with the format and requirements of ORDM 608-12, and, in addition, contain the detail and information specified above.

6.3.7 *Submission of contractor designs.* Designs shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-ND. Design review will normally be accomplished within one month after receipt by Picatinny Arsenal. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs.

6.4 **Submission of Initial Production Sample.** Instructions, as to the location for the evaluation of the initial production sample shall be obtained from the contracting officer. Upon receipt of such request, the contracting officer shall advise Picatinny Arsenal and instructions will be issued accordingly. All inquiries should be forwarded to: Commanding Officer, Picatinny Arsenal ATTN: SMUPA-NI.

Custodian:

Army—MU

Preparing activity:

Army—MU

Project No. 1340–A099

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:07Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:07Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:07Z
Check the source to verify that this is the current version before use.