MIL-C-45468E(AR)
13 January 1986
SUPERSEDING
MIL-C-45468D(PA)
10 November 1982

MILITARY SPECIFICATION

CAP, BLASTING, ELECTRIC: M6
PARTS FOR, AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for one type of blasting cap designated as Blasting Cap, Electric: M6.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

FEDERAL

W-B-411	-	Blasting-Machine; Galvanometer, Blasting, Resistor Assembly.
QQ-L-201	-	Lead, Sheet.
PPP-F-320	-	Fiberboard, Corrugated and Solid Sheet Stock (Container Grade), and Cut Shapes
PPP-B-566	-	Boxes, Folding, Paperboard.
PPP-C-1120	-	Cushioning Material, Uncompressed Bound Fiber For Packaging
PPP-C-1797	-	Cushioning Material, Resilient, Low Density Unicellar, Polypropylene Foam

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116	-	Preservation, Method of.
MIL-B-117	-	Bag, Interior Packaging.
MIL-B-48024	-	Box, Ammunition Packing, Wood, (W/Plywood Top and Bottom) Nailed
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes (ABC-STD-105).
MIL-STD-129	-	Marking For Shipment and Storage

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

2128218	-	Package, Shipping and Storage (For 24 Cap, Blasting, Electric, M6).
3139685	-	Pack, Shipping and Storage (For 96 Cap, Blasting, Electric, M6).
8796522	-	Marking Diagram and Sealing for Wood Packing Boxes.
8830972	-	Cap, Blasting, Electric, M6 Assembly.

(Copies of specifications, standards, drawings, publications required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and parts. Materials and parts shall be in accordance with applicable drawings, specifications and standards.

3.2 Assemblies. The assemblies shall comply with all requirements specified on Drawing (Dwg.) 8830972 all associated drawings, and with all requirements specified in applicable specifications and standards.

3.3 Moisture content of the lead azide. The moisture content of the lead azide at the loading station, at the time of loading the blasting cap assemblies, shall not exceed 0.50 percent.

3.4 Waterproofness. The blasting cap assemblies shall function satisfactorily as evidenced by perforation of lead discs after submersion in water for not less than 4 hours at 70 degrees plus or minus 5 degrees Fahrenheit (^{O}F.) and the water is under a pressure of 50 plus 0.50 pounds per square inch (gauge).

3.5 Functioning. The blasting cap assembly shall fire when a electric current of not more than 0.45 amperes is applied.

3.6 Non-functioning. The blasting cap assembly shall not fire when an electric current, of not less than 0.2 amperes is applied for not less than 5 seconds.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner. They shall be free of burrs, sharp edges, cracks, dirt, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:05Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantity
(a) Inert Component	See Table I	35
(b) Inert Assembly	See Table I	35
(c) Loaded Blasting Cap Assemblies	See Table I	190

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any item fails to comply with any of the applicable requirements. the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-C-45468E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Cap Blasting, Electric, M6				See Below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Assembly (Dwg. 8830972)				
	Examination for Defects	190		3.2	4.4.2.7
	Non-Functioning	190(a)		3.6	4.5.4
	Waterproofness (output)	30(b)			4.5.2.1/4.4.3.2
	Waterproofness (series)	80(c)			4.5.2.2/4.4.3.2
	Functioning	80(d)		3.5	4.5.3/4.4.3.2
NOTES:	(a) This test shall be performed on the same samples subjected to examination for defects.				
	(b) 30 Samples shall be selected from the same samples subjected to examination for defects.				
	(c) 80 Samples shall be selected from the same samples subjected to examination for defects.				
	(d) The remaining 80 samples shall be subjected to the function test.				

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each lot shall contain:

a. Parts of one lot interfix number from one manufacturer.

b. Lead azide from not more than one lot from one manufacturer.

c. Ignition charge from not more than one lot from one manufacturer.

d. RDX from not more than one lot from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Plug Assembly (Rubber)				8830971
					NEXT HIGHER ASSEMBLY 8830972
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pull test of lead wire		0.40%	3.2	4.5.5
102	Length from bare end of lead wire to insulation max.		0.40%	3.2	Gage
103	Length of plug, min.		0.40%	3.2	Gage
104	Bridge wire improperly soldered		0.40%	3.2	Visual
105	Tension on bridge wire		0.40%	3.2	Visual
Minor					
201	Diameter of plug min.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cup				8830953
					NEXT HIGHER ASSEMBLY 8830972
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cup split or cracked		100%		Visual
Major					
101	Thickness through bottom		0.40%	3.2	Gage
10	Concavity of bottom, max.		0.40%	3.2	Gage
Minor					
201	Inside diameter, min		0.65%	3.2	Gage
202	Outside diameter, max.		0.65%	3.2	Gage
203	Length, min.		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Spool		8830954
			NEXT HIGHER ASSEMBLY 8830972

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Total length		0.65%	3.2	Gage
202	Depth of slot		0.65%	3.2	Gage
203	Width of slot, min.		0.65%	3.2	Gage
204	Outside diameter, max.		0.65%	3.2	Gage
205	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.4	Assembly, Prior to Inserting in Spool	1 OF 1	8830972
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Resistance of bridge wire and wire leads		100%	3.2	4.5.6
2	Lead wires not shunted		100%	3.2	Visual
3	Cup split or cracked		100%	3.2	Visual
Major					
101	Length of cup, max.		0.40%	3.2	Gage
102	Diameter of cup, crimp end, max.		0.40%	3.2	Gage
103	Insulation on lead wires damaged		0.40%	3.2	Visual
104	Not crimped 360° (4 places)		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Assembly				8830972
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Non-functioning		100%	3.6	4.5.4
2	Functioning	4.4.3	.2	3.5	4.5.3
3	Evidence of explosive leakage		100%	3.2	Visual
Major					
101	Insulation on wires damaged		0.40%	3.2	Visual
102	Spool cracked or broken		0.40%	3.2	Visual
Minor					
201	Wires improperly wrapped on spool		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Unit Carton, Prior to Insertion in Bag		--
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Marking misleading or unidentifiable		0.40%	3.2	Visual
Minor 201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Intermediate Package, Prior to Closing Fiberboard Box		--
			NEXT HIGHER ASSEMBLY
			--

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Heat seal of waterproof bag incomplete		0.40%		Visual/Manual
102	Bag punctured, cut, or torn		0.40%		Visual
103	Marking of bags misleading or unidentifiable		0.40%	3.2	Visual
Minor					
201	Number of unit packs incorrect		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Intermediate Package		--
			NEXT HIGHER ASSEMBLY
			--

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Container damaged		0.40%	5.1.1.2	Visual
102	Container not sealed		0.40%	5.1.1.2	Visual
103	Marking misleading or unidentifiable		0.40%	5.3	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Box, Wood, Prior to Closing		--
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Box liner material improper		0.40%	5.2.1	Visual
102	Liner not sealed		0.40%	5.2.1	Visual
103	Liner perforated		0.40%	5.2.1	Visual
Minor					
201	Number of intermediate packages incorrect		0.65%	5.2.1	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Box, Wood				--
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Top improperly assembled		0.40%	5.2.1	Visual
102	Strapping missing, broken or loose		0.40%	5.2.1	Visual/Manual
103	Board broken or split		0.40%	5.2.1	Visual
104	Box damaged so that contents are exposed or liable to become exposed		0.40%	5.2.1	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Package, Shipping and Storage, prior to closing				2128218
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any packing component missing or improperly assembled		0.40%	3.2	Visual
Minor					
201	Number of desiccant units incorrect		0.65%	3.2	Visual
202	Desiccant bags not secured properly		0.65%	3.2	Visual
203	Indicator card missing		0.65%	3.2	Visual
204	Number of inner packages incorrect		0.65%	3.2	Visual
205	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45468E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Package, Shipping and Storage				2128218
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	CFR Markings missing or unidentifiable		100%	3.2	Visual
Major 101	Fiberboard interferes with seal of lid		0.40%		Visual
Minor 201	Descriptive marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4 4.2.13	Pack, Shipping and Storage prior to				3139685
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Package missing or positioned improperly		0.40%	3.2	Visual
Minor 201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.14	Pack, Shipping and Storage				3139685
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	CFR markings missing or unidentifiable		100%	3.2	Visual
Major					
101	Wire binding not properly secured		0.40%	---	Visual
102	Car seal missing		0.40%	---	Visual
Minor					
201	Descriptive marking missing, misleading or unidentifiable		0.65%	---	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:05Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.3.1 Moisture content of lead azide (see 3.3). Major Defect. The moisture content of the lead azide shall be determined for each lot at the time of loading. A sample of 2 grams shall be selected and tested as specified in 4.5.1. If the moisture content is in excess of the percentage specified and loading has not begun, the lot of lead azide shall be rejected until proper corrective action has been accomplished as verified by performing the moisture content test specified in 4.5.1. If loading has begun, action on the unloaded lead azide shall be as specified above and all detonators loaded with the questionable lead azide shall be rejected.

4.4.3.2 Functioning and waterproofness. One hundred and ninety (190) blasting cap assemblies shall be selected from each lot for test. The number of samples allotted for each test is specified as follows:

Test	Classification	No. of Samples	Test Para.
Waterproofness (see 3.4)			
(a) Output	Major	30	4.5.2
(b) Series	Major	80	4.5.2
Functioning (see 3.5)	Major	See Note 1 80 (less output duds)	4.5.3

Note 1 - Duds that occur in the "output" phase of testing shall be recorded and replaced from this sample. The lot shall be rejected if a total of three (3) or more blasting cap assemblies fail to fire out of the total sample tested.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (See 4.5). The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.4.5 Warning. This specification contains sampling procedures and tests which involve materiel potentially hazardous to personnel. It is emphasized that all applicable safety rules, procedures and regulatory requirements be strictly followed during the handling, processing and testing of these blasting caps. Hazardous component safety data sheets contained in the technical data package contain specific safety-related information.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Determination of moisture content of lead azide. A tared, dried, aluminum dish, 2 inches in diameter shall be covered with a sheet of polytetrafluoroethylene 2 1/2 inches square, and sufficiently flat to form a tight cover. An accurately weighed portion of approximately two grams of the sample shall be transferred to an oven and dried at 95 degrees C. plus or minus 2 degrees C. for 2 hours. The cover shall be placed in the sulfuric acid desiccator during the drying period. After drying, the dish shall be quickly transferred to the desiccator and allowed to cool to room temperature. The polytetrafluoroethylene cover shall be placed on the dish and the assembly weighed. The loss in weight shall be calculated to percentage of moisture in the lead azide to determine compliance with 3.3 as follows:

$$\text{Percentage of moisture} = \frac{100\ A}{B}$$

Where:
A = loss in weight, gm
B = weight of original sample, gm.

4.5.2 Waterproofness.

4.5.2.1 Output. The cap assemblies shall be completely immersed in water for 4 hours at a temperature of 70 degrees plus or minus 5 degrees F., and a pressure of 50 plus 0.50 pounds per square inch gauge. Immediately upon removal from the water, thirty of the sample caps shall be subjected to the following static functioning test: The lead discs used in this test shall be made of 8 pound sheet lead complying with Specification QQ-L-201, Grade B, and shall be 0.1345 inch min. thickness and 1.22 - .01 inch in diameter. The disc shall be centered over a 15/16 inch diameter hole in a metal support. The cap shall be suitably fixed in an upright position, with its bottom resting on the unsupported section of the lead disc. The cap shall be fired with an electric current of 0.45 amperes. Observation shall be made for complete detonation of the cap as evidenced by the perforation of the lead disc.

4.5.2.2 Series. The eighty blasting cap assemblies shall be either connected in series and an electric current of 1.5 amperes, maximum, applied to the circuit, for a period not exceeding 50 milliseconds, or, the eighty caps shall be connected in series, in groups of 10 each, and fired with a 10-cap capacity blasting machine complying with Specification W-B-411, Type 1, Class A, through a total resistance of 32 ohms. Observation shall be made for evidence of complete detonation of the caps to determine compliance with the requirements.

4.5.3 Functioning. The blasting cap shall be assembled to the applicable test fixture specified in 4.4.4. An electric current of 0.45 amperes shall be applied to each cap. Any assembly which fails to comply with the specified requirement shall be classed defective.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.5.4 Non-functioning. The blasting cap shall be assembled to the applicable test fixture specified in 4.4.4. An electric current of 0.20 ampere shall be applied singularly to each cap for a period of 5 seconds. Observation shall be made for non-functioning of the assembly to determine compliance with the specified requirement.

4.5.5 Pull test of lead wires. The plug assembly shall be assembled to the applicable test equipment specified in 4.4.4 and the specified load applied. Any plug assembly that shows evidence of slippage of either lead wire within the plug shall be classed defective and removed from the lot.

4.5.6 Resistance of bridge wire and wire leads. The blasting cap shall be assembled to the applicable test equipment specified in 4.4.4. The electrical resistance of the cap, including the leads, shall be measured as specified using a test current not to exceed 20 milliamperes. Any assembly which fails to comply with the applicable requirement shall be classed defective and removed from the lot.

5 PACKAGING

5.1 Preservation and packing.

5.1.1 Level A.

5.1.1.1 Option A. NSN: 1375-01-192-9174 M130.

5.1.1.1.1 Unit package. Place ten (10) blasting cap assemblies in a 5 x 2 pattern into a folding paperboard carton (size 1.2 inch by 3.4 inch by 5.2 inch) conforming to PPP-B-566, Style II, Type A, Class A. The minimum paperboard thickness shall be .020 inch. Add chipboard fillers as required to obtain a tight pack. The box shall be closed by applying a strip of tape, one-inch wide by two inches long across the top and bottom of the carton. Each carton shall be placed in a barrier bag MIL-B-117, Type I or II, Class E (approximate size 5 inch by 10.5 inch) and closed by exhausting all excess air and heat sealing the bag to comply with the requirements of MIL-P-116.

5.1.1.1.2 Intermediate package. Place nine (9) bagged unit packs (90 assemblies) in a 3 x 3 x 1 pattern in a M2A1 metal box lined with cushioning 3/4 inch thick, PPP-C-1120, Type II, Class B. Add filler material PPP-F-320 to side, end fillers and top pad as required to obtain a tight pack. Close and seal metal box.

Source: https://assist.dla.mil -- Downloaded: 20260-22T03:05Z
Check the source to verify that this is the current version before use.

5.1.1.1.3 Exterior package. Place two M2A1 metal boxes (180 assemblies) in a wooden box (MIL-B-48024, Type 2, Class 2, Grade A, Size 14.50 inch by 14.5 inch by 9.75 inch I.D.). Line the box with 1 inch thick (minimum) polypropylene (PPP-C-1797, Type 1 material or equal) between the metal boxes and the exterior wooden box. Place a fiberboard separator (PPP-F-320, com. gd. size 11.5 inch by 7.0 inch) between the metal boxes. Close box in accordance with the instructions contained in the appendix of the box specification.

5.2 Marking. Marking will be in accordance with MIL-STD-129 and Drawing No. 8796522 except that all letters shall be upper case with 1/8 inch (minimum) letter heights for unit pack, 1/4 inch height for intermediate pack and barrier bags. Marking shall be applied to cartons by means of labeling, printing, or stamping. Labels will not be applied to bags, metal boxes, or wooden boxes.

5.2.1 Level A.

5.2.1.1 Option A. NSN 1375-01-192-9174 M130.

5.2.1.1.1 Unit package. Each unit carton and barrier bag shall be marked as follows: 1375-M130, 10-Caps, Blasting Electric, M6, Lot No. _____.

5.2.1.1.2 Intermediate package. Each M2A1 metal box shall be marked on one side as follows: NSN: 1375-01-192-9174 M130, 90-Caps, Blasting Electric, M6 Lot No._____.

5.2.1.1.3 Exterior package. Exterior package shall be marked in accordance with Drawing No. 8796522. The descriptive nomenclature will be "180-Caps, Blasting Electric, M6. C.O.E. CCN AY-84-041 applies and must be annotated on all shipping papers. Mark MIL-C-45468 on bottom of exterior package. The DOT proper shipping name shall be "Detonators - Handle Carefully" and shall require a class A Explosive label.

6. NOTES

6.1 Ordering data. See MIL-A-48078. For Marine Corps packing, packaging and marking, see 5.1.3, 5.2.3, and 5.3.1 of this specification.

6.2 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: US ARDC, ATTN: AMSMC-QAT-M(D), Dover, NJ 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:05Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, US ARDC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraph number.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDC.

6.5 International standardization agreement. Certain provisions of this specification, sections 3, 4, and 5, are the subject of international standardization agreement STANAG 2817. When amendment, revision, or cancellation of this specification is proposed which affects or violates the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices, if required.

6.6 Check test for possible deterioration of blasting caps. The following test is designed to prevent blasting caps that have deteriorated from being assembled into major ammunition items. The test shall be performed on blasting caps from each lot which have been stored under normal conditions for more than two (2) years or under adverse conditions for any period of time. If the specification for the ammunition item into which blasting caps are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check tests for possible deterioration. Blasting caps shall be selected from each lot and tested as per 6.6.1.

6.6.1 Functioning. Eighty (80) blasting cap assemblies shall be selected from each lot and subjected to the functioning test as specified in 4.5.3. The lot shall be rejected if two (2) or more blasting caps fail to comply with the functioning requirements specified in 3.5. Test equipment shall be as specified in 4.4.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

6.7 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A309)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-45468E(AR)	CAP, BLASTING, ELECTRIC: M6 PARTS FOR, AND LOADING, ASSY & PACK

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.