INCH-POUND
MIL-C-45468E(AR)
AMENDMENT 1
19 August 1996

MILITARY SPECIFICATION

CAP, BLASTING, ELECTRIC: M6
PARTS FOR, AND LOADING, ASSEMBLING AND PACKING

This amendment forms a part of MIL-C-45468E (AR), dated 13 January 1986, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 2

2.1.2, DRAWINGS:

Add new drawing as follows:

"7553296 - Box Ammo M2A1"

Delete drawings 2128218 and 3139685.

PAGE 5

TABLE I, Assembly (Dwg. 8830972), Examination for Defects: Delete "4.4.2.7" and substitute "4.4.2.4" under PARAGRAPH REFERENCE/INSPECTION METHOD.

PAGE 11

4.4.2.5:

Critical 2: Delete in its entirety.

Add new Major 103 as follows:

"103 Waterproofness and functioning 4.4.3.2 3.4/3.5 4.5.2/4.5.3"



AMSC N/A FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

PAGE 23 and 24

Section 5, delete in its entirety and substitute the following:

"5 PACKAGING

5.1 Preservation and packing.

5.1.1 Level A.

5.1.1.1 Option A. NSN: 1375-01-192-9174-M130.

5.1.1.1.1 Unit package. Place ten (10) blasting cap assemblies in a 5 x 2 pattern into a folding paperboard carton (size 1.2 inches by 3.4 inches by 5.2 inches) conforming to PPP-B-566, Variety I, Style II, Type D, Class A. The minimum paperboard thickness shall be 0.20 inch. Add chipboard fillers as required to obtain a tight pack. The box shall be closed by applying a strip of tape, conforming to UU-T-106, one inch wide by two inches long across the top and bottom of the carton. Each carton shall be placed in a barrier bag MIL-B-117, Type I or II, Class F (approximately size 5 inches by 10.5 inches) and closed by exhausting all excess air and heat sealing the bag to comply with the requirements of MIL-P-116.

5.1.1.1.2 Intermediate package. Place nine (9) bagged unit packs (90 assemblies) in a 3 x 3 x 1 pattern in a M2A1 metal box with top and bottom pads of 3/4 inch thick cushioning, PPP-C-1120, type II, Class B. Add filler material conforming to PPP-F-320 to side, end and top as required to obtain a tight pack. Close and seal metal box.

5.1.1.1.3 Exterior package. Place two (2) M2A1 metal boxes (180 assemblies) in a wooden box (MIL-B-2427, Type 2, Class 2, Grade A, Size 14.5 x 14.5 x 9.75 inches I.D.). An alternate plywood top and bottom (see 5.1.1.1.3.1) may be used with a 1/2 inch thick top and 3/8 inch thick bottom using hardware fasteners of MS 35692-28 or MS 35494-32 or equivalent. Line the box with 1 inch thick (minimum) polypropylene (PPP-C-1797, Type 4, or equivalent) between the exterior wood box and the metal boxes. Place a fiberboard separator (PPP-F-320, Commercial Grade, Size 11.5 x 2.0 inches) between the metal boxes. Close box in accordance with the instructions contained in the appendix of the box specified.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5.1.1.1.3.1 Plywood. Group B or C, container grade standard interior with exterior glue shall be used. If specified grade is not available, a better exterior grade may be substituted.

5.1.1.1.3.1.1 Grade A, B and C Boxes. Top and bottom panels. Plywood utilized for top and bottom panels shall meet the standard requirements outlined in Department of Commerce Publication PS-1 for Group B plywoods and CS-157 for Group C plywoods after cutting to size.

5.1.1.2 Option B. NSN: 1375-00-283-9442-M130

5.1.1.2.1 Unit Package. Six (6) blasting cap assemblies, affixed to individual spools, shall be packaged in a folding paperboard box conforming to Variety I, Style II, Type A, Class A, of PPP-B-566. The minimum paperboard thickness shall be 0.20 inch. The box shall be closed by applying a strip of tape conforming to UU-T-106, 1 inch wide by 2 inch long, across the top and bottom flap of the carton. Each sealed box shall be inserted into a barrier bag meeting the requirements of MIL-B-117, Type I or II, Class F. The bag shall be closed by exhausting all excess air from the bag and heat sealing the bag opening. Heat seals shall comply with the test requirements specified in MIL-P-116.

5.1.1.2.2 Intermediate package. Pack four (4) unit packaging in M19A1 metal box in accordance with Drawing 21282178.

5.1.1.2.3 Exterior package. Pack four (4) M19A1 metal boxes in wirebound box in accordance with Drawing 3139685.

5.1.1.3 Option C. NSN: 1375-01-316-1229-M130.

5.1.1.3.1 Packaging.

5.1.1.3.1.1 Level A. Level A packaging shall be in accordance with Drawing 12913870.

5.1.1.3.1.2 Level B. Level B packaging shall be the same as Level A.

5.1.1.3.1.3 Level C. Level C packaging shall be the same as Level A.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5.1.1.3.2 Packing.

5.1.1.3.2.1 Level A. Level A packing shall be in accordance with Drawing 12913871.

5.1.1.3.2.2 Level B. Level B packing shall be the same as Level A.

5.1.1.3.2.3 Level C. Level C packing shall be the same as Level A.

5.1.1.4 Option D. NSN

5.1.1.4.1 For Non-tactical Level B shipments of ten (10) blasting caps, the packaging shall be in accordance with Drawing 12934701, and the packing shall be in accordance with Drawing 12934702.

5.2 Marking.

5.2.1 Level A.

5.2.1.1 Option A. NSN: 1375-01-192-9174-M130.

5.2.1.1.1 Unit package. Each unit carton and barrier bag shall be marked as follows: 1375-M130, 10-Caps, Blasting Electric, M6, Lot No.

5.2.1.1.2 Intermediate package. Each M2A1 metal box shall be marked on one side as follows: 1375-01-192-9174-M130, 90-Caps, Blasting Electric, M6, Lot No.

5.2.1.1.3 Exterior package. Exterior package shall be marked in accordance with Drawing No. 8796522. The descriptive nomenclature will be "180-Caps, Blasting Electric, M6". Mark MIL-C-45468 on bottom of exterior package. The proper shipping name and identification number shall be "DETONATORS, ELECTRIC UN 0030" and shall require a Class A Explosive label. Mark UN POP marking on the opposite side of the box as the descriptive nomenclature as follows:

4C1/Y*/S/**
USA/DOD/AYD

at * enter the gross weight when packed in kilograms, rounded up to the next whole number, and at ** enter the last two digits of the year packed.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5.2.1.2 Option B. NSN: 1375-00-283-9442-M130.

5.2.1.2.1 Unit package. Each unit package shall be marked as follows:

6 - CAPS, BLASTING, ELECTRIC, M6

Lot No.

5.2.1.2.2 Intermediate package. Intermediate package shall be marked in accordance with Drawing 2128218. Descriptive nomenclature shall be:

24 - CAPS, BLASTING, ELECTRIC, M6

5.2.1.2.3 Exterior package. Exterior package shall be marked in accordance with Drawing 3139685. The proper shipping name and identification number shall be:

DETONATORS, ELECTRIC UN 0030

and descriptive nomenclature shall be "96 - CAPS, BLASTING, ELECTRIC, M6". The CNN must be shown on all transportation and shipping documents. Mark UN POP marking on the opposite of the box as the descriptive nomenclature as follows:

4C1/Y*/S/**
USA/DOD/AYD

at * enter the gross weight when packed in kilograms, rounded up to the next whole number, and at ** enter the last two digits of the year packed.

5.2.1.3 Option C. NSN: 1375-01-316-1229-M130.

5.2.1.3.1 Level A. Level A marking shall be in accordance with Drawings 12913870 and 12913871.

5.2.1.3.2 Level B. Level B marking shall be the same as Level A.

5.2.1.3.3 Level C. Level C marking shall be the same as Level A.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5.2.1.4 Option D. NSN:

5.2.1.4.1 Marking for Level B Non-tactical shipments of ten (10) blasting caps shall be in accordance with Drawings 12934701 and 12934702."

PAGE 24

6.1: Delete in its entirety.

PAGE 24 thru 26

Delete paragraph numbers 6.2 thru 6.7 and renumber with paragraph numbers 6.1 thru 6.6.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-0036)



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.