MILITARY SPECIFICATION

CAP, BLASTING, NON-ELECTRIC: M7. LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for one type of Blasting Cap designated as Blasting Cap, Non-Electric: M7. (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

FEDERAL

QQ-L-201	-	Lead Sheet.
UU-C-282	-	Chipboard
PPP-B-566	-	Boxes, Folding, Paper Board.
PPP-B-621	-	Box, Wood, Nailed and Lock-corner
PPP-B-636	-	Boxes, Fiber.
PPP-C-1120	-	Cushion Material, Uncompressed Board Fiber for Packing.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.
Source: https://assist.dla.mil -- Downloaded: 2026-10-22 03:06Z
Check the source to verify that this is the current version before use.

PPP-C-1797-		Cushioning Material, Resilient, Low Density, Unicellular, Polypropolene, Foam.
PPP-F-320	-	Fiberboard, Corrugated and Solid, Sheet Stock (Container grade) and cut

MILITARY

MIL-P-116	-	Preservation, Method of.
MIL-B-117	-	Bags, Interior Packaging.
MIL-C-43438	-	Crimper, Blasting Cap, M2, Plier Type w/fuse Cutter.
MIL-F-45144	-	Fuse, Blasting, Time, M700, Loading, Assembling and Packing.
MIL-B-48024	-	Box, Ammunition Packing, Wood, (W/plywood Top and Bottom) Nailed
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	-	Marking For Shipment and Storage
MIL-STD-650	-	Explosives Sampling, Inspection and Testing.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT CENTER (ARDC)

2128217	-	Inner Package.
2128219	-	Package, Shipping and Storage (For 192 Cap, Blasting, Non-Electric, M7).
3139687	-	Pack, Shipping and Storage (For 768 Cap, Blasting, Non-Electric, M7).
8796522	-	Marking Diagram and Sealing Wood Packing Boxes.
8830948	-	Cap Blasting, Non-Electric, M7 Assembly.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the currentversion before use.

(Copies of specifications, standards, drawings and publications required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the test of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials and parts shall be in accordance with the applicable drawings, specifications and standards.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (Dwg.) 8830948, and with all requirements specified in applicable specifications and standards.

3.3 Moisture content of the lead azide. The moisture content of the lead azide at the loading station, at the time of loading the blasting caps shall not exceed 0.50 percent when tested as specified in 4.5.1.

3.4 Impact resistance. The cap shall not detonate, the cup shall not crack or break, or the charge loosen or drop out during impact testing when tested as specified in 4.5.2.

3.5 Output functioning after impact test. The caps shall detonate completely as evidenced by the perforation of the lead discs when tested as specified in 4.5.3.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and loaded in a thorough, workmanlike manner; and all manufacturing, processing, and assembling operations shall be correctly performed. They shall be clean and free of burrs, sharp edges, unblended radii, cracks, gouges, surface defects, chips, dirt, grease, and oil (except where specifically required), corrosion, and other foreign matter. The cleaning method shall not be injurious to any of the parts or assembly nor shall they be contaminated by the cleaning

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the currentversion before use.

agents. Exterior surface coating shall be continuous except for a few light scratches not exposing base material. All required markings and stamping shall be neat and sharply defined. Required packing shall be dry.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsiblity for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of twenty-five (25) cups and 125 loaded assemblies.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Cap, Blasting, Non-Electric, M7				See Below
					NEXT HIGHER ASSEMBLY
					See Below
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup (Dwg. 8830949)				
	Examination for Defects	25		3.2	4.4.2.1
	Loaded assemblies (Dwg. 8830948)				
	Examination for Defects	25(a)		3.2	4.4.2.2
	Impact resistance	125		3.4	4.5.2
	Output functioning	125(b)		3.5	4.5.3

NOTES: (a) Taken randomly from the 125 loaded assemblies and returned after inspection.
(b) Same 125 used for impact resistance. If any assembly fails to comply with the specified requirements, it shall be classed defective and the sample shall be rejected.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of caps shall contain:

a. Cups from one supplier.

b. RDX from not more than one lot.

c. Lead styphnate from not more than one lot.

d. Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant.

e. Certificates of findings (certificates of analysis) on all charge powders and the ignition mix and certificates of conformance on all remaining materials purchased by the contractor when such material is controlled by Government or commerical specifications referenced in any of the contractual documents.

4.4.2 Examination. (See MIL-A-48078). Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.1	Cup		8830949
			NEXT HIGHER ASSEMBLY 8830948

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter below datum diameter at mouth, maximum (max)		0.40%	3.2	Gage
102	Thickness of bottom, minimum (min)		0.40%	3.2	Gage
Minor					
201	Length to datum diameter at mouth		0.65%	3.2	Gage
202	Inside diameter near bottom		0.65%	3.2	Gage
203	Poor workmanship		1.00%	3.7	Visual

NOTICE:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Assembly		8830948
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Cup split or cracked exposing charge or evidence of explosive leakage		100%	3.2	Visual
2	Loose powder on inner or outer wall of cup		100%	3.2	Visual
Major					
101	Depth to charge, min.		0.40%	3.2	Gage
102	Overall length, max.		0.40%	3.2	Gage
Minor					
201	Outside diameter at open end, max.		0.65%	3.2	Gage
202	Outside diameter at closed end, max.		0.65%	3.2	Gage
203	Poor workmanship except as defined in critical above.		1.00%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Unit Carton (prior to insertion in bag)				See 5.1.1.1
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Box damaged exposing contents		0.65%	3.2	Visual
202	Separator missing or damaged to extent that caps touch		0.65%	3.2	Visual
203	Marking missing, incorrect or illegible		0.65%	3.2	Visual
204	Number of caps incorrect		0.65%	3.2	Visual
205	Poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH 4.4.2.4	TITLE Sealed Packed Barrier Bag (prior to insertion into box)		SHEET 1 OF 1		DRAWING NUMBER See 5.1.1.2 (when applicable NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Waterproofness of barrier bag destroyed by rupture, puncture, or separation of heat seal		0.40%	3.2	Visual
102	Crushed carton		0.40%	3.2	Visual (Note (a))
Minor					
201	Heat seal of barrier bag located so that one or more subsequent seals cannot be applied		0.65%	3.2	Visual
202	Marking of bag misleading or unidentifiable		0.65%	3.2	Visual
203	Poor workmanship		1.00%	3.7	Visual

NOTES: (a) Package should be opened if there is evidence of crushing.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Intermediate Package				See 5.1.1.2 & 5.1.2.2
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Number of unit packages incorrect		0.65%	3.2	Visual
202	Marking missing, incorrect or illegible		0.65%	3.2	Visual
203	Poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Wooden Box (prior to sealing)				See 5.2.1 & 5.2.2
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Liner missing or unsealed (when applicable)		0.40%	3.2	Visual
102	Liner damaged to extent that function is impaired (when applicable)		0.40%	3.2	Visual
Minor					
201	Cushioning material not dry		0.65%	3.2	Manual
202	Number of intermediate packages incorrect		0.65%	3.2	Visual
203	Poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Wooden Box (sealed)				See 5.2.1 & 5.2.2
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Strapping missing, broken or loose		0.40%	3.2	Visual/Manual
102	Top improperly assembled		0.40%	3.2	Visual
103	Board broken or split		0.40%	3.2	Visual
104	Box damaged so that contents are exposed or liable to become exposed		0.40%	3.2	Visual
Minor					
201	Contents loose when box is tilted		0.65%	3.2	Manual
202	Strapping improperly assembled		0.65%	3.2	Visual
203	Marking misleading or unidentifiable		0.65%	3.2	Visual
204	Poor workmanship		1.00%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026/0-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Package, Shipping and Storage (prior to closing)				2128219
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any packing component missing or misassembled		0.40%	3.2	Visual
Minor					
201	Number of inner packages incorrect		0.65%	3.2	Visual
202	Number of desiccant units incorrect		0.65%	3.2	Visual
203	Indicator card missing		0.65%	3.2	Visual
204	Poor workmanship		1.00%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Package, Shipping and Storage				2128219
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	*CFR marking missing or unidentifiable		100%	3.2	Visual
Major					
101	Packing or cushioning material interferes with seal of lid		0.40%	3.2	Visual
Minor					
201	Descriptive marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.7	Visual

NOTES: *Code of Federal Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026/10-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Pack, Shipping, and Storage, prior to closing	1 OF 1	3139687
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Package missing or improperly positioned		0.40%	3.2	Visual
Minor	None defined				

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-C-45469E(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Pack, Shipping and Storage		3139687
			NEXT HIGHER ASSEMBLY --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	CFR markings missing or unidentifiable		100%	3.2	Visual
Major 101	Wire binding not properly secured		0.40%	3.2	Visual
102	Metallic seal missing		0.40%	3.2	Visual
Minor 201	Descriptive marking missing, misleading or unidentifiable		0.65%	3.2	Visual
202	Poor workmanship		1.00%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T03:06Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Moisture content of lead azide (see 3.3). Major defect. - The contractor shall provide adequate controls to insure that the lead azide complies with the requirement. For verification, the contractor shall select and test a sample from that quantity of lead azide used in each eight hours of loading production. A composite sample shall not be used. If the moisture content of a sample exceeds the requirement and loading has not begun, the lead azide represented by the sample shall be rejected. If components have been loaded with lead azide containing excessive moisture, the remaining unloaded lead azide and the loaded components shall be rejected. The test procedure shall be as specified in 4.5.1.

4.4.3.2 Impact resistance (see 3.4 and Table II).

TABLE II Impact Resistance Defects

	Defect	Classification
(a)	Blasting cap functions on impact	Critical
(b)	Crack or split in cup (charge not exposed)	Major
(c)	Loose or dislodged charge	Major
(d)	Blasting cap fails to perforate lead disc	Major
(e)	Blasting cap fails to fire	Major

4.4.3.2.1 Beginning with the first lot produced and continuing until three (3) consecutive lots have complied with the specified requirements, one hundred and twenty-five (125) blasting caps shall be selected from each lot for test. The lot shall be rejected if a critical defect occurs or if three or more assemblies exhibit a (b) or (c) major defect listed in Table II. The test shall be performed as specified in 4.5.2 using equipment in accordance with 4.4.4. Following this test, the Functioning after Impact Test shall be performed as specified in 4.4.3.3.1.

4.4.3.2.2 After three (3) consecutive lots have been accepted in accordance with the criteria of 4.4.3.2.1 and 4.4.3.3.1, a sample of fifty (50) blasting caps shall be selected from each lot for test. The lot shall be rejected if a critical defect occurs or if two (2) or more assemblies exhibit (b) or (c) major defectives (see Table II). The test shall be performed as specified in 4.5.2 using equipment in accordance with 4.4.4. Following this test, the Functioning after Impact Test shall be performed as specified in 4.4.3.3.2.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the currentversion before use.

4.4.3.3 Functioning after impact test (see 3.5 and Table II).

4.4.3.3.1 The blasting caps selected for the test specified in 4.4.3.2.1 shall be used for this test. The lot shall be rejected if the total number of major defectives (see Table II) found in the two tests (d and e) is three (3) or more. The test shall be performed as specified in 4.5.3.

4.4.3.3.2 The blasting caps selected for the test specified in 4.4.3.2.2 shall be used for this test. The lot shall be rejected if the total number of major defectives (see Table II) found in the two tests (d and e) is two (2) or more. The test shall be performed as specified in 4.5.3.

4.4.4 Inspection equipment. The inspection equipment required to perform the inspections and tests prescribed in this specification is identified in the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1, and the test method paragraph (see 4.5). The contractor shall submit for approval, inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.4.5 Warning. This specification contains sampling procedures and tests which involve materiel potentially hazardous to personnel. It is emphasized that all applicable safety rules, procedures and regulatory requirements be strictly followed during the handling, processing and testing of these blasting caps. Hazardous component safety data sheets contained in the technical data package contain specific safety-related information.

4.5 Methods of inspection.

4.5.1 Moisture content of lead azide. The moisture content of the lead azide shall be determined in accordance with Method 101.5 of MIL-STD-650, except that a two-gram (gr.) sample shall be tested and the dish shall be covered with a sheet of polytetrafluoroethylene.

4.5.2 Impact resistance.

4.5.2.1 Apparatus and set-up procedures. The apparatus shall consist of the following:

a. Galvanized iron pipe. 1-9/16 inch I.D. x 7 feet long.
b. One pulley to fit the rope.
c. Rope, length to suit.
d. Anvil, steel 12 inches square x 3 inches thick, minimum.
e. Weight, cylindrical, steel, 1-3/8 inch diameter x 14 inches long, weighing 5.3 pounds approximately, with an eyelet at one end for rope attachment.
f. Plywood, dry, 3/4 inch thick x approximately 4 inches square, Spec NN-P-00530.
g. Pin, steel, 1/2 inch diameter x 3-1/2 inches long (eyelet) at one end.
h. Clamps (as required).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.

Erect the galvanized iron pipe so that its axial center is perpendicular to the center of the 12 inch square surface of the anvil and the bottom of the pipe is 3-1/2 inches above the anvil. Drill two 9/16 inch diameter holes in the pipe diametrically opposite each other at a height of 48-3/4 inches above the anvil. Place the 4 inch square piece of plywood on the anvil so that the centers of the anvil and plywood are common. Securely clamp the plywood to the steel anvil in two places minimum, diametrically opposite each other. If the plywood is not replaced after each item tested, not more than ten (10) drops shall be made in the same spot. Drill a 9/32 inch diameter hole 2 inches deep in the eyelet end of the cylindrical steel weight. The hole shall be located so that the eyelet does not interfere with insertion and removal of the blasting caps. Attach a piece of rope (length to suit) to the eyelet in the steel pin and insert the pin in the 9/16 inch hole in the pipe. Locate the other end of the rope behind a suitable barricade. Attach a rope approximately 15 feet long to the eyelet in the cylindrical steel weight and lower the weight into the pipe until it rests on the pin. Mount a pulley above the pipe so that when the rope is threaded through the pulley, the weight after dropping, may be withdrawn to permit insertion or removal of the blasting caps. The test anvil must be rigidly supported.

4.5.2.2 Test procedure. The blasting caps shall be tested for impact resistance in the following manner: Cover the open end of the blasting cap with tape. Insert the blasting cap, taped end first into the hole in the top of the steel weight. Tape the blasting cap to the weight to prevent it from bouncing during the test. Insert the weight in the pipe and lower it until it rests on the steel pin that is inserted in the 9/16 inch holes in the pipe. Pull the pin from behind the barricade to allow the weight to drop and impact on the plywood. Retract the weight by means of the rope, reinsert the pin, and repeat the drop procedure for a total of two (2) drops per blasting cap. After the second drop, remove the blasting cap from the weight and examine for compliance with the requirements. After the drop test, the blasting caps shall be subjected to the output functioning test specified in 4.5.3.

4.5.3 Output functioning after impact test. The lead discs used in this test shall be 1.22 minus .01 inch in diameter and 0.1345 inch thick min. complying with QQ-L-201 Grade B material. The disc shall be centered over the 15/16 inch diameter hole in the test fixture. A six (6) inch length min. of M700 safety fuse complying with MIL-F-45144 shall be inserted in the open end of the blasting cap cup to a depth to contact the explosive charge. An M2 blasting cap crimping tool complying with MIL-C-43438 shall be used to crimp the safety fuse in the cup. The blasting cap complete with safety fuze shall be fixed in an upright position so that the base of the blasting cap is in contact with the center of the lead disc. The blasting cap shall be fired and observed for complete detonation and the lead disc perforation size.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Option A. NSN: (SPI/TPO) 1375-01-057-6439 M131.

5.1.1.1.1 Unit package. Place ten (10) caps in a folding box conforming to PPP-B-566 (size 1 7/8 inch by 3/4 inch by 2 1/2 inch). The caps shall be separated in 5 x 2 pattern using half slotted die-cut or folded inserts that provide individual cells made from chipboard, conforming to UU-C-282 or equal. Enclose each box (10 caps) in a barrier bag conforming to MIL-B-117, Style I, Type I, class F (size 3 x 6). Remove air and heat seal in accordance with MIL-P-116.

5.1.1.1.2 Intermediate packaging. Place five (5) unit packs (bags) in a waterproof bag conforming to MIL-B-117, Style 2, Type 1, class B or equal. Exhaust all air and heat seal in accordance with MIL-P-116.

5.1.1.1.3 Exterior package. Place two bags (100 caps) into a fiberboard box (PPP-B-636 VC3 Size 8 x 8 x 14 inches I.D.). Cushion between the intermediate pack and exterior fiberboard box with one inch thick (minimum) polypropylene Type 1, PPP-C-1797 or equal material. Place fiber box in a wooden box PPP-B-621 (size 8 1/2 x 8 1/2 x 14 7/8 inches I.D.). Close and seal box in accordance with PPP-B-621.

5.1.1.2 Option B. NSN 1375-01-193-2976 M131.

5.1.1.2.1 Unit package. Place ten (10) caps in a folding paperboard box complete with half-slotted partitions or similar die-cut, folded or combination folded and die-cut inserts assembled to form individual cells or separations in a 5 x 2 pattern. The box and cells shall be contructed of minimum .020 inch thick paperboard and shall conform to PPP-B-566 Style II, Variety 1, Type A, Class A (box size 1.6 x .75 x 2.5 inches). Place each box (10 caps) in a barrier bag conforming to MIL-B-117, Type I or II, Class E; exhaust all air from the bag and close by heat sealing in accordance with the requirements of MIL-P-116.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the current version before use.

5.1.1.2.2 Intermediate package. Place 24 unit packs between top and bottom cushions 10 inch by 3.12 inch by 1.25 inch thick PPP-C-1120, Type II, Class B, and add side fillers 9.5 inch by 6.25 inch and end fillers 6.25 inch by 3.25 inch PPP-F-320, Type CF, class domestic variety SW grade 175 to obtain a tight pack and top fillers as required (10.0 inch by 3.12 inch) in a M19A1 metal container.

5.1.1.2.3 Exterior package. Place two (2) M19A1 metal boxes (480 caps) in a wooden box (MIL-B-48024, Type 2, Class 2, Gd A, Size 9.5 x 13.25 x 9.75 inches I.D.). Line the box with one inch thick (minimum) polypropylene (PPP-C-1797, Type 1 material or equal) between the metal boxes and the exterior wooden box. Place a fiberboard separator (PPP-F-320, com. gd. size 3.75 x 11 x 7 1/8 inches) between the metal boxes. Box shall be closed in accordance with instructions contained in the appendix of the box specification.

5.2 Marking. Marking will be in accordance with MIL-STD-129 and drawing 8796522. All letters shall be upper case; letter size of 1/8 inch (min.) for unit packaging and bags, and 1/4 inch for intermediate pack. Marking may be applied to cartons by labeling, printing or stamping. Labels will not be applied to metal or wooden boxes or bags.

5.2.1 Level A.

5.2.1.1 Option A. NSN (SPI/TPO) 1375-01-057-6439-M131.

5.2.1.1.1 Unit package. Each unit box and barrier bag shall be labeled, printed or stamped with the following information: "1375-M131" - "10 Caps, Blasting Non-Electric, M7, Lot No. _____."

5.2.1.1.2 Intermediate package. Each barrier bag shall be printed or stamped in 1/4 inch (min.) letters with the following information: "NSN: 1375-01-057-6439 M131" - "50 Caps, Blasting, Non-Electric, M7, Lot No. _____."

5.2.1.1.3 Exterior package. Each wooden exterior package shall be marked in accordance with marking drawing 8796522 and MIL-STD-129. The DOT proper shipping name shall be "Detonators - Handle Carefully". The descriptive nomenclature shall be "100 Caps, Blasting, Non-Electric, M7".

5.2.1.2 Option B. NSN 1375 -01-193-2976-M131.

5.2.1.2.1 Unit package. Each unit box and barrier bag shall be labeled, printed or stamped with the following information: "1375-M131" - "10 Caps, Blasting, Non-Electric, M7, Lot No. _____".

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the current version before use.

5.2.1.2.2 Intermediate package. Each metal box shall be marked with the following information: "NSN: 1375-01--193-2976-M131" - "240 Caps, Blasting, Non-Electric, M7, Lot No. _____".

5.2.1.2.3 Exterior package. Each wooden exterior package shall be marked in accordance with Drawing 8796522 and MIL-STD-129. The DOT marking shall be "Detonators - Handle Carefully". The descriptive nomenclature shall be "480 Caps, Blasting, Non-Electric, M7". "C.O.E. CNN AY84-041 Applies" must be annoted on all shipping papers. Each wooden exterior package shall be marked on the bottom on the box "MIL-C-45469".

6. NOTES

6.1 Intended use. The Blasting Caps covered by this specification are intended for detonating compressed TNT, compressed nitrostarch, Composition C-3 and Composition C-4 explosives.

6.2 Ordering data. See MIL-A-48078.

6.3 Data cards. (See MIL-A-48078) Distribution of data cards shall include the following: Commander, US ARDC, ATTN: AMSMC-QAT-M(D), Dover, NJ 07801-5001.

6.4 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, US ARDC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraph number.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Center (ARDC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDC.

6.6 International standardization agreement. Certain provisions of this specification, sections 3, 4 and 5, are the subject of international standardization agreement STANAG 2818. When amendment, revision or cancellation of this specification is proposed which effects or violates the international agreement concerned, the preparing activity will take appropriate action through international standardization channels including departmental standardization offices, if required.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.

6.7 Check test for possible deterioration of blasting caps. The following test is designed to prevent blasting caps that have deteriorated from being assembled into major ammunition items. The test shall be performed on blasting caps from each lot which have been stored under normal conditions for more than two (2) years or under adverse conditions for any period of time. If the specification for the ammunition item into which blasting caps are assembled does not require that the check test be performed, the Contracting Officer should insert in the contract a provision for the performance of the check test. The Contracting Officer will arrange for the contractor to be reimbursed for expense incurred in his performance of the check tests for possible deterioration. Blasting caps shall be selected from each lot and tested as per 6.7.1.

6.7.1 Functioning. Fifty (50) blasting cap assemblies shall be selected from each lot and subjected to the functioning test as specified in 4.5.3. The lot shall be rejected if three (3) or more blasting caps fail to comply with the functioning requirements specified in 3.5. Test equipment shall be as specified in 4.4.4.

6.8 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A308)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:06Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragrapn of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARMAMENT RESEARCH & DEVELOPMENT CENTER
ATTN: AMSMC-QA
DOVER, NJ 07801 5001

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:06Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-C-45469E	CAP, BLASTING, NON-ELECTRIC: M7 LOADING, ASSEMBLING AND PACKING

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
	☐ USER
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426

PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026l0-22T03:06Z
Check the source to verify that this is the currentversion before use.