MILITARY SPECIFICATION

CAP, BLASTING, NON-ELECTRIC: M7
LOADING, ASSEMBLING AND PACKING

This Amendment forms a part of Military Specification MIL-C-45469E(AR), dated 13 January 1986, and is approved for use by the US Army, Armament, Munitions and Chemical Command and is available for use by all the Departments and Agencies of the Department of Defense.

PAGE 21

5: Delete Section 5 in its entirety and substitute the following:

"5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level A.

5.1.1.1 Option A. NSN: (SPI/TPO) 1375-01-057-6439-M131.

5.1.1.1.1 Unit package. Place ten (10) caps in a folding box conforming to PPP-B-566, Variety I, Style II, Type D, Class A (size 1 7/8 inches by 3/4 inches by 2 1/2 inches). The caps shall be separated in a 5 x 2 pattern using half slotted die-cut or folded inserts that provide individual cells made from chipboard, conforming to UU-C-282 or equivalent. The box shall be closed by applying a strip of tape conforming to UU-T-106, 1 inch wide by 2 inches long, across the top and bottom of the carton. Enclose each box (10 caps) in a barrier bag conforming to MIL-B-117, Style I, Type I, Class F (size 3 x 6). Remove air and heat seal in accordance with MIL-P-116.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5.1.1.1.2 Intermediate packaging. Place five (5) unit packs (bags) in a waterproof bag conforming to MIL-B-117, Style 2, Type 1, Class B or equivalent. Exhaust all air and heat seal in accordance with MIL-P-116.

5.1.1.1.3 Exterior package. Place two (2) bags (100 caps) into a fiberboard box (PPP-B-636 VC3 Size 8 x 8 x 14 inches I.D.). Cushion between the intermediate pack and exterior fiberboard box with one inch thick (minimum) polypropylene Type 1, PPP-C-1797 or equivalent material. Add filler(s)/ pad(s) as required to obtain a tight pack. Place fiber box in a wooden box PPP-B-621 (size 8 1/2 x 8 1/2 x 14 7/8 inches I.D.). Close and seal box in accordance with PPP-B-621.

5.1.1.2 Option B. NSN: 1375-01-193-2976-M131.

5.1.1.2.1 Unit package. Place ten (10) caps in a folding paperboard box complete with half-slotted partitions or similar die-cut, folded or combination folded and die-cut inserts assembled to form individual cells or separations in a 5 x 2 pattern. The box and cells shall be constructed of minimum .020 inch thick paperboard and shall conform to PPP-B-566, Style II, Variety I, Type A, Class A, or shall conform to PPP-F-320, Type SF, either class (box size 1.6 x .75 x 2.5 inches). Place each box (10 caps) in a barrier bag conforming to MIL-B-117, Type I or II, Class F; exhaust all air from the bag and close by heat sealing in accordance with the requirements of MIL-P-116.

5.1.1.2.2 Intermediate package. Place 24 unit packs between top and bottom cushions 10 inch by 3.12 inch by 1.25 inch thick PPP-C-1120, Type II, Class B, and add side fillers 9.5 inch by 6.25 inch and end fillers 6.25 inch by 3.25 inch PPP-F-320, Type CF, class domestic variety SW grade 175 to obtain a tight pack. Add top fillers, 10.0 inch by 3.12 inch, as required in an M19A1 metal container.

5.1.1.2.3 Exterior package. Place two (2) M19A1 metal containers (480 caps) in a wooden box (MIL-B-2427, Type 2, Class 2, Grade A, Size 9.5 x 13.25 x 9.75 inches I.D.). An alternate plywood top and bottom (see 5.1.1.2.3.1) may be used with a 1/2 inch thick top and 3/8 inch thick bottom using hardware fasteners of MS 35492-28 or MS 35494-32 or equivalent. Line the exterior wooden box with one inch thick (minimum) polypropylene (PPP-C-1797, Type 1, or equivalent between the exterior wooden box and the metal boxes. Place a fiberboard separator (PPP-F-320, commercial grade, Size 3.75 x 11 x 7.125 inches) between the metal boxes. Box shall be closed in accordance with instructions contained in the appendix of the specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5.1.1.2.3.1 Plywood. Group B or C, container grade standard interior with exterior glue shall be used. If specified grade is not available, a better exterior grade may be substituted.

5.1.1.2.3.1.1 Grades A, B and C boxes. Top and bottom panels. Plywood utilized for top and bottom panels shall meet the standard requirements outlined in Department of Commerce Publications PS-1 for Group B plywoods and CS-157 for Group C plywoods after cutting to size.

5.1.1.3 Option C. NSN 1375-01-315-1335-M131.

5.1.1.3.1 Packaging.

5.1.1.3.1.1 Level A. Level A packaging shall be in accordance with Drawing 12913876.

5.1.1.3.1.2 Level B. Level B packaging shall be the same as Level A.

5.1.1.3.1.3 Level C. Level C packaging shall be the same as Level A.

5.1.1.3.2 Packing.

5.1.1.3.2.1 Level A. Level A packing shall be in accordance with Drawing 12913877.

5.1.1.3.2.2 Level B. Level B packing shall be the same as Level A.

5.1.1.3.2.3 Level C. Level C packing shall be the same as Level A.

5.1.1.4 Option D. NSN

5.1.1.4.1 For non-tactical Level B shipments of ten (10) blasting caps the packaging shall be in accordance wth Drawing 12934700, and the packing shall be in accordance with Drawing 12934703.

5.2 Marking.

5.2.1 Level A.

5.2.1.1 Option A. NSN (SPI-TPO) 1375-01-057-6439-M131.

Source: https://assist.dla.mil -- Downloaded: 202610-22T03:05Z
Check the source to verify that this is the currentversion before use.

5.2.1.1.1 Unit package. Each unit box and barrier bag shall be labeled, printed or stamped with the following information: "1375-M131" - "10 Caps, Blasting Non-Electric, M7, Lot No. ".

5.2.1.1.2 Intermediate package. Each barrier bag shall be printed or stamped in 1/4 inch (min.) letters with the following information: "NSN: 1375-01-057-6439-M131" - "50 Caps, Blasting, Non-Electric, M7, Lot No. ".

5.2.1.1.3 Exterior package. Each wooden exterior package shall be marked in accordance with marking Drawing 8796522 and MIL-STD-129. The proper shipping name and identification number shall be "DETONATORS, NON-ELECTRIC UN 0029". The descriptive nomenclature shall be "100 Caps, Blasting, Non-Electric, M7". Mark UN POP marking on the opposite side of the box as the descriptive nomenclature as follows:

" (u / n) 4Cl/Y*/S** "
USA/DOD/AYD

At * enter the gross weight when packed in kilograms, rounded up to the next whole number, and at ** enter the last two digits of the year packed.

5.2.1.2 Option B. NSN 1375-01-193-2976-M131.

5.2.1.2.1 Unit package. Each unit box and barrier bag shall be labeled, printed or stamped with the following information: "1375-M131" - "10 Caps, Blasting Non-Electric, M7, Lot No. ".

5.2.1.2.2 Intermediate package. Each metal box shall be marked with the following information: "NSN: 1375-01-193-2976-M131" - "240 Caps, Blasting, Non-Electric, M7, Lot No. ".

5.2.1.2.3 Exterior package. Each wooden exterior package shall be marked in accordance with marking Drawing 8796522 and MIL-STD-129. The proper shipping name and identification number shall be "DETONATORS, NON-ELECTRIC UN 0029". The descriptive nomenclature shall be "480 Caps, Blasting, Non-Electric, M7". "C.O.E. CNN AY84-041 Applies" must be annotated on all shipping papers. Each wooden exterior package shall be marked on the bottom on the box "MIL-C-45469". Mark UN POP marking on the opposite side of the box as the descriptive nomenclature as follows:

" (u / n) 4Cl/Y*/S** "
USA/DOD/AYD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

At * enter the gross weight when packed in kilograms, rounded up to the next whole number, and at ** enter the last two digits of the year packed.

5.2.1.3 Option C. NSN 1375-01-315-1335-M131.

5.2.1.3.1 Level A. Level A marking shall be in accordance with Drawings 12913876 and 12913877.

5.2.1.3.2 Level B. Level B marking shall be the same as Level A.

5.2.1.3.3 Level C. Level C marking shall be the same as Level A.

5.2.1.4 Option D. NSN

5.2.1.4.1 Marking for Level B non-tactical shipments of ten (10) blasting caps shall be in accordance with Drawings 12934700 and 12934703.*

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A511)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.