INCH-POUND
MIL-DTL-45469F
07 March 2024
SUPERSEDING
MIL-C-45469E
AMENDMENT 1
7 December 1993
Revision E
13 January 1986

DETAIL SPECIFICATION

CAP, BLASTING, NON-ELECTRIC: M7
LOADING, ASSEMBLING AND PACKING

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements, examinations, and tests for delivery of one type of blasting cap designated as Blasting Cap, Non-Electric: M7 (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4 and 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, and 5 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

Comments, suggestions, or questions on this document should be addressed to: Commander, U.S. Army CCDC, ATTN: FCDD-ACE-QSA, Picatinny Arsenal, New Jersey 07806-5000, or emailed to usarmy.pica.devcom-ac.list.ardec-stdzn-branch@army.mil. Since contact information can change, you may want to verify the currency of this information using ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 1375

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-C-43438	-	Crimper, Blasting Cap, M2, Plier Type W/Fuse Cutter
MIL-DTL-15011	-	Pallets, Material Handling, Wood Post Construction, 4 Way Entry
MIL-DTL-45144	-	Fuse, Blasting, Time - M700, and Dummy Fuse, Blasting, Time - Inert Loading, Assembling and Packing

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-331	-	Fuzes, Ignition Safety Devices and Other Related Components, Environmental and Performance Tests for
MIL-STD-650	-	Explosive; Sampling, Inspection and Testing
MIL-STD-1168	-	Ammunition Lot Numbering and Ammunition Data Card
MIL-STD-1916	-	DOD Preferred Methods for Acceptance of Product

(Copies of these documents are available online at https://quicksearch.dla.mil/).

COMMERCIAL STANDARDS

A-A-55057	-	Panels, Wood/Wood Based; Construction and Decorative

2.2.2 Other Government documents. The following other Government documents, drawings and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

US ARMY DEVCOM AC DRAWINGS

ACV00561	-	Unit Load Marking for Shipment and Storage, Ammunition and Explosives
8830948	-	Cap Blasting, Non-Electric, M7 Assembly
8830949	-	Cup
12913876	-	Packing and Marking for Box, Wirebound for Cap Blasting: Non-Electric, M7
12913877	-	Packing and Marking for M19A1 Ammunition Box for Cap Blasting: Non-Electric, M7
13091258	-	Packing and Marking for Box, Wirebound for Cap, Blasting: Electric, M6 (MYCO Foam)
13091259	-	Packing and Marking for M19A1 Ammunition Box, for Cap, Blasting: Electric, M6 (MYCO Foam)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

13105950	-	MYCO Foam
19-48-4116	-	Unitization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallets
19-48-4116/121Q	-	Unitization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallets
QS 13075109	-	Pad, End
QS 13075110	-	Support, Top/Bottom
QS 13075111	-	Pad, End
QS 13075112	-	Support, Bottom
QS 13075113	-	Support, Top

(Copies of these documents may be requested online at usarmy.pica.pica.ccdc-ac.list.drawing-requested-help-desk@mail.mil)

2.3 Non-Government standards and publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents are those cited in the solicitation or contract.

ASTM INTERNATIONAL

ASTM E300	-	Standard Practice for Sampling Industrial Chemicals

(Copies of these documents are available from https://www.astm.org/.)

2.4 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Required inspections.

3.1.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection in accordance with 4.2.

3.1.2 Conformance. A sample shall be subjected to conformance inspection in accordance with 4.3.

3.2 Materials. Materials and parts shall be in accordance with the applicable drawings, specifications, and standards. All energetic materials used in components or end items shall have been manufactured not greater than five years from the date of loading.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

3.3 Assembly. The assembly shall comply with all requirements specified on Drawing 8830948, and with all requirements specified in applicable specifications and standards.

3.4 Moisture content.

a. Lead azide. The moisture content of the lead azide at the loading station, at the time of loading the blasting caps, shall not exceed 0.50 percent

b. Ignition mix. The moisture content of the ignition mix at the loading station, at the time of loading the blasting caps, shall not exceed 0.30 percent

3.5 Cold conditioning. The M7 blasting cap shall not exhibit evidence of cracking or breakage in the cup, charge loosened or drop out and shall function in accordance with section 3.7 after being subjected to not less than 72 hours of temperature conditioning at not greater than -50˚C.

3.6 Impact resistance. The cap shall not detonate, the cup shall not crack or break, or the charge loosen or drop out when subjected to impact testing.

3.7 Output functioning. The blasting cap shall be initiated by M700 Time Fuze and shall detonate completely while not creating a dent less than 0.010 inches when subjected to MIL-STD-331 Test D4 (Dent Block Method) utilizing a steel dent block.

3.8 Ammunition lot numbering. Lot numbers shall be assigned in accordance with MIL-STD-1168.

3.9 Workmanship. All parts and assemblies shall be clean and free of burrs, sharp edges, unblended radii, cracks, gouges, surface defects, chips, dirt, grease, and oil (except where specifically required), corrosion, and other foreign matter. The cleaning method shall not be injurious to any of the parts or assembly nor shall they be contaminated by the cleaning agents. Exterior surface coating shall be continuous except for a few light scratches not exposing the base material. All required markings and stamping shall be neat and sharply defined. Required packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

TABLE I. Requirements/verification cross reference matrix.

Method of verification 1 – Analysis 2 – Demonstration 3 – Examination 4 – Test						Classes of verification A – First article B – Conformance		
Section 3 Requirement	Description	Verification Methods				Verification Class		Section 4 Verification
		1	2	3	4	A	B	
3.1.1	First article	X		X	X	X		4.2
3.1.2	Conformance	X		X	X		X	4.3
3.2	Materials	X		X	X	X	X	4.4
3.3	Assembly	X		X	X	X	X	4.3.4.2
3.4	Moisture content	X		X	X	X	X	4.4.1
3.5	Cold conditioning			X	X	X		4.4.2
3.6	Impact resistance			X	X	X	X	4.4.3
3.7	Output functioning			X	X	X	X	4.4.4
3.8	Lot numbering			X		X	X	4.4.6
3.9	Workmanship			X		X	X	4.3.4.1 thru 4.3.4.7
5.1.1	Packing and marking ammo can			X		X	X	4.3.4.4, 4.3.4.5
5.1.2	Packing and marking wirebound box			X		X	X	4.3.4.6 thru 4.3.4.8
5.2	Moisture content			X		X	X	4.4.5
5.3	Packaging workmanship			X		X	X	4.3.2.4 thru 4.3.2.8
5.4	Unitization			X		X	X	4.3.4.8

4.1 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see paragraph 4.2).
b. Conformance inspection (see paragraph 4.3).

4.2 First article inspection. When specified, a sample of M7 blasting caps shall be subjected to first article inspections in accordance with Table II. The sample shall be obtained from the first production lot which has been produced by the contractor using the same production processes, procedures and equipment as shall be used in fulfilling the contract. All materials shall be obtained from the same sources of supply as shall be used in regular production.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.2.1 First article rejection. If any assembly, component or test specimen fails to comply, the sample and test shall be rejected.

Table II. First article acceptance tests and inspections.

Examination or test	Drawings	Quantity	Requirement paragraph	Inspection method reference
Cup	8830949	25	3.2	4.3.3 and 4.3.4.1
Assembly	8830948	60	3.3	4.3.4.2
Moisture content		60	3.4	4.3.3
Cold conditioning		20	3.5	4.4.2
Impact resistance	8830948	40	3.6	4.4.3
Output functioning	8830948	60 1/	3.7	4.4.4
Ammunition lot numbering		6 2/	3.8	4.4.6
Packing and marking ammo can	12913876 12913877	6 3/	5.1.1	4.3.4.4 thru 4.3.4.5 and 4.4.5
Packing and marking wirebound box	12913876	2 3/	5.1.2	4.3.4.6 thru 4.3.4.7
Unitization	19-48-4116/121Q		5.4	4.3.4.8
Packaging Workmanship	12913876 12913877	2 3/	5.3	4.3.4.4 thru 4.3.4.8

Notes:
1/ Same 60 used for impact resistance. 20 caps shall be pulled from the 60 to use for cold conditioning only. If any assembly fails to comply with the specified requirements, it shall be classed defective and the sample shall be rejected.
2/ 10 caps per ammo can.
3/ 60 caps in 6 ammo cans is 1 ½ wirebound boxes, so make one full box and light box

4.3 Conformance inspection.

4.3.1 Inspection lot formation. Inspection lots shall conform to the requirements of MIL-STD-1916. In addition, each lot shall contain:

a. Cups from not greater than one supplier.
b. RDX from not greater than one lot.
c. Lead styphnate from not greater than one lot.
d. Lead azide of the same type from not greater than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant.

4.3.2 Classification of characteristics. Unless otherwise specified in the Conformance Inspection, sampling plans for major and minor defects shall be in accordance with MIL-STD-1916, Verification Level IV for Major defects and Verification Level II for Minor defects. Critical Characteristics shall be inspected 100% followed by a Verification Level VII inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.3.3 Sampling for lead azide or ignition mix. A sample of lead azide or ignition mix, as applicable, shall be selected in accordance with ASTM E300 from that quantity used in each shift of loading production up to a maximum of a daily 10 hour shift. A composite sample shall not be used. If the moisture content of a sample exceeds the requirement and loading has not begun, the lead azide or ignition mix represented by the sample shall be rejected. If components have been loaded with lead azide or ignition mix containing excessive moisture, the remaining unloaded lead azide or ignition mix and the loaded components shall be rejected.

4.3.4 Rejection. If any assembly, subassembly, material, or component fails to comply with the conformance inspection requirements, the lot from which the sample was taken shall be rejected.

4.3.4.1 Cup.				Drawing Number 8830949 Next Higher Assembly 8830948
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical	None defined			
Major				
101	Inside diameter below datum diameter at mouth, maximum (max.)	IV	3.2	Gage
102	Thickness of bottom, minimum (min.)	IV	3.2	Gage
Minor				
201	Length to datum diameter at mouth	II	3.2	Gage
202	Inside diameter near bottom	II	3.2	Gage
203	Workmanship	II	3.9	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.3.4.2 Assembly.				Drawing Number 8830948 Next Higher Assembly -----
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical				
1	Cup split or cracked exposing charge or evidence of explosive leakage	100% + VII	3.3	Visual
2	Loose or compacted powder on inner or outer wall of cup	100% + VII	3.3	Visual
Major				
101	Depth to charge, min.	IV	3.3	Gage
102	Overall length, max.	IV	3.3	Gage
Minor			3.3	
201	Outside diameter at open end, max.	II	3.3	Gage
202	Outside diameter at closed end, max.	II	3.3	Gage
203	Workmanship, except as defined in Critical above	II	3.9	Visual

4.3.4.3 M7 non-electric blasting cap tests.				Drawing Number 8830948 Next Higher Assembly -----
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical				
1	Blasting cap functions on impact	24 1/	3.6	4.4.3
Major				
101	Crack or split in cup (charge not exposed)	24 1/	3.6	4.4.3
102	Loose or dislodged charge	24 1/	3.6	4.4.3
103	Blasting cap fails to perforate lead disk	24 1/	3.6	4.4.3
104	Blasting cap fails to fire	24 1/	3.6	4.4.3
105	Output functioning	24 1/	3.7	4.4.4
Minor	None defined			
Notes: 1/ Same 24 samples used for impact resistance shall be used in the output testing				

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.3.4.4 Packing and marking for M19A1 ammunition box (prior to closing).				Drawing Number 12913877 130901259
				Next Higher Assembly 12913876 13091258
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical	None defined			
Major				
101	Any packing component missing or misassembled	II	5.1.1	Visual
102	Packaging material moisture content incorrect	4.4.5	5.2	4.4.5
Minor				
201	Number of inner packages incorrect	I	5.1.1	Visual
202	Workmanship	I	5.3	Visual

4.3.4.5 Packing and marking for M19A1 ammunition box.				Drawing Number 12913877 13091259
				Next Higher Assembly 12913876 13091258
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical	None defined			
Major				
101	Packing or cushioning material interferes with seal of lid	II	5.1.1	Visual
102	Metallic seal missing, loose, not embossed, or not installed correctly	II	5.1.1	Visual
Minor				
201	Marking missing, incorrect, or unidentifiable	I	5.3	Gage
202	Workmanship	I	5.3	Gage

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.3.4.6 Packing and marking for box, wirebound (prior to closing).				Drawing Number 12913876 13091258
				Next Higher Assembly -----
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical	None defined			
Major				
101	Package missing or improperly positioned	II	5.1.2	Visual
102	Separators and fillers not present or improperly positioned	II	5.1.2	Visual/manual
Minor				
201	Workmanship	I	5.3	Visual

4.3.4.7 Packing and marking for box, wirebound.				Drawing Number 12913876 13091258
				Next Higher Assembly -----
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical	None defined			
Major				
101	Wire binding not properly secured	II	5.1.2	Visual
102	Metallic seal missing, loose, not embossed, or not installed correctly	II	5.1.2	Visual
Minor				
201	Marking missing, incorrect, or unidentifiable	I	5.3	Visual
202	Workmanship	I	5.3	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.3.4.8 Unitization.				Drawing Number 19-48-4116/121Q Next Higher Assembly ----------
	Examination	Conformance Criteria	Requirement Paragraph	Paragraph reference/ Inspection Method
Critical	None defined			
Major				
101	Pallet not in accordance with requirements	1/	5.4	1/
102	Pallet markings missing, incorrect or not located properly	II	5.4	Visual
103	Boxes incorrectly oriented or positioned on pallet	II	5.4	Visual
104	Filler assembly, if required, not made, treated, or marked correctly	II	5.4	Visual
105	Strapping incorrectly routed, not located correctly or material incorrect	II	5.4	Visual
106	Unit load not tightly strapped or any strap loose	II	5.4	Visual
107	Strapping seal not properly crimped	II	5.4	Visual
108	Wood preservative marking is missing, incorrect, or in incorrect location on pallet.	II	5.4 and 5.3	Visual
109	Heat treatment stamp missing, incorrect, or in incorrect location on pallet.	II	5.4 and 5.3	Visual
Minor				
201	Evidence of poor workmanship	I	5.3	Visual
Note: 1/: Inspection shall be in accordance with MIL-DTL-15011 .				

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.4 Test methods and procedures.

4.4.1 Moisture content of lead azide or ignition mix.

a. Lead azide. The moisture content of the lead azide shall be determined in accordance with Method 101.5 of MIL-STD-650, except that a two gram sample shall be tested and the dish shall be covered with a sheet of polytetrafluoroethylene.

b. Ignition mix. The moisture content of the ignition mix shall be determined in accordance with Method 101.5 of MIL-STD-650, except that a two-gram sample shall be tested and the dish shall be covered with a sheet of polytetrafluoroethylene.

4.4.2 Cold conditioning. Perform not less than 72 hours of temperature conditioning on the bare M7 cap. Verify the M7 is able to withstand cold conditioning and shall not exhibit evidence of cracking or breakage in the cup, charge loosened or drop out and shall function in accordance with 4.4.4.

4.4.3 Impact resistance. Impact resistance shall be determined in accordance with the following procedure and equipment.

4.4.3.1 Apparatus and set-up procedures. The apparatus shall consist of the following:

a. Galvanized iron pipe. 1-9/16 inch inner diameter x 7 feet long.
b. One pulley to fit the rope.
c. Rope, length to suit.
d. Anvil, steel 12 inches square x 3 inches thick, minimum.
e. Weight, cylindrical, steel, 1-3/8 inch diameter x 14 inches long, weighting 5.3 pounds approximately, with an eyelet at one end for rope attachment.
f. Plywood, dry, ¾ inch thick x approximately 4 inches square, in accordance with A-A-55057
g. Pin, steel, ½ inch diameter x 3-1/2 inches long, eyelet at one end.
h. Clamps (as required).

4.4.3.2 Apparatus assembly. Erect the galvanized pipe so that its axial center is perpendicular to the center of the 12 inch square surface of the anvil and the bottom of the pipe is 3-1/2 inches above the anvil. Drill two 9/16 inch diameter holes in the pipe diametrically opposite each other at a height of 48-3/4 inches above the anvil. Place the 4 inch square piece of plywood on the anvil so that the centers of the anvil and plywood are common. Securely clamp the plywood to the steel anvil in two places minimum, diametrically opposite each other. If the plywood is not replaced after each item tested, not more than ten (10) drops shall be made in the same spot. Drill a 9/32 inch diameter hole 2 inches deep in the eyelet end of the cylindrical steel weight. The hole shall be located so that the eyelet does not interfere with insertion and removal of the blasting caps. Attach a piece of rope (length to suit) to the eyelet in the steel pin and insert the pin in the 9/16 inch hole in the pipe. Locate the other end of the rope behind a suitable

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

barricade. Attach a rope approximately 15 feet long to the eyelet in the cylindrical steel weight and lower the weight into the pipe until it rests on the pin. Mount a pulley above the pipe so that when the rope is threaded through the pulley, the weight after dropping, may be withdrawn to permit insertion or removal of the blasting caps. The test anvil shall be rigidly supported.

4.4.3.3 Procedure. The blasting caps shall be tested for impact resistance in the following manner: Cover the open end of the blasting cap with tape. Insert the blasting cap, taped end first into the hole in the top of the steel weight. Tape the blasting cap to the weight to prevent it from bouncing during the test. Insert the weight in the pipe and lower it until it rests on the steel pin that is inserted in the 9/16 inch holes in the pipe. Pull the pin from behind the barricade to allow the weight to drop and impact on the plywood. Retract the weight by means of the rope, remove the blasting cap from the weight and examine for compliance with the requirements. After the drop test, the blasting caps shall be subjected to output functioning.

4.4.4 Output functioning. Perform output testing per MIL-STD-331 Test D4 (Dent Block Method) on the blasting caps. The dent block shall be made of grade 1018 steel per ASTM A108, have a Rockwell Hardness between B70-B95, and be 1.25 x 1.25 x 0.625 inches in size. A six inch length minimum of M700 Time Blasting Fuse complying with MIL-DTL-45144 shall be inserted in the open end of the blasting cap cup to a depth to contact the explosive charge. An M2 blasting cap crimping tool complying with MIL-C-43438 shall be used to crimp the Time Fuse in the cup. Secure each blasting cap perpendicularly to a dent block using a test fixture, which only contacts the blasting cap at or above the crimp and also does not create any confinement on the blasting cap. The lot shall be rejected if any blasting cap has a crack or split in the cup, fails to fire, does not function completely, has loose or dislodged charge or if any dent block measurement does not meet the measurement criteria.

4.4.5 Packaging material moisture content. At the start of each production day, three (3) samples of all paper packaging material contained within the barrier bag (setup box) shall be randomly selected and subjected to moisture content analysis. No less than ten (10) grams of each sample shall be accurately weighed and placed in a tared weighing dish. Each dish and contents shall be weighed and placed in an oven and dried at 100± 2°C for 2 hours. Each dish and contents shall be cooled in a desiccator for a minimum of 15 minutes and weighed. The loss in weight shall be calculated as percent moisture in each sample. If any sample does not meet the moisture requirement, the sample(s) and that production day's packaging material shall be rejected.

4.4.6 Ammunition lot numbering. Lot numbers shall be assigned and visually inspected in accordance with MIL-STD-1168.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging and Marking

5.1.1 Packing and marking for M19A1 ammunition box. Packing and marking shall be in accordance with Drawing 12913877 and 13091259 where applicable.

5.1.2 Packing and marking for wirebound box. Packing and marking shall be in accordance with Drawing 12913876 and 13091258 where applicable.

5.2 Moisture content. The packing materials shall be in accordance with the moisture content requirements of Drawing 12913877 and 13091259 where applicable

5.3 Packaging workmanship. All parts, subassemblies, and assemblies shall be free of defects such as cracks and tears, shall be clean by being free of dirt, grease, oil (except where specifically required), rust, salt deposits, corrosion, and other foreign matter.

5.4 Unitization

5.4.1 Pallet Unitization Procedures. Loaded pallets should be in accordance with 19-48-4116 and 19-48-4116/121Q

5.4.2 Unitized Load Marking. Unitized load markings should be in accordance with ACV00561

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. M7 Non-Electric Blasting Caps are intended for initiating all past and current fielded and developmental military explosives.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Provisions for submission/resubmission of first article samples.
c. Acceptance and description sheet - Acceptance and description sheets should be prepared for each lot in accordance with MIL-STD-1171 (see 6.4).
d. Quantity required and delivery schedules.
e. Type and grade required (see 1.2 and 3.3).
f. Levels of preservation and packing (see 5.1).
g. Item hazard classification.
h. Limitation on the use of recycled RDX (see 6.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment designs for approval. Equipment designs should be submitted per the Contract Data Requirements Lists (DD Form 1423).

6.4 Consideration of data requirements. When this specification is used in a procurement contract which incorporates DD Form 1423, contract data requirements list, acceptance and description sheets (for explosives) are required for each lot. These sheets should be prepared and submitted by the contractor in accordance with MIL-STD-1171 or otherwise as directed by the contract.

6.5 Technical agency. Picatinny Arsenal is the technical agency that is responsible for the preparation and revision of the specification. All correspondence to the Technical Agency should be submitted through the contracting officer to: DEVCOM AC, ATTN: FCDD-ACE-QMG, Picatinny Arsenal, NJ 07806-5000.

6.6 Approval of equivalent test methods. Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: DEVCOM AC, ATTN: FCDD-ACE-QMG, Picatinny Arsenal, NJ 07806-5000. This description should include but not be limited to the procedures used, the accuracy and precision of the method, test data to demonstrate the accuracy and precision and drawings of any special equipment required.

6.7 Submission of alternative conformance inspection provisions. Unless otherwise specified in the contract, proposed alternative conformance inspection provisions should be submitted by the contractor for evaluation by the Technical Agency responsible for preparation of this specification. (See 6.5)

6.8 Critical classification rationale.

Table III. Critical classification rationale.

Paragraph	Critical callouts	Critical rationale
4.3.4.2	C1 – Cup split or cracked exposing charge or evidence of explosive leakage	The blasting cap cup being split or cracked, explosive charge being exposed, or there being evidence of explosive leakage may result in unintended detonation of cap during handling or crimping. The explosive contained within the blasting cap are highly sensitive to impact, flame, and static discharge. These defects can lead to injury and death during handling and usage.
4.3.4.2	C2 – Loose or compacted powder on inner or outer wall of cup	Loose or compacted powder on exterior or interior walls of the cup may result in unintentional detonation of cap during handling or crimping. These defects can lead to injury and death during handling and usage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.

4.3.4.3	C1 – Blasting cap functions on impact	Blasting caps functioning on impact is unintentional detonation that can cause injury and death.

6.9 Incorporated changes. ECP R24B2002 provides documentation for noted changes.

6.10 Subject term (key word) listing.

Explosive compositions
Research department explosive
Energetic material

6.11 Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

6.12 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

CONCLUDING MATERIAL

Custodians:
Army-AR
Navy-OS
Air Force-170

Preparing activity:
Army-AR

(Project 1375-2022-001)

Review Activities:
Air Force-70

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:05Z
Check the source to verify that this is the current version before use.