MILITARY SPECIFICATION

DETONATOR, STAB, M46
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-D-45483B (MU), dated 15 April 1965.

Page 1

Add the following Preamble underneath the title: "This specification is approved by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense."

Page 4

4.2.1b: Delete in its entirety and substitute the following: 4.2.1b Lead azide of the same type from not more than two lots produced by the same manufacturer in accordance with the same specification and same specification revision and which have subsequently been subjected to uniformly controlled drying and operating conditions at the loading plant."

Page 9

4.2.3.4.1: Delete in its entirety and substitute the following: "4.2.3.4.1 Sensitivity (see 3.5.1) - Major defect - Code No. 09001. - A sample of three hundred and fifteen (315) detonators shall be randomly selected from each lot. If three or more detonators fail to comply with the specified requirements, the lot shall be rejected. If one or two defectives occur, a second sample of 315 detonators shall be selected and tested. If, in the combined first and second sample, a total of four (4) or more defectives occur, the lot shall be rejected. The test shall be performed as specified in 4.3.5.1 using test equipment specified in 4.2.4."

Custodian:
Army - AR

Preparing Activity:
Army - AR

Project No: 1375-A204

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T03:08Z
Check the source to verify that this is the current version before use.